

TQB Brands Pty Ltd
PRICED PRODUCT
GUIDE



Established 1984
Trusted by Australia's
trade for more than

40 YEARS

VALID THROUGH TO SEPT. 30 2025

WORKSHOP EQUIPMENT



BORUM
INDUSTRIAL WORKSHOP EQUIPMENT

High Clearance Mobile Workshop Table

BMWST

Safe working capacity: 34kg

Adjustable working height: 960-1500mm Distance between front casters: 955mm

Caster wheel diameter: 75mm

Table top: 797L x 695W Main tray: 556L x 695W Depth at full width: 485mm Includes top tray liner

FEATURES

Height adjustable to most commercial vehicles.

Smooth rolling castors.

Extra wide legs to suit most commercial vehicles. Multi-functional top table with 2 compartments

and 8 screwdriver holes.

Top EVA mat for skid resistance.

Protective bumper for top tray.

Strong tubular steel construction.

Sturdy main support post.





34kg Capacity

THE HEIGHT
ADJUSTMENT
GIVES YOU
PLENTY OF
OPTIONS
FOR LARGER
VEHICLES
AND TRUCKS.

INDUSTRIAL QUALITY

Extra wide legs to suit most commercial vehicles.

Adjustable working height: 960-1500mm

Ball bearing castors ensure you can easily manoeuvre this mobile workshop table around the workshop. Excludes GST \$399

Inc. GST \$438.90















Safe working capacity: 2,000kg Working height: 210-900mm Cradle size: min. 385-470mm Cradle size: max. 570-470mm Adjustable tilt cradle Cradle forward tilt: 30° Cradle backward tilt: 30 Swivel castors: 100mm

Weight: 130kg

The adjustable cradle can be tilted forward or backward for optimum alignment of transmission bolt patterns and pins. Hydraulic system is protected from overload

damage.
Safety load-restraint for raising & lowering safety.
Rugged steel wheels & full swivel ball bearing





MADE FOR THE

TRADE





For full product specifications go to www.tgbbrands.com.au

Transmission Lifter SUV / 4x4 & Light Commercial

Cradle lateral adjustment: 90mm Chassis: 850L x 490W x 305Hmm Weight: 54kg

Adjustable head (forward & backward). Lateral cradle adjustment. Hydraulic system overload protection Four (4) swivel castors allow easy movement and positioning of

transmission jack.
Rugged heavy duty steel wheels with full swivel hall bearing castors User-friendly 360° rotating pump handle.

Chassis: 1160L x 685Wmm

User-friendly 360° rotating pumping handle.

Underhoist Auxiliary Stand 680KG

1198T TRADEQUIP Safe working capacity: 680kg Height: 1370-2045mm

Base diameter: 300mm

Weight: 16.5kg



FEATURES

Fast and safe technology for professional mechanics.

Heavy gauge steel frame prevents distortion or twisting. Provides partial support for components -NOT designed to support the vehicle. Foot pedal allows easy load movement and hand free operation.

Quick action adjustable height mechanism Sold individually recommended only to be used individually.



MADE FOR THE

TRADE

foot pedal





Scan code to go to our **Top Tips Transmission Lifter Guide and learn** how to extend the life of your TQB Brands equipment



Visit our webpage www.tgbbrands.com.au for instructional & pre-start videos.

Auxiliary Lifter 500KG 2058T TRADEQUIP Rated capacity: 500kg Working height: 1175-1985 mm Lifting platform size:

MADE FOR THE

TRADE

A: 362 x 362mm R: Ф 107 5mm

FEATURES This **TradeQuip "Made for the Trade"** 500kg Auxiliary Lifter is the perfect underhoist aid during remova and installation of small components

It features a mounting cradle and lift pad and a manually operated hydraulic system with smooth hydraulic lift and descent. The hydraulic system also includes a bypass system to prevent over extension and accidental overloading.

NOT INTENDED FOR SUPPORTING LOADS AND NOT INTENDED AS STAND ALONE TRANSMISSION LIFTER



Auxiliary Lifter Kit 500KG

2068T TRADEQUIP

Rated capacity: 500kg Working height: 1175-1985 mm Lifting platform size: A: 362 x 362mm B: Φ 107.5mm C: 812 X 352mm

capacity

NOT INTENDED FOR SUPPORTING LOADS AND NOT INTENDED
AS STAND ALONE

Scissor Lift Workshop Trolley 225KG

6010T TRADEQUIP

Safe working capacity: 225kg Working height: 225mm-710mm Table size: 708L x 450Wmm



FEATURES

Cradle and

Lift Pad

500kg Capacity

В

Hands free footoperated pedal Quick release hand lever for easy. controlled release. Heavy duty oilresistant nonslip ma Powder coated all parts to vehicles.



Inc. GST \$911.90

Scissor Lift Workshop Trolley 500KG

6009T TRADEQUIP

Safe working capacity: 500kg Working height: 265mm-865mm Table size: 820L x 520Wmm



FEATURES

Hands free foot-operated pedal. Quick release hand lever for easy, controlled release. Heavy duty oilresistant nonslip ma Powder coated all steel construction. Perfect for moving parts to vehicles.



Scissor Lift Workshop Trolley 300KG 6008T TRADEQUIP MADE FOR THE

Safe working capacity: 300kg Working height: 350mm-1285mm

Table size: 820L x 520Wmm Inc. GST \$1153.90

300kg

Capacity



CAPACITY 300KG

FEATURES Hands free foot-operated hydraulid Heavy duty oil-resistant nonslip m Powder coated all

steel construction. Perfect for moving parts to vehicles

Scissor Lift Workshop Trolley 450KG

6003T TRADEQUIP

Safe working capacity: 450kg Working height: 280-875mm Table size: 500 x 810mm Wheel Diameter: 125mm Dimensions: 1140L x 515W x 995Hmm FEATURES

Hands free foot-operated hydraulic pedal Quick release hand lever.

Heavy duty oil-resistant nonslip mat Powder coated all steel construction. Perfect for moving heavy parts to vehicles.









Scissor Lift Workshop Trolley 500KG

6007T TRADEQUIP

Safe working capacity: 500kg Working height: 440-1575mm Table size: 1010L x 520Wmm Wheel diameter: 150mm Dimensions: 1130L x 520W x 1260Hmm

> MADE FOR THE TRADE

FEATURES

Double Scissor High Lift. Foot-operated hydraulic pedal keeps your hands free. Quick release hand lever for easy, controlled hydraulic release. 2 locking heavy duty swivel castors All steel construction. Powder coated for extra protection Perfect for moving heavy parts to and from the vehicle.









Foldable Engine Crane 1,200KG 1001T TO TRADEQUIP

For full product specifications go to www.tqbbrands.com.au

Safe working max. capacity: 1200kg Safe working max. capacity: 1200kg
(AS1418.5 approved)
Adjustable boom: 250kg, 500kg, 750kg & 1200kg
Max. lifting height @ 1200kg: 620mm
Max. lifting height @ 250kg: 1160mm
Jib length fully retracted @ 1200kg: 1040mm
Jib length fully extended @ 250kg: 1580mm

Leg height: 190mm



FEATURES

Ideal for automotive & light engineering. Adjustable boom in four positions. Outrigger legs easily fold up for storage. Stix swivel castor wheels.

High-grade steel and built to exacting standards for quality and durability.

Short lifting chain & hook with safety latch. Lead-free paint is oil, grease and dirt-resistant for easy cleanup.



Engine Crane Load Leveller 1030 TRADEQUIP

Safe working capacity: 680kg Chain length: 300mm Chain anchor positions: 3 Engine mount positions: 4 Weight: 6kg





Safe working capacity: 500kg Extension: 1020 - 1600mm Weight: 15kg

Adjusts to fit across most car bonnets. Supports engines or transmissions. Powder coat finish.

Adjustment screw for load leveling. Supplied with short length of chain





Ram to Suit TradeQuip **1001T Engine Crane**

680kg

capacity

2008 TRADEQUIP

Safe working capacity: 8,000kg Length: 630-1135mm Ram pin hole: 16mm dia. 35mm Outside ram

Ram diameter: 80mm Clevis base pin hole: 16mm dia Clevis base: 25mm inside - 45mm outside Base width: 129mm

Weight: 10.5kg

1020T TRADEQUIP

Safe working capacity: 500kg

Extension: 1020- 1430mm



TRADE

Engine Support Bar 1021T TRADEQUIP

Safe working capacity: 500kg Extension: 1020 - 1630mm Weight: 23kg





FEATURES

Cross bar feature for improved stability and more flexibility.

Dual hook assemblies for balanced support of engines & transmissions High gloss enamel finish. Adjustment screw for leveling









Engine Support Bar FEATURES

Dual hook assemblies for balanced support Adjustable to fit across most car bonnets. Supports engines or transmissions. Rubber cushioned support legs. High gloss enamel finish. djustment screw for load leveling. Supplied with a short length of chain



MADE FOR THE



MADE FOR THE

IMPORTANT:

ENGINE DIMENSIONS

MUST BE WITHIN LEGS

OF ENGINE STAND

MADE FOR THE TRADE

FOLDING LEGS STURDY REINFORCED **NECK AND** STABLE WIDE BASE

Engine Crane 3,000KG

1193 TRADEQUIF

Safe working capacity: 3000kg Adjustable boom: 1000kg, 1500kg, 2000kg & 3000kg Maximum lifting height @ 3000kg: 1745mm Maximum lifting height @ 1000kg: 2088mm Jib length fully retracted @ 3000kg: 1100mm

This heavy duty TradeQuip "Made for the Trade³⁹ engine crane has a long stroke lifting ram, a single action pump with a maximum load capacity of 3,000kg.

Very simple to use manual hydraulic operation.
The jib extends to the desired lifting capacity of 1000kg, 2000kg or 3000kg secured by a single locking pin.

Mounted on heavy duty castor wheels for

excellent manoeuvrability around the workshop.



Engine Stand 1894T TRADEQUIP

Safe Working Capacity: 4/5/6/V6 cylinder less than 4lt Rated capacity: 500kg 360° rotating head 1190L x 850W x 1230H mm Weight: 54kg



MADE FOR THE

TRADE

WORM GEAR HEAD DRIVE STURDY REINFORCED **NECK**

IMPORTANT: ENGINE DIMENSIONS



MUST BE WITHIN LEGS OF ENGINE STAND



Engine Stand

Cylinder less than 6.2ltr

Rated capacity: 900kg

Centre height: 800mm

1110L x 530W x 900H mm

360° rotating head

Weight: 45kg

1192T TRADEQUIP

Safe working capacity: 4/5/6/V6/V8

Engine Stand

V6/V8 less than 5ltr

360° rotating head Centre height: 895mm 870L x 800W x 900H mm

Weight: 39kg

Rated capacity: 680kg

1891T TRADEQUIP

Safe working capacity: 4 cylinder &



MADE FOR THE

Engine Stand

TQES450 TRADEQUIP Safe working capacity: 4cylinder engine only

Rated capacity: 450kg 360° rotating head Centre height: 780mm 7001 x 750W x 860H mm Weight: 21kg

SPACE SAVING COMPACT DESIGN **EASY SETUP &** DISASSEMBLY













Car and 4WD Jack Stands

TRADEQUIP
the trusted brand in equipment

FEATURES

Constructed of high-grade steel & built to exacting standards for quality & durability. Lead-free paint finish is oil, grease and dirtesistant for easy cleanup.

Quick action adjustable height mechanism Double-lock safety pin design for extra safety and security. (1128T & 1148T). Welded steel frame & cast iron support.

Sold in pairs and only recommended to be used in pairs.



Incl. GST \$115.50 \$199.10 \$339.90



For full product specifications go to www.tqbbrands.com.au

Garage Jack 3,000KG Low Profile

2906T TRADEQUIP

Working load limit: 3,000kg Height: 118 - 488mm Handle length: 1400mm

Front wheels: 90mm dia 40mm width Rear castors: 60mm dia 25mm width Saddle diameter: 115mm Dimensions: 670L x 380W x170Hmm

Weight: 43kg

FEATURES

Low profile and deep reach. Heavy gauge steel construction.

1400mm long handle for deeper reach. Quick Lift Dual Pump technology Internal bypass valve overload protection Lead-free paint finish to ensure a longlasting finish and prevent rust. Paint is oil, grease and dirt-resistant. Protective foam handle cover prevents

vehicle damage.

3000kg Capacity



Safe working capacity: 25kg Tray depth: 43mm (inner) Swivel castors: 4 x 50D x16Wmm 435L x 400W x 120Hmm (castor included



FEATURES

Easy to clean finish that is oil and solven resistant and won't rust. 4 smooth-rolling swivel castors. Impact resistant polymer plastic



25kg

Capacity

Ratcheting Positioning Jacks

1054T TRADEQUIP Safe working capacity: 680kg each

Max. distance between rollers: 710mm Min. distance between rollers: 340mm Suits tyres up to: 280mm (W) Swivel castors: 100mm





pair

FEATURES

Steel construction with metal rollers Heavy duty nylon swivel castors.

2 jacks permit full 180° vehicle pivot. 4 jacks place vehicle on a 360° rolling platform Lead-free paint finish helps prevent rust and is oil, grease and dirt-resistant for easy cleanup.

Quick action adjustable height mechanism. Sold &recommended only to be used in pairs.

Easy foot-pedal lifting design.

Mechanics Creeper 130KG

1023T TRADEQUIP

Safe working capacity: 130kg 1010L x 475W x 115Hmm





Wheel Tyre Lifter 1055T TRADEQUIP

Safe working capacity: 50kg Rollers moving distance: 125mm Roller diameter & length: (D) 76.2 x 240mm Rollers push force: <4kg based on 50kg load Lifting handle force: 1kg based on 50kg load Overall height: 1380mm Overall base dimensions: 725W x 872D mm Roller working range: 100mm to 1060mm Front castors: 2(D) 75 x 24mm

Weight: 51.25kg TRULY MOBILE NO ADDITIONAL AIR LINE OR CHARGING CABLES NEEDED

Rear castor - Locking: 2(D) 75 x 24mm

FEATURES

Braked Swivel Castor Sturdy Frame to safely transport wheel around Adjustable Safety Brace



50kg



For the lifting, lowering, supporting & transporting of tyre & rim assemblies up to 50kgs & 300mm wide.

Truck Wheel Nut Wrench Torque Multiplier 8033 TRADEQUIP

1" Drive hand winder operated Trans-speed ratio: 1:56 27mm, 32mm, 33mm, 41mm wheel nut sockets Torque output: 4800Nm





Wheel Dolly Single 250KG

B250WH - B O R U M

Safe working capacity: 250kg Maximum depth: 305mm Overall height: 1000mm Weight: 14kg

FFATURES

The lifters drive screw can be

activated by an air or battery-operated ratchet wrench from

the top of the unit.

Adjustable arms Equipped with rollers for easy positioning. Stop rollers on the rear side. Francomic handle with rounded & soft

This BORUM WHEEL DOLLY is a sturdy & handy transport aid for various types of wheels (trucks, vans, utes and cars). This versatile and easy to operate piece of equipment features adjustable arms. Equipped with two wheels and an ergonomic handle, the units manoeuvrability is not hampered by the size of the wheel.





INDUSTRIAL

GUALITY

Capacity



750kg

Capacity



Safe working capacity: 750kg Lift arm spread: 533-635mm Lifting range: 60-275mm Tilt range: -2.5 to 10 degrees 787L x 1092W x 895H mm



















SOCKETS Available

BORUM BOTTLE JACK FEATURES

Capacity



Hydraulic Bottle Jacks TRADEQUIP

HEAVY DUTY One Piece Ergonomic Handle

Code

Capacity

Hydraulic Lift

Min. Height

Max. Height

Base Area

Excl. GST

Incl. GST

Adjustable Height



2012

10,000kg

125mm

70mm

205mm

400mm

124x124mm

\$109

2013

15,000kg

125mm

70mm

227mm

447mm

148x136mm

\$132

2014

20,000kg

145mm

60mm

245mm

450mm

167x156mm

\$169

\$119.90 \$145.20 \$185.90 \$141.90 \$185.90

For full product specifications go to www.tgbbrands.com.au

Machined and notished cylinders with die-cut threads provide non-abrasive leak-free, durable performance. Fabricated from hard-cast steel with heat-treated critical stress areas.

Unique cross-type forged release valve ensures positive load control.

Overload protection Hydraulic system is protected from internal damage by a by-pass mechanism. High quality glide-action pressure pump. Supplied with 500mm pump handle.

2015

12,000kg

85mm

50mm

180mm

315mm

157x134mm

\$129

TRADE

\$169

ı	ensures is protected echanism. up.	BORUM BOTTLE JACK FEATURES Manufactured of superior-grade steel and built to exacting standards for quality and durability. Lead-free paint finish is oil, grease and dirt-resistant. Built-in by-pass device protects hydraulic system. Compact, powerful Air Turbo Motor. High quality large diameter hydraulic steel cylinder. Precision machined, chrome plated and polished piston-
	2016	Versatile "quick connector" for easy removal of air hose.
	20,000kg	Air/Hydraulic Bottle Ja
	115mm	BTSJ20TB /= B O R U M
	75mm	Safe working capacity: 20,000kg
	200mm	Working height: 262 - 504mm Hydraulic lift: 163mm
	390mm	Op. air pressure: 110-125psi
	167x156mm	Air inlet fitting: 1/4"

Hydraulic Bottle Jack 20,000KG J20TB /= BORUM working capacity: 20,000kg ing height: 262 - 504mm ulic lift: 163mm r pressure: 110-125psi et fitting: 1/4"

Weight: 16kg **Excludes GST**



Air/Hydraulic Bottle Jack 20,000KG PROBJ20TA

orating the latest technology in aggressive wiping lips and OD exclusion, the high capability um quality seal systems efficiently protect internal hydraulics keeping it free from dirt, mud,

enium quality seem cysteme with the state, and other contaminants. lead-free paint finish is applied after a thorough chemical wash to ensure a long-lasting premium iish with a final coat that is oil, grease and dirt-resistant for easy cleanup.

Safe working capacity: 20,000kg Working height: 261.5-525mm Hydraulic lift: 156mm Adjustable lift: 95mm Operating air pressure: 110-125psi Air inlet fitting: 1/4" Base: 230 x 150 x 30mm Weight: 19kg

or professional quality and durability. remium quality large diameter hydra

Air/Hydraulic Bottle Jack 12,000KG TQBJ12TA TRADEQUIP MADE FOR THE

Safe working capacity: 12,000kg Working height: 260-510mm Adjustable screw: 80mm Work pressure: 110-125psi Hydraulic stroke: 170mm Air inlet fitting: 1/4"

FEATURES

Compact powerful Air Turbo motor. Versatile "quick connector provides 'quick & easy air Two piece pump handle Convenient welded carry handle.

Air/Hydraulic Squat Jack 20,000KG TQBJ20TAS TRADEQUIP

Safe working capacity: 20,000kg Working height: 178-328mm Adjustable screw: 63mm Work pressure: 110-125psi Hydraulic stroke: 87mm



.000kg Capacity

Air/Hydraulic Bottle Jack 20,000KG BWBBJ20T /= B O R U M

INDUSTRIAL

Air/Hydraulic Bottle Jack 30,000KG

Safe working capacity: 20,000kg Working height: 263 - 503mm Hydraulic lift: 160mm Adjustable height: 80mm Base area: 200x152mm On air pressure: 90-120ps

QUALITY 20,000kg Capacity WELDED BASE

WELDED

BASE

Air Actuated Bottle Jack Squat 20,000KG PROBJ20TAS Safe working capacity: 20,000kg Working height: 185-330mm Hydraulic lift: 80mm

Operating air pressure: 110-125psi Adjustable height: 61mm Air inlet fitting: 1/4" Base: 230 x 150 x 30mm

WELDED

Air/Hydraulic Bottle Jack 20,000KG 2026T TRADEQUIP

12,000kg

20,000kg

Cápacity

Safe working capacity: 20,000kg Working height: 265-510mm Hydraulic lift: 170mm (265mm to 435mm) Adjustable height: 75mm (max. height 510mm) Base area: 224x134mm Work pressure: 90-120psi Weight: 16kg

FEATURES

Compact powerful Air Turbo motor. Versatile "quick connector provides quick & easy air connection Two piece pump handle Convenient welded carry handle



2051T TRADEQUIP

Safe working capacity: 20,000kg Working height: 148-259mm Screw extension height: 45mm Operating air pressure: 100-145psi Hydraulic stroke: 66mm Air inlet fitting: 1/4"



Chrome plated rams. Convenient welde carry handle



20,000kg

Air/Hydraulic Bottle Jack 35,000KG BBJ35TA Z= BORUM Safe working capacity: 35,000kg Working height: 264 - 414mm Hydraulic lift: 150mm Operating air pressure:

BWBBJ30T /= B O R U M

Safe working capacity: 30,000kg

Working height: 275 - 532mm Hydraulic lift: 162mm Adjustable height: 95mm Base area: 229x180mm Op. air pressure: 90-120psi

QUALITY

110-125psi Air inlet fitting: 1/4" Weight: 29kg



30,000kg

Capacity

Air/Hydraulic Bottle Jack 30,000KG 30,000kg PROBJ30TA

Safe working capacity: 30,000kg Working height: 279.5-533mm Hydraulic lift: 155mm On air pressure: 110-125psi Air inlet fitting: 1/4' Base: 250 x 180 x 40mm











Truck Jack Stands Z= B O R U M

SOLD INDIVIDUALLY

Code	15TJSSHORT	15TJS
Load limit	15,000kg	15,000kg
Height	446 - 631mm	645-1077mm
Base Area	300x300mm	460x460mm
Excl. GST	\$439	\$529
Incl. GST	\$482.90	\$581.90
Code	25TJSSHORT	25TJS
Code Load limit	25TJSSHORT 25,000kg	25TJS 25,000kg
Load limit	25,000kg	25,000kg
Load limit Height	25,000kg 415 - 539mm	25,000kg 680-968mm



FEATURES

Manufactured from high-grade steel and built to exacting standards for quality and durability. Lead-free paint finish is oil, grease and dirt-resistant for easy cleanup. High strength locking pin Controlled pin holes for easy heigh adjustments.
Turned post slide for easy quick

Heavy-gauge steel gusseted uprights prevent distortion or twisting. Rugged base provides plenty of

Conveniently located carry handle Sold individually. (not in pairs)

INDUSTRIAL QUALITY

00000

apacity



For full product specifications go to www.tgbbrands.com.au

Auxiliary Stand 7,000KG

Safe working capacity: 7,000kg Working height: 1295-1905mm Adjustable pin heights: 8 (75mm increments) Base: 300x300x300mm Weight: 65kg

BAUXS7T - BORUM

FEATURES

Heavy duty design and support bracing system to sustain heavy vehicle loads. Manufactured from high-grade

steel and built to exacting standards for quality and durability.
Fitted with spring loaded castor

wheels to ensure easy moveme around the workshop.

beam. Lead-free paint finish is applied after a thorough chemical wash to ensure a long-lasting finish and to help prevent rust. Paint is oil, grease and dirt-resistant for easy cleanup. High strength locking pin. Controlled pin holes for easy height adjustments. Turned post slide for easy quick adjustments



Support Stand 10,000KG 10TSS /= BORUM

Safe working capacity: 10,000kg Working height: 720-1190mm Adjustable pin heights: 10 Saddle dimensions: 150x80mm Base: 406 x 556mm Weight: 23.5kg

FEATURES

Stable 4 legged stability. Lead-free paint is oil, grease and dirt-resistant for easy cleanup. High strength locking pin & controlled pin holes for easy height adjustments. Turned post slide for easy adjustment.

*10TSS/10TSSHORT SOLD INDIVIDUALLY

Support Stand SHORT 10,000KG /- BORUM 10TSSHORT

Safe working capacity: 10,000kg Working height: 480-780mm Adjustable pin heights: 6 Saddle dimensions: 150x80mm Base: 310 x 310mm



10 Metric Sizes:

INDUSTRIAL

OUALITY

Jumbo Spanner Set Jumbo Spanner Set 10 Piece Imperial 10 Piece Metric

B10PJSI /= B O R U M B10PJSM /= B O R U M

10 Imperial Sizes: 1 5/16", 1 3/8", 1 7/16", 1 1/2", 1 5/8", 1 11/16", 1 3/4", 1 13/16", 1 7/8" 2" Wallet rolled out: 830 x 690 x 30mm Wallet rolled up: 150 x 690 x 130mm

> INDUSTRIAL QUALITY







34mm, 36mm, 38mm, 41mm, 42mm,

Wallet rolled out: 830 x 690 x 30mm

Wallet rolled up: 150 x 690 x 130mm

44mm 45mm 46mm 48mm & 50mm

Air Actuated Truck Jack 22,000KG

B2003T /= B O R U M

Safe working capacity: 22,000kg Lift range: 210-525mm Hydraulic lift: 120mm Adjustable height: 105mm Handle length: 1075mm Air supply: 100-120psi Wheel diameter: 175mm Adaptors: 20, 50, 100mm Chassis: 500L x 215H x 320Wmm

FFATURES

Solid heavy duty construction. Advanced technology sealing rings. Fast motion super duty air pump. Temperature-resistant hydraulic oil. Treated and polished piston and ram Built-in bypass hydraulic safety overload system. Compact design easily fits dual tandem

Convenient & efficient height adaptors. 3-position pumping handle. High quality lead-free paint is oil, grease and dirt-resistant finish for easy cleanup.







MADE FOR THE

Includes

Height

Adaptors

2 PRO

Professional

Reputable

Outstanding

TRADE



Air Actuated Truck Jack 22,000KG

2004T TRADEQUIP

Safe working capacity: 22,000kg Lift range: 225-552mm Hydraulic lift: 124mm Adjustable height: 103mm Chassis: 560L x 230H x 320Wmm Adaptors: 21, 60, 100mm Handle length: 1160mm Wheel diameter: 200mm





FEATURES

Frade quality rugged steel construction. Wear-resistant quality sealing O-rings. Strong hydraulic pump.
Temperature-resistant hydraulic oil.
Treated and polished piston and Quick lift ram. Built-in hypass hydraulic safety overload system Compact design easily fits dual tandem axles. Convenient & efficient height adaptors. 3-position pumping handle High quality lead-free paint is oil, grease and dirt-resistant finish for easy cleanup.

Air Actuated Truck Jack 20,000KG -PROTRJA20T

Working height: 215-541mm Hydraulic Lift: 141mm Adjustable screw: 85mm Adaptors: 20, 50, 100mm Handle length: 1335mm Operating air pressure: 145-175psi Chassis: 520L x 215H x 258Wmm

Safe working capacity: 20,000kg





FEATURES

Double sealing using XTP industry sealing. Telescopic air actuation lift (air-hydraulic pump). Long T-handle lets you easily position your jack under vehicle. Self-returning lowering and lifting switch.

Internal and external cylinders hard chromed High manoeuvrability & deep reach. 8 extension adaptors/saddle plates

Air Jack Support Stand 10,000KG BSJ10T FABORUM

Safe working capacity: 10,000kg Height: Min. 444mm - Max. 1298mm Hydraulic lift: 292mm Base diameter: 339mm Rated air pressure capacity: 200psi Weight: 91kg



pair

FFATURES

The BORUM Industrial AIR JACK/SUPPORT STAND 10.000KG is a reinforced pin style jack and stand with industrial quality design and support bracing system to sustain heavy loads up to 10,000kg. Adjusts to match the job with a 444mm minimum height, 292mm of hydraulic lift and up to 1298mm maximum height using the extension tube!!

Featuring Heavy-Duty Industrial design, this tough air jack/suppor stand is ideal for truck, bus, farm, earthmoving equipment and fleet vehicle maintenance workshop use.





"NON-SKID BASE" - 4 ply pads of rubber grins are holted and glued to the 6mm stee floor plates and they will not skid ahead of the wheels. Replaces need for a pit or hoist, and at a

fraction of the cost and floor space













Air Actuated Truck Jack 35,000KG

BTJ35TA /= BORUM


INDUSTRIAL

Safe working capacity: 35,000kg Lift range: 255-633mm Hydraulic lift: 155mm Adjustable height: 123mm

OUALITY Adaptors: 21, 61, 100mm Handle length: 1110mm Operating air pressure: 110-125psi Chassis: 555L x 255H x 295Wmm

FEATURES

Pro quality rugged steel construction Wear-resistant quality sealing O-rings. Strong hydraulic pump & 3-position handle.
Temperature-resistant hydraulic oil.
Treated and polished piston and ram. Built-in bypass hydraulic safety overload Compact design and Quick Lift ram.
Convenient & efficient height adapto
High quality lead-free paint.



BTJ50TA /= BORUM

Safe working capacity: 50,000kg Lift range: 287-650mm Hydraulic lift: 153mm Adjustable screw: 110mm Adaptors: 20 60 100mm Handle length: 1230mm Operating air pressure: 110-125psi Chassis: 525L x 288H x 325Wmm

INDUSTRIAL QUALITY

FEATURES

Pro quality rugged steel construction.
Wear-resistant quality sealing O-rings.
Strong hydraulic pump & 3-position handle. Temperature-resistant hydraulic oil. Treated and polished piston and ram.
Built-in bypass hydraulic safety overload.
Compact design and Quick Lift ram. Convenient & efficient height adaptors High quality lead-free paint

Air Actuated Truck Jack 30,000KG BTJ30TA /= BORUM

Safe working capacity: 30,000kg Lift range: 360-772mm Hydraulic lift: 267mm Adaptors: 45 & 100mm Handle length: 1370mm Operating air pressure: 145-175psi Chassis: 840L x 360H x 282Wmm





FEATURES

XTP industry double sealing function using Telescopic air actuation lift. Self-returning lowering and lifting switch Internal & external cylinders hard chromed Long T-handle for high manoeuvrability & deep reach under vehicles Designed for extremely high axles



INDUSTRIAL

GUALITY

30.000KG

Air Actuated Jack 2 Stage 15,000/30,000KG

FEATURES

hydraulic pump).

under vehicles.

chromed.

For full product specifications go to www.tgbbrands.com.au

INDUSTRIAL

GUALITY

Double sealing function using XTP

ong T-handle lets you easily position your jack under vehicle.

industry sealing.
Telescopic air actuation lift (air-

Self-returning lower & lift switch

High manoeuvrability & deep reach

2 extension adaptors/saddle plates

30.000KG

BTJ1530TA /= B O R U M 1st stage: 30,000kg safe working capacity

2nd stage: 15,000kg safe working capacity First stage hydraulic lift: 73mm Second stage hydraulic lift: 66mm Operating air pressure: 145-175psi

Height: 150-409mm Adaptors: 45 and 75mm Handle length: 1300mm Chassis: 480 x 290 x 150mm

Includes Height **Adaptors**

Inc. GST \$1318.90

Includes

Height

Adaptors

LIFTS

35.000KC

ncludes

Height

Adaptors







Air Actuated Truck Jack 60.000KG BTJ60TA /- B O R U M

Safe working capacity: 60,000kg Lift range: 420-1031mm Hydraulic lift: 311mm Adaptors: 100 & 200mm Handle length: 1290mm Operating air pressure: 145-175psi Chassis: 910L x 420H x 300Wmm



FEATURES

Double sealing function using XTP industry sealing. Telescopic air actuation lift

Self-returning lowering and lifting switch nternal & external cylinders hard chromed Long T-handle for high manoeuvrability & deep reach under vehicles Designed for extremely high axles



Includes

Height

Adaptors

Air Actuated 2 Stage Truck Jack 10,000/25,000KG

BTJ1025TA FAIBORUM

Stage 1: 25,000kg safe working capacity Stage 2: 10,000kg safe working capacity Lift range: 185-497mm

Hydraulic lift: Stage1: 97mm, Stage2: 95mm Adaptors: 45, 75mm

Handle length: 1380mm Operating air pressure: 145-175psi Chassis: 770L x 282H x 185Wmm



Includes Height **Adaptors**

FEATURES

Double sealing function - XTP industry sealing. Telescopic air actuation lift. Self-returning lowering and lifting switch.
Internal & external cylinders hard chromed Long T-handle for high manoeuvrability & deep

Air Actuated 2 Stage Truck Jack 25,000/50,000KG

BTJ2550TA = BORUM

Stage 1: 50,000kg safe working capacity Stage 2: 25,000kg safe working capacity Lift range: 215-564mm

Hydraulic lift: Stage1: 115mm, Stage2: 114mm Adaptors: 45, 75mm Handle length: 1380mm

> INDUSTRIAL GUALITY

Operating air pressure: 145-175psi

Chassis: 805L x 282H x 215Wmm

FEATURES

Double sealing function - XTP industry sealing. Telescopic air actuation lift. Self-returning lowering and lifting switch. Long T-handle for high manoeuvrability & deep

DEEP REACH OWER PROFILE

Includes

Height

Adaptors

LIFTS

50,000KG

25,000KG

INDUSTRIAL

GUALITY

REACH

Air Actuated 3 Stage Truck Jack 10,000/25,000/50,000KG BTJ102550TA -BORUM

Safe working capacity: Stage1: 50,000kg Stage2: 25,000kg, Stage3: 10,000kg Lift range: 160-472mm Hydraulic lift: Stage1: 62mm Stage2: 61mm, Stage3: 69mm

Adaptors: 45, 75mm Handle length: 1380mm Operating air pressure: 145-175psi Chassis: 825L x 282H x 160Wmm



FEATURES Double sealing function using XTP

industry sealing. Telescopic air actuation lift Self-returning lowering and lifting switch. Internal & external cylinders hard chromed

INDUSTRIAL

QUALITY

Long T-handle for high manoeuvrability &

LIFTS

50,000KG



Air Actuated 3 Stage Truck Jack 20,000/40,000/60,000KG

BTJ204060TA /= B O R U M



First stage: 60,000kg safe working capacity Second stage: 40,000kg safe working capacity Third stage: 20,000kg safe working capacity First stage hydraulic lift: 57mm Second stage hydraulic lift: 59mm

Third stage hydraulic lift: 61mm Height: 150-447mm Adaptors: 45 and 75mm Operating air pressure: 145-175psi Handle length: 1380mm Chassis: 875 x 295 x 150mm

> Includes Height Adaptors



LIFTS

80,000KG

INDUSTRIAL GUALITY

FEATURES

Double sealing function using XTP industry sealing Telescopic air actuation lift (air-hydraulic pump). Long T-handle lets you easily position your jack under vehicle.
Self-returning lowering and lifting switch.

Internal and external cylinders hard chromed High manoeuvrability & deep reach under vehicles 2 extension adaptors / saddle plates

Air Actuated 2 Stage Truck Jack 50,000/80,000KG BTJ5080TA /= B O R U M

First stage: 80,000kg safe working capacity

Second stage: 50,000kg safe working capacity First stage hydraulic lift: 111mm Second stage hydraulic lift: 102mm Height: 230-563mm Adaptors: 45 and 75mm

Operating air pressure: 145-175psi Handle length: 1300mm Chassis: 930 x 340 x 230mm









FEATURES

Double sealing function using XTP industry sealing Telescopic air actuation lift (air-hydraulic pump) Long T-handle lets you easily position your jack under vehicle

Self-returning lowering and lifting switch. Internal and external cylinders hard chromed High manoeuvrability & deep reach under vehicles. 2 extension adaptors / saddle plates













MORE THAN JUST A PRESS!

Workshop Mate Workstation featuring a 30,000KG Shop Press & Spring Compressor



Safe working capacity: 30,000kg Working range: 224mm-819mm Piston ram stroke main ram:

140mm (Standard load cap fitted)

Bed height settings: 85mm increments-8 settings Bed width: 466mm Bed gap: 200mm

Spring compressor: Piston ram stroke: 295mm Operating air pressure: 90-125psi

Overall dimensions: 1820H x 1170W x 820Dmm

Weight: 400kg



AIR/HYDRAULIC OPERATED 30,000KG PRESS SPRING COMPRESSOR. FILTER CRUSHING ACCESSORY DOZENS OF UNIQUE TOOLING OPTIONS **ON-BOARD TOOLING STORAGE STAND**

WINCH OPERATION TO LOWER AND RAISE BENCH

BENEFITS

Press almost any bearing or bush with PRECISION and ACCURACY in minutes, saving valuable workshop time. Smooth AIR/HYDRAULIC foot pedal operation for handsfree accuracy & control.

Hands free Spring Compression.

Even the most difficult pressing tasks become SAFE &

Complete with COMPREHENSIVE HIGH QUALITY Interlocking Tool, Die and Spacer Kit to ensure SAFE **WORK PRACTICES.**


Complete on machine storage - minimises time spent searching for the required tools & spacers for each job! Tasks like SUSPENSION BUSHES once seen as too hard become a breeze.

A comprehensive variety of spring adaptors, suitable to almost any type or model of spring SAFE & EASY to

Decrease labour time & increase productivity and

INCREASE WORKPLACE SAFETY.

Undertake jobs that are currently too difficult.



WSMP50 WORKSHOP MATE

18 Piece Sleeve Set includes:

28x20x80mm: 33x25x80mm: 38x30x80mm; 43x35x80mm;

48x40x80mm; 53x45x80mm;

58x50x80mm; 63x55x80mm; 68x60x80mm; 73x65x80mm;

78x70x80mm; 83x75x80mm; 88x80x80mm; 93x85x80mm; 98x90x80mm; 103x95x80mm;

FEATURES

18 sleeves constructed from heat-treated forged carbon steel. Sturdy metal carry case. Designed and engineered to work as an added accessory to all current Workshop Mate Workstations.



Great Workshop Mate Accessory







For full product specifications go to www.tgbbrands.com.au

MADE FOR THE

SAFETY

BARRIER

AVAILABLE

SEPARATELY

6 HEIGHT SETTINGS

SAFETY

BARRIER

AVAILABLE

SEPARATELY

45,000kg

TATRADEQUIP

45,000kg

Capacity

TATRADEQUIP

Workshop Press 20,000KG

1061T TRADEQUIP

Safe working capacity: 20,000kg Working range: 60-773mm Overall height: 1503mm Overall width: 705mm BARRIER Overall depth: 660mm AVAILABLE Bed width: 504mm

SEPARATELY Bed gap: 103mm Bed inside: 285 x 103mm Press head diameter: 40mm Press head length: 68mm

Jacking handle: 694mm Piston ram stroke: 160mm Weight: 82kg



FFATURES

High-grade Channel Steel Hydraulics are powered with a high

quality oil.
Integrated overload protection valve keeps from overloading the system Lead-free paint finish is oil, grease and dirt-resistant for easy cleanup and to help prevent rust.

Hydraulic Workshop

Press 20,000KG

1063T TRADEQUIP

Safe working capacity: 20,000kg

Working range: 43-882mm

Bed Inside: 358 x 105mm

Piston ram stroke: 185mm

Press head cap diam: 45mm

Press head cap length: 17mm

High-grade Channel Steel. 100mm pressure gauge. High quality large diameter hydraulic

steel cylinder unit. Hydraulics are powered with a high

Integrated overload protection valve keeps from overloading the system

Lead-free paint finish is oil, grease

and dirt-resistant for easy cleanup

Ram lateral adjustment: 180mm

Overall height: 1795mm

Overall width: 780mm

Overall depth: 690mm

Bed width: 505mm

Bed gap: 105mm

Weight: 90kg

FEATURES

quality oil.



SAFETY

BARRIER

AVAILABLE

TO TRADEQUIP

20,000kg

Capacity

MADE FOR THE

TRADE

Workshop Press 30,000KG

1062T TRADEQUIP

Safe working capacity: 30,000kg Working range: 45-705mm Overall height: 1605mm Overall width: 745mm BARRIER Overall depth: 660mm AVAILABLE Bed width: 480mm SEPARATELY

Bed gap: 124mm Bed inside: 254 x 124mm Press head diameter: 50mm Press head length: 68mm Jacking handle: 694mm Piston ram stroke: 163mm Weight: 113kg



FFATURES

High-grade Channel Steel.
Hydraulics are powered with a high quality oil. Integrated overload protection valve

keeps from overloading the system Lead-free paint finish is oil, grease and dirt-resistant for easy cleanup and to help prevent rust.



SAFETY

BARRIER

AVAILABLE

For full product specifications go to www.tqbbrands.com.au

Hydraulic Workshop Press 30,000KG

1064T TRADEQUIP

Safe working capacity: 30,000kg Working range: 50-1030mm Overall height: 1950mm Overall width: 830mm Overall depth: 660mm Bed width: 455mm Bed gap: 154mm Bed inside: 230 x 154mm Press head diameter: 56mm Load cap length: 17mm Jacking Handle: 639mm Ram lateral adjustment: 70mm Piston ram stroke: 170mm Weight: 138kg

FEATURES

High-grade Channel Steel.
100mm pressure gauge.
High quality large diameter hydraulic steel culinder unit steel cylinder unit. Hydraulics are powered with a high

ntegrated overload protection valve keeps from overloading the system Lead-free paint finish is oil, grease and dirt-resistant for easy cleanup and to help prevent rust.

Lateral Ram Adjustment





TO TRADEQUIP

Hydraulic Workshop Press 45,000KG WIDE

2036T TRADEQUIP

Safe working capacity: 45,000kg Working range: 159-859m Bed outside: 359mm Bed inside: 195mm Red width: 826mm Piston ram stroke: 190mm Ram diameter: 90mm 1707H x 1420W x 826Dmm Bed height settings: 6 Weight: 296kg



FEATURES

High-grade steel frame. 100mm pressure gauge. Bed winch for easy raise and lower adjustment Lead-free paint finish is oil grease and dirt-resistant Hand winch for fast



Air/Hydraulic Workshop Press 45,000KG WIDE 2038T TRADEQUIP

Safe working capacity: 45,000kg Working range: 159-859mm Bed outside: 359mm Bed inside: 195mm Bed width: 826mm Piston ram stroke: 190mm Ram diameter: 90mm Op. air pressure: 110-125 psi 1707H x 1420W x 800Dmm Bed height settings: 6 Weight: 301kg

FEATURES

AIR OPERATED

High-grade steel frame 2 speed pump. 100mm pressure gauge.
Bed winch for easy raise
and lower adjustment.
Paint is oil, grease and dirtresistant for easy cleanup. High quality large diameter hydraulic steel cylinder unit. Piston-ram is treated, polished. Includes hand winch. Integrated overload

protection valve prevents overloading. Extra-long handle included for easy pumping force.
Double spring ram return fo fast ram retraction.



Hydraulic Workshop Press 50,000KG

2048T TATRADEQUIP

Safe working capacity: 50,000kg Working range: 137-837mm Bed outside: 356mm Bed inside: 210mm Bed width: 713mm Bed internal: 390 x 200mm Piston ram stroke: 190mm

MADE FOR THE

TRADE

Ram diameter: 95mm Op. air pressure: 110-125 psi 1700H x 1290W x 745Dmm Bed height settings: 6 Weight: 271kg

SHOP PRESSES





Heavy-duty high-grade steel frame. Hand operated air trigger ram travel control. 100mm pressure gauge Polished pneumatic aluminium air motor. Bed winch for easy raise and lower adjustment.
Lead-free paint finish helps prevent rust& is oil grease and dirt-resistant. High quality large diameter hydraulic unit. Hand winch for fast height adjustments



Workshop Press Adaptor Kit

BPAK /- BORUM

Includes 8 different sized pins (mandrels) ranging from 2,000kg to 20,000kg capacity, a pin holder, a storage shelf along with a mounting kit, and a pin plate with the weight capacity shown for each pin.

This very handy set of eight steel mandrels, adaptor and press plate expands the uses of your workshop press for a wider range of applications involving different sized work pieces



60mm x 12mm 60mm x 16mm 85mm x 18mm 85mm x 20mm

Mandrel

Length x Diameter

50mm x 10mm

15mm x 25mm 110mm x 30mm

*UNLESS STATED OTHERWISE ALL TOR BRANDS PRODUCTS, EXCLUDING CONSUMABLES, COME WITH A 12 MONTH COMMERCIAL USE WARRANTY AGAINST MANUFACTURING DEFECTS. THE BONUS 12 MONTH WARRANTY OFFERED EXCLUSIVELY IN THIS PROMOTIONAL PERIOD APPLIES ONLY TO THE HYDRAULIC RAM AND HYDRAULIC PUMP FOR 'BONUS' MARKED PRODUCTS. THE ADDITIONAL 12 MONTHS DOES NOT INCLUDE INSTALLATION/REMOVAL LABOUR OR FREIGHT FOR THE COMPONENT

Lateral Ram Adjustment



















Air/Hydraulic Workshop Press 30,000KG 6 HEIGHT SETTINGS PROSHPR30TA

Safe working capacity: 30,000kg Working range: 25-850mm Screw adjustment: 75mm Bed outside: 164mm BARRIER Red inside: 148mm Bed width: 600mm AVAILABLE Ram diameter: 58mm SEPARATELY Bed height settings: 6 1800H x 770W x 505Dmm



30,000kg Capacity



- / Mandrel Kit Included ✓ Long Pump Handle
- ✓ Premium Bed Blocks
- ✓ Winch Adjustable Bed ✓ Premium Hydraulic System
- ✓ Premium Paint Finish
- ✓ Precision Lateral Ram Adjustment
- ✓ Premium Grade Steel Construction
- ✓ Designed for maximum strength, reliability and durability
- ✓ Foot Pedal Air/Hydraulic Operation

Capacity



Scan code for **TQPro Presses** online product demonstration

Air/Hydraulic **Workshop Press** 50,000KĠ

Safe working capacity: 50,000kg Working range: 80-780mm Screw adjustment: 75mm Bed inside: 200mm BARRIE

Bed outside: 220mm Bed width: 750mm AVAILABL Ram diameter: 68mm SEPARATELY Bed height settings: 6 1900H x 930W x 535Dmm

Weight: 243kg

PROSHPR50TA











Hydraulic Workshop Press 20,000KG BHSP20T /= B O R U M

For full product specifications go to www.tgbbrands.com.au

Safe working capacity: 20,000kg Working range: 38-918mm Red outside: 172mm Bed inside: 152mm Bed width: 510mm Piston ram stroke: 185mm Bed height settings: 8 Ram diameter: 72mm 1626H x 755W x 560Dmm Weight: 115kg



FEATURES

Heavy-duty high-grade steel H-frame ntegrated overload protection valve Foot & Hand operated pump. 100mm pressure gauge. STEEL SAFETY MESH BARRIER Lead free paint finish is oil, grease and dirt-resistant for easy cleanur Piston-ram is fitted with backup ring, preventing bypass oil drift High quality hydraulic oil offers better sion resistance and flexibility Pair of bed plates included





SETTINGS

Hydraulic Workshop Press 30,000KG

BHSP30T /= B O R U M Safe working capacity: 30,000kg Working range: 151-1031mm Bed outside: 184mm Bed inside: 164mm Bed width: 535mm Piston ram stroke: 150mm Bed height settings: 8 Ram diameter: 80mm 1830H x 1000W x 700Dmm Weight: 167kg



FEATURES

Heavy-duty high-grade steel H-frame. Integrated overload protection valve Foot & Hand operated pump. 100mm pressure gauge. STEEL SAFETY MESH

BARRIER Lead free paint finish is oil, grease and dirt-resistant for easy cleanup. Piston-ram is fitted with

bypass oil drift. High quality hydraulic oil offers better corrosion resistance and flexibility. Pair of bed plates included





V= BORUM

BSP75TA V= B O R U M

Safe working capacity: 75,000kg Working range: 170-884mm Overall height: 1925mm Overall width: 1340mm Overall depth: 800mm Bed width: 800mm Bed surface depth: 279mm

Piston ram stroke: 250mm Ram diameter: 125mm Width between side posts: 217mm Red height settings: 8 Operating air pressure: 110-125psi Air inlet: 1/4"NPT Weight: 451kg

Power to safely remove & install bearings, gears, U-joints, bushings, ball joints and pulleys with precision and versatility!



Air/Hydraulic Workshop Press 75,000KG Air/Hydraulic Workshop Press 100,000KG BSP100TA V= B O R U M

Safe working capacity: 100,000kg Working range: 113-813mm Overall height: 1848mm Overall width: 1250mm Overall depth: 990mm Bed width: 787mm Bed surface depth: 342mm

Piston ram stroke: 300mm Ram diameter: 140mm Width between side posts: 268mm Bed height settings: 6 Operating air pressure: 110-125psi Air inlet: 1/4"NPT

Weight: 652kg

6 HEIGHT SETTINGS Ideal for straightening, stamping, bending and pressing any component that is difficult to handle.





- Heavy-duty H-frame constructed of high-grade steel and built to exacting standards for quality and durability.
 Foot operated air trigger ram travel control.
 100mm pressure gauge.
 Extra tall working range for versatility.
 Pair of bed plates included
 Table winch system lowers or raises the bed.
 Integrated overload protection valve keeps from overloading the system.
- High quality large diameter hydraulic steel cylinder unit results in lower oil pressure needed to raise the load, helping to reduce wear and extend service life.
- Piston-ram is treated and polished and fitted with backup ring, preventing load from falling slowly or bypassing oil drift.
- Hydraulics are powered with a high quality oil, which offers better corrosion resistance & high/low temperature flexibility, allowing the unit to operate at temperatures.

Léad-free paint finish is applied after a thórough chemical wash to ensure a long-lasting finish to help prevent rust & is óil, grease, & dirt-resistant for easy clean up.

""UNLESS STATED OTHERWISE, ALL TOB BRANDS PRODUCTS, EXCLUDING CONSUMABLES, COME WITH A 12 MONTH COMMERCIAL USE WARRANTY AGAINST MANUFACTURING DEFECTS. THE BONUS 12 MONTH WARRANTY OFFERED EXCLUSIVELY IN THIS PROMOTIONAL PERIOD APPLIES ONLY TO THE HYDRAULIC RAM AND HYDRAULIC PUMP FOR "BONUS" MARKED PRODUCTS. THE ADDITIONAL 12 MONTHS DOES NOT INCLUDE INSTALLATION/REMOVAL LABOUR OR FREIGHT FOR THE COMPONENT.

MADE FOR THE

TRADE

Polycarbonate TQB Shop Press Safety Barrier

7@ TRADEQUIP

SUIT TQB BRANDS **PRESSES ONLY**



SGUARD-2 PRESS GUARD POLY CARBONATE

SUIT 1064T



SGUARD-3 PRESS GUARD

POLY CARBONAT SUIT BSP75TA SGUARD-4

\$315 PRESS GUARD POLY CARBONATE SUIT 2048T/2038T/ 2036T/BSP100TA

* * * * AVAILABLE IN FOUR DIFFERENT SIZES



For full product specifications go to www.tgbbrands.com.au

Master Press & Pull Set 28 Piece

9028T TRADEQUIP

4 x Step plates: 74, 76, 78, 80mm 4 x Pulling spindles with thrust bearings 20 x Press sleeves: 44 x 43; 46 x 36; 48 x 38; 50 x 40; 52 x 42; 54 x 44; 56 x 46; 58 x 48; 60 x 50; 62 x 52; 64 x 54; 66 x 56; 68 x 58; 70 x 60; 72 x 62; 74 x 64; 76 x 66; 78 x 68; 80 x 70; 82 x 72mm Heat-treated forged carbon steel

Sturdy Blow Mould Case





83.3; 86; 88.4; 102mm Heat-treated forged carbon steel



FWD Wheel Bearing

Kit 23 Piece

Hub screw length: 207mm

Hub screw drive: 32; 38mm

91 x 81.5: 102 x 92mm Drift sizes: 50; 55; 59; 63; 66.5;

9029T TRADEQUIP

Sleeve external: 76.5 x 65; 86 x 77;

70: 71.5: 73: 73.5: 75. 77.5: 81.4:



Universal Press & Pull Sleeve Kit 26 Piece

9024T TRADEQUIP

4 Beams 3 1/2" Sleeves 20 Sleeves 11pieces (GOLD) 9 pieces (SILVER)



For removal and installation of bushes, bearings and seals, races, sprockets and pulleys on cars, trucks, off-road construction equipment and machinery



Hydraulic Gear Puller 23 Piece

9023T TRADEQUIP

Capacity: 10,000kg Bearing Separator: 20-105mm Twin/triple head, beam and legs to build: 100, 150 and 200mm Two and three leg hydraulic pullers with separator capacity: 75-105mm Size: 355L x 195W x 150Hmm

Pulls bearings, timing gears, steering wheels and pulleys on most cars and light trucks





Universal Press Support Block 30,000KG

9025T TRADEQUIP

Base block: 250 x 200 x 40mm Height adaptor block:

Made from Billet aluminiun





TRADEQUIP

For use with a hydraulic shop press for workpieces with a complicated shape to allow bearings to be pressed in or out accurately.





Code	7000T	7001T	7002T	7003T	7004T	7005T
Vice type	Fixed	Fixed	Fixed	Swivel	Swivel	Swivel
Jaw Width	125mm	150mm	200mm	125mm	150mm	200mm
Jaw Opening	130mm	150mm	170mm	140mm	170mm	220mm
Throat Depth	69mm	76mm	88mm	76mm	86mm	110mm
Anvil Size	85x90mm	100x105mm	105x105mm	106x106mm	127x127mm	147x147mm
Excl. GST	\$149	\$199	\$269	\$218	\$319	\$439
Incl. GST	\$163.90	\$218.90	\$295.90	\$239.80	\$350.90	\$482.90

Multi-Purpose Bench Vice FEATURES with Pipe Jaws 150MM

7009T TRADEQUIP

Jaw width: 150mm Jaw opening: 140mm Throat depth: 80mm Anvil size: 80x65mr

Body of rugged quality malleable cast iron Forge hardened steel serrated jaws.
Precision machined steel screw and handle Reinforced mounting lugs.
Versatile 360° Swivel base locks in place.
Jaws rotate 360° and lock for unlimited

positioning.
Holds flat stock as well as round stock with



Bench Offset Vice 150MM

7007T TRADEQUIP

Jaw width: 150mm Jaw opening: 140mm Throat depth: 103mm Weight: 21kg

MADE FOR THE





Commercial Bench Vice Swivel with Anvil 150MM

BRV150 /= BORUM

Jaw width: 150mm Jaw opening: 150mm Throat depth: 105mm Anvil size: 90x105mm



INDUSTRIAL

GUALITY

Commercial Bench Vice Swivel with Anvil 200MM

BRV200 /= BORUM

Jaw width: 200mm Jaw opening: 200mm Throat depth: 115mm Anvil size: 100x113mm









DESIGNED FOR AUTOMOTIVE **& INDUSTRIAL APPLICATION**

DON'T BE FOOLED BY CHEAPER IMITATIONS THAT ARE DESIGNED FOR DENTISTRY, MODEL BUILDING, OPTOMETRY & LIGHTER DUTIES

* Adjustable Temp. Control

* 304 Grade

Stainless

Steel Tank

MADE FOR THE

Scan code for online product

6 Litres TRADEQUIP

Capacity: 6 Litres Ultrasonic power: 150W Ultrasonic frequency: 40KHz Heating power: 300W Heating temperature: 20-80 C

Timer range: 0-30 Minutes Tank material: 304 Grade 2mm thick Tank size: 300L x 155W x 150Hmm Size: 330L x 180W x 310Hmm MADE FOR THE

1036T



13 Litres TRADEQUIP

Capacity: 13 Litres Ultrasonic power: 300W Ultrasonic frequency: 40KHz Heating power: 400W Heating temperature: 20-80 C

Timer range: 0-30 Minutes Tank material: 304 Grade 2mm thick Tank size: 330L x 300W x 150Hmm Size: 360L x 330W x 310Hmm

For full product specifications go to www.tgbbrands.com.au

1037T

27 Litres TRADEQUIP

Capacity: 27 Litres Ultrasonic power: 500W Ultrasonic frequency: 40KHz Heating power: 500W Heating temperature: 20-80 C

Timer range: 0-30 Minutes Tank material: 304 Grade 2mm thick Tank size: 500L x 300W x 200Hmm Size: 550L x 330W x 360Hmn

1038T

36 Litres TATRADEQUIP Capacity: 36 Litres

Ultrasonic power: 600W (adjustable) Ultrasonic frequency: 28/40KHz Heating power: 800W Heating temperature: 20-80 C

Timer range: 0-30 Minutes Tank material: 304 Grade 2mm thick Tank size: 500L x 290W x 250Hmm Size: 570L x 360W x 450Hmm



LARGER SIZES AVAILABLE FOR SPECIAL ORDER PLEASE ENQUIRE WITH YOUR PREFERRED DISTRIBUTOR

Parts Washer 90 Litre

1003T TRADEQUIP

Pump power: 240V/50Hz/0.5A Pump output: 2.7-3.3 Litres per min. Tank: 758L x 527W x 275Hmm Minimum fluid capacity: 18 Litres Maximum fluid capacity: 45 Litres Size: 780L x 540W x 908Hmm



FEATURES

Sturdy metal construction and quality enamelled gloss finish.

Enclosed "High Volume" electric pump & fully screened pump housing.

Built-in replaceable pump inlet filter

Chromed flexible metal fluid delivery pipe. Large removable parts cleaning shelf for inspection and drying. Immersion soaking when parts cleaning shelf

removed. Non welded one-piece tank with Quick Close fire safe lid mechanism.

Suitable for use with aqueous water based cleaning fluids.

Replacement parts available

Parts Washer 180 Litre

1004T TATRADEQUIP

Pump power: 240V/50Hz/0.5A Pump output: 2.7-3.3 Litres per min. Tank:1135L x 545W x 320Hmm Min. fluid capacity: 33 Litres Max. fluid capacity: 90 Litres Size: 1150L x 560W x 1430Hmm



FEATURES

Sturdy metal construction and quality enamelled gloss finish. Enclosed "High Volume" electric pump & fully screened pump housing.

Built-in replaceable pump inlet filter Chromed flexible metal fluid delivery pipe.

Large removable parts cleaning shelf for inspection and drying. Immersion soaking when parts cleaning shelf removed.

Non welded one-piece tank with Quick Close fire safe lid mechanism Suitable for use with aqueous water based cleaning fluids Replacement parts available



Parts Washer Brush & Hose

1806 TATRADEQUIP

Long life 70mm synthetic bristles Polypropylene handle Stepped hose fitting suitable for connecting to 13mm and 16mm spouts Suits TradeQuip parts washers 1003T, 1004T & 1050

Stiff bristles are ideal for cleaning automotive and machined parts



SOLUTIONS

Parts Cleaning Concentrate



ENVIRO FRIENDLY BIODEGRADABLE **NON-TOXIC**

FORMULATED FOR USE IN ALL TRADEQUIP PARTS CLEANERS

Code	5083T	5082T
Bottle contents	10 Litres	20 Litres
Creates	50 Litres	100 Litres
Exl. GST	\$89	\$145
Incl. GST	\$97.90	\$159.50



Replacement Parts Washer Pump WARNING:

1005 TRADEQUIP Power: 230V 50Hz 26W 0.6Amp

Cable length: 305mm Head max: 1.8m Flowrate: 3.15 litres per minute Outlet thread: 1/2" NPT Female

100L x 85H x 65W mm

ONLY SUITABLE FOR USE WITH WATER BASED SOLUTIONS





FEATURES

Sturdy poly/plastic body. Stainless steel shaft Suits parts washers with chromed flexible metal fluid delivery pipes Snap off inlet grill for easy cleaning.
Suitable for use with aqueous water based cleaning fluids.
Works with TradeQuip parts washers (Code/s 1003T, 1004T

and 1050, sold separately)









MADE FOR THE

3051 TRADEQUIP

Cabinet capacity: 220 Litre Working pressure: 60-110psi Maximum media capacity: 20kg

4 Ceramic nozzle tips: 4, 5, 6 & 7mm With gun & low voltage internal fluorescent light glass window Tempered glass view window: 250 x 525mm External size: 1400H x 890L x 550Wmm

Includes oun and light



220 LITRE Capacity

Freestanding floor model. Complete with gun and low voltage internal fluorescent light. Tempered glass viewing window with nrotective shields Cabinet fitted and ready to be used with a workshop vac as dust collection system.

Spare parts available in Australia

FEATURES



Oversized hinged top door opening Includes 240V dust

Capacity

Blasting Cabinet 420 Litre Capacity

3036T TRADEQUIP

Cabinet capacity: 420 Litre Air regulator & gauge panel 4 Ceramic nozzles: 2x5mm, 2x6mm Maximum media capacity: 70kg Maximum air pressure: 125psi Required air supply: 15-25CFM Sand blasting efficiency: 100cm²/min

14 gauge steel legs & 16 gauge panels Optimum operating pressure 60-110psi External size: 1680H x 1180W x 940Dmm



gun and vinvl

FFATURES

Perfect for surface preparation on any type where other forms of preparation Ideal for removing paint, rust, scale and

oxidation. Large viewing window gives the operator a wide viewing area.
Oversized hinged top door opening
& large inside work area allows eas: maneuverability.
Hinged door on hopper allows for easy

abrasive changes.
Fluorescent light kit and 90CFM dust

collector help the operator to maintain a good visual.

Rear-mounted dust collector.

Replaceable protective window.Footpedal-controlled siphon blast gun.





3053 TARADEQUIF Durable fabric & synthetic-leather construction

Large 110mm x 55mm acrylic viewing plate Adjustable internal helmet for added comfort Reinforced side ventilation panels for increased airflow

FEATURES

Protect eyes and face from "rebounding" abrasive particles by wearing Abrasive Blasting Hood, Ideal for many abrasive blasting application





BLASTING MEDIA ABRASIVE

For full product specifications go to www.tgbbrands.com.au

TradeQuip "Made for the Trade" Blasting Media Abrasives are designed for use in conjunction with our TradeQuip Mobile Blasting Kits and Blasting Cabinets. Abrasive blasting has been used for many years o clean and remove rust, paint and corrosion. There are many types of abrasive media available, the most common being Garnet. Steel Grit and Glass Bead. These media have an aggressive cut and can rapidly remove paint and rust. However, they can also generate significant heat, potentially resulting in warped metal and etched surfaces, and they cannot be used on fibreglass. Also, chrome, plastic, rubber, trim, and other parts must be removed from a work surface or masked-off before blasting.

Alternatively, less-aggressive media, such as Walnut Shell, will do a great job at removing paint. Walnut Shell does not generate as much heat as other media, and can be used on sheet metal and fibreglass without damaging the base material. However, Walnut Shell as with any abrasive media, will require more clean-up as it leaves particles in the car body's seams and crevices that can be difficult to completely remove. Soda blasting media has non abrasive properties which makes it a very universal blasting media which can be applied to lighter materials such as aluminium, plastic, fibreglass, wood etc. Soda Blasting does not damage glass, rubber, chrome items if they are left on a vehicle for blasting

GARNET 25KG MEDIUM 30/60 3020T TRADEQUIP

Garnet is a gemstone with excellent naturally abrasive properties. This hard abrasive is fast-cutting, low-dust producing and low-consuming, excellent for removing tough coatings, paint, rust and mill scale from steel. Garnet also permits precise feathering control. A good general outdoor surface preparation abrasive.



WALNUT SHELLS 20KG 6-100 MICRON 3022T TRADEQUIP

Walnut Nut shells and other organic materials, don't cause anchor patterns, making them useful for removing dirt, grease, oil, carbon, scale, burrs and paint without changing the underlying substrate. Walnut shells can be an excellent choice for softer surfaces such as wood — they won't cause etching. Walnut shells are one of less abrasive blasting media you can use and are completely biodegrad able, making them among the most environmentally-friendly



GARNET 25KG COARSE 20/40 3023T TRADEQUIP

Garnet is a gemstone with excellent naturally abrasive properties. This hard abrasive is fast-cutting, low-dust producing and low-consuming, excellent for removing tough coatings, paint, rust and mill scale from steel. Garnet also permits precise feathering control. A good general outdoor surface preparation abrasive.



GLASS BEAD 25KG 106-300MICRON 3025T TRADEQUIP Glass beads are used for general cleaning, peening and cosmetic

finishing of sensitive metal surfaces; removing automotive paint; brightening grout and removing fungus and calcium deposits from tile; polishing cast iron, stainless steel, aluminium, propellers and turbine blades. Glass Beads are environmentally friendly and can be used in many blast applications to provide a finish with no profile Use while working with metal, plastic or rubber materials to clean



SODA BI CARB 22KG TRADEQUIP 3028T (Product of America)

Clean tools, strip paint and more with Soda Bi-Carbonate. The medium-sized crystals provide blasting power to smooth and strip paint without damaging other surfaces. Works with aluminum, steel stainless steel, fibreglass and more.



Capacity

Mobile Blasting Kit 37 Litre Capacity 3008 TRADEQUIP

Tank capacity: 37 Litre Working pressure: 60-125psi Air delivery: 400-600 Ltr p/min. @ 125psi (dependent on nozzle size) 4 ceramic nozzle tips: 2.0 2.5 3.0 3.5mm

Hose length: 2.4M 508H x 305Ø



FEATURES leavy duty welded steel design

High volume extra large valve.

Designed for high flow with minimal air input. Blast gun fitted with safety trigger. Heavy-wall blast hose. Durable wheels. Safety pressure-relief valve. Safety mask, thread tape and refill funnel Onboard pressure regulator Easy to fill screw tank cap

Porta Power Kit

9 Piece Kit Blow mould carry case. 530 x 500 x 110mm Weight: 24kg



2011T TRADEQUIP

INDUSTRIAL

GUALITY

Set Includes: 4 x Hooks - 2 Large and 2 Small 2,000kg Mini Ram - Compressed 139mm > Stroke 76mm 4,000kg Mini Ram - Compressed 42mm > Stroke 16mm 10,000kg Mini Ram - Compressed 118mm > Stroke 60mm 4,000kg Porta Power Ram - Compressed 276mm > Stroke 132mm 10.000kg Porta Power Ram - Compressed 350mm > Stroke 150mm 2.000kg Pull Back Ram - Extended 537mm > Stroke 128mm 5,000kg Pull Back Ram - Extended 613mm > Stroke 130mm

Porta Power Kit BPP20T - BORUM

Safe working capacity: 20,000kg Extension tubes: 125, 255, 510, 700mm 3 each. 70mm connective tube & 60mm joint connector tube Base. Ram toe. Plunger toe Wedge toe, V-base, Wrench Retracted ram length: 285mm Ram stroke: 125mm Hydraulic hose length: 1470mm Inc. GST \$1582.90 Weight: 62kg

FEATURES

Constructed of high-grade steel and built to exacting standards for quality and durability. Lead-free paint finish is oil, grease and dirtresistant for easy cleanup.
High quality hydraulic steel cylinder unit helps to reduce wear and extend service life. Piston-ram is treated and polished Hydraulics are powered with a high quality oil which offers better corrosion resistance and high/low temperature flexibility Heavy walled extension tubes



Air/Hydraulic Pump 2054T TRADEQUIP

Maximum output pressure: 10,000psi Usable hydraulic fluid capacity: 2.25 Litres Operating air pressure: 90-145 psi Air consumption: 7.5CFM @ 100 psi Oil delivery with No Load: 49.5 cu.in/mir Oil delivery with Load: 7.6 cu.in/min Input (Air) port thread: 1/4" -18 NPT Output (Oil) port thread: 3/8" -18 NPT

FEATURES

Durable light-weight corrosion-free aluminium. Built-in overload system prevents pump from being used beyond its safety capacity. Ergonomic hand/foot activation lever Air/oil filters minimise contaminants in hydraulic systen Perfect for porta power rams & bead breakers.
Compact design fits in truck storage boxes. Air exhaust muffler for quiet operation

2054H Hose to suit - \$189 ex ast \$207.90 inc ast



Porta Power Kit 2010T TRADEQUIP

Safe working capacity: 10,000kg 14 Piece Kit containing pump and hose fittings

Ram length retracted: 322mm Ram length extended: 452mm Extensions: 110,265,365,520mm Case: 905L x 385W x 175H mm Hydraulic hose length: 1500mm Hydraulic oil capacity: 650ml Adaptor diameter: 33mm Weight: 31ka



FEATURES

Spring loaded ram return system, allowing controlled retraction of the ram.
Pump may be used in horizontal & vertical position. Constructed of high-grade steel and built to exacting standards for quality and durability.

Lead-free paint finish is oil, grease and dirt-resistant. Pump has an automatic overload system Easily adapts to hoses, rams, pumps, spreaders, and other accessories using common 1/4" fittings



FEATURES

Durable steel construction

pump (sold seperately).

Clamps to wheel rim & breaks bead

simply with up to 5,000kg of force.

Requires 10,000psi air/hydraulic

Combi Portable Bead Breaker 5,000KG

BTBB05 /= B O R U M

Working load limit: 5,000kg Pressure connection: 3/8"-18NPTF Rated pressure: 10.000psi Maximum rim size: 26' Suits 1,2 & 3 pce rims (up to 26") with pry bar / bead loosening pockets



Giant Portable Bead Breaker 13.000KG

BTBB13 /= B O R U M Working load limit: 13,000kg

Pressure connection: 3/8"-18NPTF Rated pressure: 10,000psi Suits 5 pce rims 635-1,295mm (25"-51") with pry bar / bead loosening pockets Maximum rim size: 26"

Ram stroke: 105mm

FFATURES Economical solution for earthmove

wheels 25" – 51" multi-piece rims with pry bar pockets. Hydraulically clamps on wheel

Durable steel construction. Hydraulic nower breaks beads in seconds

Requires 10,000psi air/hydraulic pump (sold seperately).



















ALL BORUM DRILL PRESSES FEATURE

Flexible worklight. Engineering style work table Oversize micro-switch activated safety guard. Low-noise belt drive with cast iron balanced pullevs. Safety ON-OFF switch fitted with a dust cover and positive action push buttons plus a large (Red) self locking "Emergency Stop" hinge cover. Precision spindle bearing for long life & high accuracy. Table control via hand crank and gear rack with high load capacity. Long quill stroke, easy to adjust depth stop at the capstan handle.

Thick-walled, precision-ground column for extra rigidity. Powerful long-life commercial drive motor provides high reliability. Ground set-up areas on table and base plate. Solid rotating work table with diagonal clamping slots

The same reliable 'Heavy Duty Industrial **Quality Drill Presses**' since we started manufacturing them in 1984... but with the benefit of some 21st Century features



For full product specifications go to www.tgbbrands.com.au

1HP Pedestal Drill Press 16 Speed CH18FT FAIB ORUM

Motor: 240Volt 1HP Number of speeds: 16 Spindle taper: MT2 Spindle speeds: 200-3160rpm

Max. drilling capacity: 20mm Max. spindle stroke: 82mm Max. distance spindle to table: 775mm

Max. distance spindle to base: 1270mm Chuck: 16mm

Swing: 430mm Table diameter: 350mm Diameter of column: 80mm Size of base: 460x270mm

Overall height: 1625mm







2HP Pedestal Drill Press 12 Speed CH30T /= BORUM

Motor: 240Volt 2HP Number of speeds: 12 Spindle taper: MT4 Spindle speeds: 210-2160rpm

Max. drilling capacity: 32mm Max. spindle stroke: 122mm Max. distance spindle to table: 720mm

Max. distance spindle to base: 1230mm Chuck: 16mm

Swing: 535 Size of table: 473x410mm Diameter of column: 92mm Size of base: 572x495mm Overall height: 1780mm



TOB

Scan code to go to our Top Tips guides and learn how to extend the life of your **TQB Brands**

equipment

for instructional & pre-start videos



Motorcycle Lifter 360KG

2102T TRADEQUIP

Safe working capacity: 360kg Height: 205 - 780mm Platform: 490W x 1345l mm Weight: 95kg

Features wide

MADE FOR THE



Motorcycle Scissor Lift 500KG

2104T TRADEQUIP

Safe working capacity: 500kg Height: 95 - 420mm Platform dimensions: 450x150mm Weight: 13.8kg



Designed to deliver the ideal lift for use with motorcycles, ATV's, tractors, personal watercraft, and snowmobiles. Lifts back wheel off lift table for tyre/wheel

change .

Powder coated structural heavy duty steel

Rotate lead screw to adjust & raise the lift. Bolt down lugs to prevent unwanted mov



Motorcycle Lifter 450KG

2101T TRADEQUIP

Safe working capacity: 450kg Height: 175 - 750mm Platform: 680W x 2200Lmm Weight: 120kg





FEATURES

Ideal lift for use with motorcycles, ATV's, tractors, personal watercraft & snowmobiles Locking bar for safety.

Powder coated structural heavy duty stee Extra Long Full width loading ramp. Step-less rate of lowering irrespective of load Oil trap plate for easy drainage.

2 foot pedals for raising & lowering - for easy

hands free operation. Fitted with 2 position platform locking device

to prevent accidental lowering.

Quality wheels and swivel castors making it easier to position and move around. Lockdown bolts to prevent unwanted movement during use. Does not include tie down strans



Motorcycle Lifter Air Actuated 680KG 2103T TRADEQUIP

Safe working capacity: 680kg Heiaht: 185 - 825mm Platform dimensions: 710 x 2000mm Required air pressure: 0.75-0.85Mpa



oated structural heavy duty stee Stepless rate of lowering irrespective of

Lockdown bolts.

hands free operation. Fitted with 2 position platform locking device







Weight: 169kg

Designed to deliver the ideal lift for use with motorcycles, ATV's, tractors, personal watercraft and snowmobiles Locking bar for safety.

Extra long full width loading ramp.

the load.
Oil trap plate for easy drainage

2 foot pedals for raising & lowering - for ea





Workshop Trolley (Polymer) 6045 TRADEQUIP

Safe working capacity: 226kg 3 x 100mm deep shelves 125x30mm smooth rolling rubber swivel castors 75kg tool tray capacity 875L x 430W x 830Hmm

FEATURES

Deep shelves for plenty of storage. Will not dent, rust or chip. Convenient push handle.
Two swivel and two fixed smooth rolling rubber castors.
No painting required. Cleans easily. Virtually maintenance free.

Workshop Trolley 3 Tool Trays 6004 TRADEQUIP

MADE FOR THE

Safe working capacity: 150kg Powder coated .6mm steel 100mm composite castors 845L x 410W x 780Hmm

FEATURES

This three shelf workshop tool trolley is durable enough for moving tools and car parts. Deep shelves give you plenty of storage for your tools and parts.



Safe working capacity: 100kg One lockable drawer 100mm composite rubber castors Two 100mm deep shelves 770L x 370W x 830Hmm



FEATURES

Heavy gauge steel construction. Quality 35mm ball bearing slide drawer Side handle for comfort and control. Tough enamel finish.



150kg

Capacity

MADE FOR THE TRADE

Workshop Trolley (Polymer)

6042T TRADEQUIP MADE FOR THE Safe working capacity: 226kg TRADE Tray: 900L x 600W x 65Hmm Tray capacity: 113kg (each) Smooth rolling rubber castors: 125D x 25Wmm Ground clearance: 140mm Weight: 22kg

For full product specifications go to www.tqbbrands.com.au

MADE FOR THE

226kg

Capacity

Two deep and wide shelves for plenty of storage.
Convenient push handle. Virtually maintenance free. Two swivel and two fixed smooth rolling rubber castors Will not dent, rust or chip. No painting required. Cleans easily.

Workshop Trolley (Polymer)

6043T TRADEQUIP

Safe working capacity: 226kg Tray capacity: 76kg (each) Trav: 900L x 600W x 65Hmm

Smooth rolling rubber castors: 125D x 25Wmm Ground clearance: 140mm

Three deep and wide shelves for plenty of storage.
Convenient push handle. Virtually maintenance free. Two swivel and two fixed smooth rolling rubber castors.
Will not dent, rust or chip. No painting required. Cleans easily.

Weight: 33.5kg



Workshop Trolley (Polymer) 6046 TATRADEQUIP

226kg Capacity

Safe working capacity: 226kg 8 Parts bins 241x152x127mm 24 Parts bins 165x101x76mm 125x30mm rubber swivel castors 85kg tool tray capacity 1000L x 435W x 850Hmm

MADE FOR THE

MADE FOR THE

FEATURES

Deep shelves give you plenty of storage for your tools and parts Industrial grade castors. Will not dent, rust or chip Convenient push handles.
No painting required. Cleans easily

Self-Evacuating Oil Drainer 65 Litre 1046T TATRADEQUIP

Capacity: 65 Litres Working height: 1080-1600mm Discharge pressure: 12psi Telescopic adjustment Air inlet: 1/4" BSP

TELESCOPIC COLLECT STORE/CARRY DISCHARGE

MADE FOR THE TRADE

FEATURES Collect, transfer, evacuate

used engine oils, transmission fluids, power steering fluids etc. Top quality heavy-gauge steel collection tank with adjustable telescopic drain Offset drain howl and Tank

oil level indicator. Air pressure relief valve prevents.
Sturdy rubber front wheels

and ball bearing-mounted rear castors provide stability and easy maneuverability. Lead-free paint is oil, grease and dirt-resistant abrasion resistant hose



Truck Fluid Drain Pan with Hand Pump 65 Litre

1147T TRADEQUIP

Lightweight high-impact polypropylene. Oil and coolant resistant Manoeuvrable 4" castors Tank size: 1300x730x200mm




FEATURES

Lightweight high-impact polypropylene. Suitable for engine oil, coolant and transmission fluid. Built-in rotary hand discharge pump. Removable metal filter screen Smooth rolling rubber castor wheels.



Capacity



rotary hand

Truck Fluid Drain Pan 60 Litre

1146T TOTRADEQUIP

Capacity: 60 Litres Enamel steel construction Oil and coolant resistant Size: 1174 x 641 x 673mm Front swivel castors



FEATURES

Enamelled steel construction Oil and coolant resistant. Removable metal screen Two front swivel castors. Two rear fixed wheels Brass drain valve. Transfer pump coupling

Removable metal filter 910L x 725W x 165Hmm Size: 1120L x 780W x 195Hmm FEATURES Enamelled steel constructio Oil and coolant resistant. Removable metal screen

1145T TRADEQUIP

Minimum tray clearance: 196mm Reservoir dimensions:

Truck Fluid Drain Pan 95 Litre

which are braked. front or side. Drain valve & Grab handle

Capacity: 95 Litres

Removable metal filter



95 LITRE Capacity











Steel Workbench 1014T TRADEQUIP

Safe working capacity: 90kg Work surface: 1510x700mm Raised edge height: 50mm 1520L x 710W x 830Hmm

Weight: 48kg

FEATURES

Sturdy steel construction High gloss enamel paint finish. Raised protective edge to work surface Adjustable feet for levelling on uneven floors Quick and easy to assemble Easily wipe dirt and grime from surface with a soft cloth.

90kg Capacity MADE FOR THE

3 Drawer Steel Workbench

1012T TATRADEQUIP

Safe working capacity: 300kg Heavy duty steel construction High gloss enamel paint finish Includes bottom shelf & 3 locking drawers Each drawer holds up to 50kg 2000L x 860H x 640Wmm

For full product specifications go to www.tgbbrands.com.au

Manufactured from high quality, heavy-duty steel and features a large surface for more work space and an extended lip around the surface of the table.

The tough high gloss enamel paint finish is designed to provide years of protection against normal wear and tear

-300kg Capacity MADE FOR THE TRADE

Mobile Workbench

6047 TRADEQUIP Safe working capacity: 250kg Bench top capacity: 150kg Bench top: 1200L x 640Wmm 1200L x 640W x 875H mm Shelf: 1110L x 460Wmm Shelf capacity: 100kg

Weight: 56.5kg **FEATURES**

Heavy duty rolled edge steel construction. Convenient removable 13mm benchtop rim to contain leaking fluids

when working on engines and transmissions. Quality castors (2 swivel with brake). Lockable steel drawer with ball bearing slides

Mobile Bench

1073T TRADEQUIP

Safe working capacity: 300kg Work surface: 1100 x 700mm 1100L x 700W x 830H mm

Quality castors - two fixed & two locking swivel.



FEATURES

Sturdy steel construction

1100mm

High gloss enamel finish. Heavy-duty handle

22 Bin Parts Storage Rack

6053 TRADEQUIP MADE FOR THE Working load capacity: 100kg TRADE 15 parts bins: 345x105x75mm (3kg load capacity) 4 parts bins: 345x140x150mm (5kg load capacity)



36 Bin Parts Storage Rack 6054 TRADEQUIP

Working load capacity: 200kg 15 parts bins: 345x105x75mm (3kg load lapacity) 12 parts bins: 345x140x150mm (5kg load lapacity) 9 parts bins: 345 x 205 x 150mm

(9kg load lapacity) Swivel castor diameter: 100mm 8801 x 410W x 1705Hmm

FEATURES

Sturdy nine-tier steel powder coated rack. Zinc plated wire shelving with bin locating guides Quick & easy clip together adjustable shelves. Stackable bins made of moulded polypropyle Ideal for garage, workshop, office, shed. Powder coat frame resists corrosion Quality swivel castors (2x lockable). Convenient access to removable bins



Mobile Workshop Table 6024T TRADEQUIF

Safe working capacity: 45kg Working height: 930-1270mm Castor wheel diameter: 75mm Top dimensions: 809L x 475W x 42Hmm Main tray dimensions: 580L x 308W x 38Hmm Overall dimensions: 870L x 755W x 942Hmm Weight: 19.5kg TRADE **FEATURES** The Heavy Duty steel construction Easily handles loads up to 45kg.

Solid composite rubber castors.

Simple height adjustment gives you plenty of options for lowered cars or SUV's. **Capacity**

Mobile Workshop Table with Drawer

6056T TRADEQUIP 340x300x45mm drawer Adjustable from 860-1200mm high Includes drawer and top tray liner 80kg Distributed load capacity 730x500x25mm top trav

FEATURES

Height adjustable for mo Ball Bearing wheels for easy moving.
Multi-functional top table with 3 compartments and 6 screwdriver holes. Top EVA mat for skid resistance. Extra drawer for more



Truck Mobile Workshop Table BMWST FAIB OR UM

Safe working capacity: 34kg Adjustable working height: 960-1500mm Distance between front casters: 955mm Caster wheel diameter: 75mm Table top: 797L x 695W Main tray: 556L x 695W Depth at full width: 485mm Includes top tray lines



FEATURES

Height adjustable to most commercial vehicles. Extra wide legs to suit commercial vehicles Multi-functional top table with 2 compartments and 8 screwdrive Top EVA mat for skid resistance

Protective bumper for top tray. Strong tubular steel construction Sturdy main support post



Workshop Trolley 2 Drawers & Lockable Sliding Top

6019T TRADEQUIP

Safe working capacity: 100kg Two lockable drawers & top 100mm composite rubber castors Two 75mm deep shelves 700L x 370W x 760Hmm



FEATURES

Heavy gauge steel construction with lockable sliding top. Quality 35mm ball bearing sliding drawers which are locked when top is closed. Side handle for comfort/control when moving Tough enamel finish.

Non slip rubber tool tray liners

100kg Capacity

Workshop Trolley Single Drawer 6020T TRADEQUIP

Safe working capacity: 155kg Lockable drawer: 635L x 320W x 80Hmm Top storage tray: 695L x 405W x 65Hmm Lower storage tray: 750L x 395W x 68Hmm Rubber castors: 100Dmm 775L x 415D x 890Hmm



FEATURES

Heavy gauge steel construction with lockable drawer on smooth runners Two top mounted handles for added control when manoeuvring. Tough enamel finish.

Non slip EVA foam tool tray liner. Two heavy-duty locking swivel casters for control and Large top & bottom shelf giving



Workshop Trolley 4 Drawers with Lockable Top

6052 TRADEQUIP

Safe working capacity: 260kg 4 lockable drawers on 35mm ball bearing slides Two 75mm deep shelves for plenty of storage (one lockable)

Top 2 drawers (each): 310W x 370D x 50Hmm Middle drawer: 680W x 370D x 70Hmm Large drawer: 660W x 370D x 100Hmm

Two swivel and two fixed 100mm smooth rolling composite rubber castors 850L x 445D x 972Hmm



FEATURES

Heavy gauge steel construction with lockable sliding top on smootl ball bearing runners. Quality ball bearing slide drawers that lock when top is closed Side handle for comfort and control when manoeuvring Tough high gloss enamel finish. Non slip rubber tool tray liners. Heavy-duty ergonomic grip handle
Two heavy-duty locking castors fo control and stability





EASY TO

Ideal for Engine and

Transmission Rebuilds





Stackable bins made of moulded polypropylen

Ideal for garage, workshop, office, shed.

Powder coat frame resists corrosion

Quality swivel castors (2x lockable).

Convenient access to removable bins

DEC 1190

TAGLE PROPERTY IS

ABOUT EAGLE PRO HYDRAULICS

With nearly 3 decades experience of manufacturing hydraulic tools for industrial applications, Eagle Pro Hydraulics has become the trusted partners for applications spanning from offshore plant maintenance to mining, infrastructure, commercial and industrial. Eagle Pro Hydraulics are manufactured to ISO 9001:2018 through international quality assurance programs which involve consistent observation of administration, management, manufacturing and production control. Eagle Pro hydraulic cylinders meet or exceed ANSI B30.1. This results in reliable and dependable high-quality products you can count on every time.

ES SERIES

Single Acting General Purpose

Eagle Pro ES series redefines durability for the harshest of industrial environments with its high strength alloy steel construction. Hardened and chromed piston ensures superior product life by reducing wear and corrosion.

Eagle Pro ES series is not only durable, it gets the job done! Heavy-duty, straight pull return springs provide fast retraction. For greater flexibility and easy mounting, the ES series comes with collar, multiple piston threads, and base mounting holes. Hardened and E-coated snap-in type saddle prevents piston jamming and mushrooming, practically eliminating downtime. The female coupler comes with a dust cover – preventing dirt and debris from entering the hydraulic system.

The Eagle Pro ES series also complies with ASME B30.1 standard.



EDH SERIES

Double Acting Hydraulic

The Eagle Pro EDH series incorporates a hollow piston design that allows both pushing and pulling forces. The construction of high strength alloy steel maximizes durability. The EDH series' double acting operation ensures fast and controlled piston reaction time.

Accidental over-pressurization is prevented with a built-in safety valve. The collar, piston threads, and base mounting holes enable easy fixturing.



ED SERIES

Double Acting General Purpose

The Eagle Pro ED series produces fast and controlled piston contraction thanks to the double acting operation.

A built-in safety valve prevents accidental-over pressurization. Most models include collar, piston threads, and base mounting holes to make fixturing a simple task.

Piston jamming and mushrooming is prevented by the cylinder's hardened, and E-coated snap-in saddle. The ED series enhances durability with a hardened and chromed piston that reduces wear and corrosion. ED series cylinders are easy to move around the job site with the addition of carrying handles (and eyebolts on larger models) that ease positioning and carrying. A durable, anti-corrosive finish is added using an environmentally friendly coating process.



EDX SERIES

Double Acting High Tonnage

Eagle Pro EDX series maximizes durability with the use of a high strength alloy steel. The built-in safety valve prevents accidental over-pressurization. The EDX is easy to carry and position with the included eyebolts. Optional tilt saddles are also available. The hardened and chromed piston minimizes wear and corrosion damage. The incorporation of base mounting holes enables easy fixturing. An environmentally friendly coating process provides a highly durable finish.

EDX-1006T EDX-2006T

EDX-1002T

EL SERIES

Single Acting With Locking Collars

The Eagle Pro EL series includes an alloy steel lock nut for mechanical load holding. The EL series is constructed of a high strength alloy steel to maximize durability. The hardened chrome piston reduces damage caused from wear and corrosion. The over flow port functions as a stroke limiter.

The EL series includes hardened grooved replaceable saddles. Composite bearings prevent metal-to-metal contact. Quick reaction times are obtained through with heavy-duty straight pull return springs. An environmentally friendly coating process produces a finish that further increases durability.



ESL SERIES

Low Profile And Pancake Style

Featuring a low-profile, or flat design, the Eagle Pro ESL series cylinder is an optimal choice for confined spaces. The hardened and chromed piston is constructed of high strength alloy steel that increases durability by reducing wear and corrosion.

The grooved piston end does not require a saddle and the inclusion of mounting holes permits easy fixturing.

Retraction time is quick thanks to the heavy duty, straight pull return springs. An environmentally friendly coating process is used to provide the durable anti-corrosion finish.



ESH SERIES

Single Acting Hollow Piston

The Eagle Pro ESH Series allows for both pushing and pulling by incorporating a hollow piston design. The heavy-duty return spring provides notoriously quick reaction times. Easy fixturing with the inclusion of collar threads.



ESH-302

EPA SERIES

Dual Speed Hand Pumps

The Eagle Pro EPA series hydraulic hand pumps are some of the most durable, powerful and reliable hand pumps in the industry today. The EPA series feature valve blocks that are machined from a single piece of high strength aircraft grade aluminum and high capacity reservoirs made from alloy steel* that maximizes durability. The EPA series hand pumps are compact and easy to carry around the job site. To get the job done faster, these powerful dual speed pumps offer some of the best flow rates in the industry. All of the EPA series hydraulic hand pumps feature an internal safety valve to prevent system damage.









WHILST THE ENTIRE RANGE IS NOT IN STOCK, IT IS AVAILABE FOR SPECIAL ORDER



	Model	Description	Cylinder Capacity @ 10,000PSI	Stroke	Cylinder Effective	Oil Capacity	Collapsed Height	Extended Height	Price	Price
			(700 BAR)		Area		A	В	ex GST	inc GST
			Metric Kg	MM	CM ²	CM ³	MM	MM		
	ES-50	SINGLE ACTING RAM	5,000	16	7.1	11.4	42	58	\$399.00	\$438.90
	ES-51	SINGLE ACTING RAM	5,000	25	7.1	17.8	110	135	\$489.00	\$537.90
	ES-55	SINGLE ACTING RAM	5,000	127	7.1	90.2	215	342	\$619.00	\$680.90
	ESL-50	SINGLE ACTING RAM PANCAKE STYLE	5,000	6	7.1	4	33	39	\$389.00	\$427.90
	ES-1010	SINGLE ACTING RAM	10,000	257	14.5	372.65	349	606	\$799.00	\$878.90
	ES-102	SINGLE ACTING RAM	10,000	54	14.5	78.3	121	175	\$489.00	\$537.90
	ES-106	SINGLE ACTING RAM	10,000	156	14.5	226.2	247	403	\$799.00	\$878.90
	ESL-100	SINGLE ACTING RAM PANCAKE STYLE	10,000	10	14.5	15	42	53	\$569.00	\$625.90
	ESL-101	SINGLE ACTING RAM PANCAKE STYLE	10,000	38	14.4	55	88	126	\$599.00	\$658.90
	ESH-121	SINGLE ACTING RAM HOLLOW PISTON	13,000	42	18.4	77.3	120	162	\$969.00	\$1065.90
	ES-1510	SINGLE ACTING RAM	15,000	254	21.2	538.48	373	627	\$1099.00	\$1208.90
	ES-1514	SINGLE ACTING RAM	15,000	356	21.2	754.72	474	830	\$1199.00	\$1318.90
	ES-152	SINGLE ACTING RAM	15,000	51	21.2	108.12	149	200	\$759.00	\$834.90
	ES-154	SINGLE ACTING RAM	15,000	101	21.2	214.12	200	301	\$929.00	\$1021.90
	ESH-206	SINGLE ACTING RAM HOLLOW PISTON	20,000	49	32.8	161	162	211	\$1749.00	\$1923.90
	ESL-200	SINGLE ACTING RAM PANCAKE STYLE	20,000	11	28.3	31	51	62	\$699.00	\$768.90
	ESL-201	SINGLE ACTING RAM PANCAKE STYLE	20,000	45	28.3	127	98	143	\$769.00	\$845.90
	ES-251	SINGLE ACTING RAM	25,000	26	33.2	86.32	139	165	\$999.00	\$1098.90
	ES-252	SINGLE ACTING RAM	25,000	50	33.2	166	165	215	\$1079.00	\$1186.90
	ES-254	SINGLE ACTING RAM	25,000	102	33.2	338.64	215	317	\$1179.00	\$1296.90
	ES-256	SINGLE ACTING RAM	25,000	158	33.2	524.56	273	431	\$1349.00	\$1483.90
	ESH-302	SINGLE ACTING RAM HOLLOW PISTON	30,000	64	48	307	179	242	\$1888.00	\$2076.80
	ESH-306	SINGLE ACTING RAM HOLLOW PISTON	30,000	156	48	744	330	485	\$1999.00	\$2198.90
	ESL-300	SINGLE ACTING RAM PANCAKE STYLE	30,000	13	41.8	54	58.5	71	\$1055.00	\$1160.50
	ESL-302	SINGLE ACTING RAM PANCAKE STYLE	30,000	62	41.8	259	117	179	\$979.00	\$1076.90
	EL-506	SINGLE ACTING RAM LOCKING COLLAR	50,000	150	70.8	1062	264	414	\$1929.00	\$2121.90
\	ES-502	SINGLE ACTING RAM	50,000	51	70.9	361.59	176	227	\$1229.00	\$1351.90
1	ES-506	SINGLE ACTING RAM	50,000	159	70.9	1127.31	282	441	\$1699.00	\$1868.90
	ESL-500	SINGLE ACTING RAM PANCAKE STYLE	50,000	16	63.6	102	67	83	\$979.00	\$1076.90
	ESL-502	SINGLE ACTING RAM PANCAKE STYLE	50,000	60	63.6	382	122	182	\$1199.00	\$1318.90
	ESH-603	SINGLE ACTING RAM HOLLOW PISTON	60,000	76	87.4	664	247	322	\$3199.00	\$3518.90
	EL-1002	SINGLE ACTING RAM LOCKING COLLAR	100,000	50	132.7	663.5	187	237	\$2399.00	\$2638.90
					1			1		

		Cylinder Capacity		Max. Cylin	der Capacity	Cylinder Effe	ctive Area	Oil Ca	pacity		
Model	Description	@ 10,000PSI (700 BAR)	Stroke	Advance	Retract	Advance	Retract	Advance	Retract	Price ex GST	Price inc GST
		Metric Kg	MM	METRIC TON	METRIC TON	CM ²	CM ²	CM ³	CM ³		
EDX-506	DOUBLE ACTING RAM	50,000	150	53	26	75.4	36.9	1,131	1,131	\$1799.00	\$1978.90
EDX-1006T	DOUBLE ACTING RAM	100,000	150	93	43	132.7	61.9	1,991	928	\$2549.00	\$2803.90
EDH-307	DOUBLE ACTING RAM HOLLOW PISTON	30,000	178	33	22	47.7	32.4	849	577	\$2249.00	\$2473.90
EDH-603	DOUBLE ACTING RAM HOLLOW PISTON	60,000	89	60	39	87.4	56.2	778	481	\$2549.00	\$2803.90
EDH-606	DOUBLE ACTING RAM HOLLOW PISTON	60,000	166	60	39	87.4	56.2	1451	891	\$3199.00	\$3518.90
ED-1012	DOUBLE ACTING RAM	10,000	305	10	3	14.5	4.9	443	149.5	\$1799.00	\$1978.90

			Usable Oil	Pressure Rating		Oil Displacement Per Stroke		Handle			
Model	Description	Cylinder Type	Speed	Volume	1st Stage	2nd stage	1st Stage	2nd Stage	Force	Price ex GST	Price inc GST
				CM ³	BAR	BAR	CM ³	CM ³	KG	ex 031	IIIC UST
EPA-10921A	HAND PUMP, S/A, TWO SPEED, 55 IN3	SINGLE ACTING	TWO	750	25	700	33	3.3	49	\$699.00	\$768.90
EPA-12321A	HAND PUMP, S/A, TWO SPEED, 140 IN3	SINGLE ACTING	TWO	2300	25	700	33	3.3	49	\$1019.00	\$1120.90
EPA-12322A	HAND PUMP, D/A, TWO SPEED, 140 IN3	DOUBLE ACTING	TWO	2300	25	700	33	3.3	49	\$1039.00	\$1142.90

Model	Description	Internal Diameter Length H		Hose	Working Pressure	Burst Pressure	Hose End Configuration		Price	Price
Model	Description	MM	MM	Material	PSI	PSI	Pump End	Cylinder End	ex GST	inc GST
EH-8206F	1/4" IDX6' RBR HYDHOSE 3/8" NPT EAB-201B	6	1800	-	10,000	20,000	3/8" NPT	3/8" NPT	\$199.00	\$218.90

Model	Description	Max. Pressure	Typo	Thread	Female Coupler	Male Coupler	Price	Price
Model	Description	PSI	Type	IN	remale Couplei	Male Couplet	ex GST	inc GST
EAB-201	3/8" MALE/FEMALE HIGH FLOW QUICK	10,000	HIGH FLOW	3/8" - 18NPT	EAB-201A	EAB-201B	\$85.00	\$93.50

	Model	Description	Pressure Rang		Thread	Gauge Diameter	Price	Price
	Description	PSI	MPa			ex GST	inc GST	
	EG-2510	2.5 IN. 15,000 PSI PRESSURE GAUGE	0 - 15,000	0 - 100	1/4" - NPT	2.5	\$239.00	\$262.90

Model	Description	Male Coupler Thread	Female Coupler Thread	Gauge Port Thread	Price	Price
Model	Description	IN/D	IN/E	IN/C	ex GST	inc GST
EGA-005	GAUGE ADAPTOR	3/8" - NPT	3/8" - NPT	1/4" - NPT	\$89.00	\$97.90

Model	Description	Cylinder Capacity @ 10,000 PSI (700 BAR)	Oil Capacity	Tip Clearance	Maximum Spread Distance	Cylinder Effective Area	Weight	Price ex GST	Price inc GST
		US TON	CM ³	MM/A	MM/B	CM ²	KGS	EX 031	IIIC 031
EFS-14	14 TON HYDRAULIC SPREADER	14	78.33	6.09	81.02	14.51	7.17	\$2389.00	\$2627.90









Portable Evaporative Cooler 750W

MADE FOR THE

1029T TRADEQUIP 240V/50Hz/750W 3 speed motor Max. air flow: 23.000 m3 per hour

Water consumption: 20-35 litres per hour Effective cooling area: 200-260sqm Cooling area: 200-260m2 Water tank capacity: 200 Litres 1800H x 1600W x 780Dmm

> **UPGRADED 5 BLADE DESIGN INCREASING AIR VELOCITY**



Weight: 128kg

easy portability



Timer Panel

TRADEQUIP EVAPORATIVE COOLERS FEATURES & BENEFITS

Moulded polyethylene housing will not crack and is rust & leak proof. Environmentally-friendly alternative to traditional reverse cycle A/C. Cools without chemicals or refrigerants.

Long-term dependability. Near maintenance free operation.

Cools where traditional cooling methods are impractical or cost-prohibitive. Remote control speed adjustment. Direct drive. LCD 24 hour timer panel. Easy to read water level sight tube gauge.

Dual pour in refill water inlet and/or 3/4" hose fitting for automatic tap refill. Adjustable water flow & drain valve. Nylon castors for easy portability.

750 Watts

For full product specifications go to www.tgbbrands.com.au

Portable Evaporative Cooler 550W

1027T TRADEQUIP 240V/50Hz/550W 3 speed motor Max. air flow: 18,000 m3 per hour

Effective cooling area: 100-150sqm Water consumption: 12-18 litres per hour Water tank capacity: 100 Litres 1510H x 1120W x 680Dmm Weight: 58kg















MADE FOR THE

TRADE



240V/50Hz/750W 3 speed motor Max. air flow: 23,000 m3 per hour Effective cooling area: 150-200sqm Water consumption: 12-18 litres per hour

Water tank capacity: 130 Litres 1730H x 1120W x 680Dmm Weight: 63kg









TRADE

Portable Industrial Spot Cooling Air Conditioners TO TRADEQUIP

Code	1031T	1032T	1033T
Power Unit	240V 50Hz	240V 50Hz	240V 50Hz
Rated Power	950W	2000W	3000W
Mains Plug	10 Amp	15 Amp	15 Amp
Cooling Capacity	2.7KW/9200Btu	4.5KW/15300Btu	6.5KW/22200Btu
Max. Air Flow	400m3 p/hr	800m3 p/hr	1200m3 p/hr
Noise Level	55dB(A)	60dB(A)	65dB(A)
Operating Temp.	18º - 45º C	18º - 45º C	18º - 45º C
Suction Pressure	2.5Mpa (Max.)	2.5Mpa (Max.)	2.5Mpa (Max.)
Discharge Pressure	4.5Mpa (Max.)	4.5Mpa (Max.)	4.5Mpa (Max.)
Dimensions	855Hx430Wx405D	1035Hx520Wx480D	1245Hx640Wx560D
Excl. GST	\$1599	\$3199	\$4399
Incl. GST	\$1758.90	\$3518.90	\$4838.90



TRADEQUIP INDUSTRIAL AIR CONDITIONERS FEATURES & BENEFITS

Compact vet powerful. Wide operating range of 18°- 45°C

Single duct system for easy installation. Capillary tube construction for simplicity. 5 Litre self-contained condensation tank for easy removal and emptying.

Heavy duty compressor with automatic restart and short cycle protection

Motors and compressors have overload protection. Durable and long lasting steel construction.

Heavy duty locking castors and handles for easy manoeuvrability.

Easy to use plug in and place the hot air duct out of window/door or into false ceiling.

TradeQuip "Made for the Trade" Portable Air Conditioners offer a quick spot cooling solution with strong air flow and easy installation.



*Freight Rates May Apply



1096T TRADEQUIP

Power output: 30kW - 102,360 Btu/h Motor: 240V/50Hz 10A 230W Air delivery: 720cubic metres per hour

Noise level: 76dB(A) Fuel consumption: 2.4kg/hr Tank capacity: 38 Litres

Dimensions: 880 x 456 x 590mm

Weight: 21kg







RUNS UP TO 9 HOURS ON A SINGLE FILL

FEATURES

Burns diesel or kerosene. Built in oil burner Electronic flame control system Safety overheat thermostat and pressure switch. Stainless steel heat exchanger.

Double skinned combustion chamber for thermoacoustic insulation and safe low surface temperature. Preheated oil filter. Twist lock fuel cap with cable.

Pre-purge and post-ventilation cycles





Workshop Heater 50kW

1097T TRADEQUIP the trusted brand in equipment

Power output: 50kW - 170,600 Btu/h Motor: 240V/50Hz 10A 340W

Air delivery: 1100 cubic metres per hour

Noise level: 77dB(A)

Fuel consumption: 4kg per hour

Tank capacity: 56 Litres

Dimensions: 1090 x 490 x 585mm

Weight: 27kg

ADE FOR THE TRADE

SEASONAL LINE

Limited

Stock



RUNS UP TO 9 HOURS ON A SINGLE FILL

FEATURES

Burns diesel or kerosene. Built in oil burner. Electronic flame control system Safety overheat thermostat and pressure switch. Stainless steel heat exchanger. Double skinned combustion chamber for thermo-

acoustic insulation and safe low surface temperature. Preheated oil filter. Twist lock fuel cap with cable. Pre-purge and post-ventilation cycles

SEASONAL LINE

Inc. GST **\$**933.90



National Phone: 1300 133 129 Web: www.hsy.com.au

THIS IS A PRICED PRODUCT GUIDE WITH RTP VALID TO 30 SEPT. 2125. AT TIME OF GOING TO PRINT, EXCLUDING SOME NEW PRODUCTS, STOCK IS PLENTIFUL WITH REPLENISHMENT STOCK IN PRODUCTION AND SHIPPING AT THE TIME THAT YOU PLACE
YOUR ORDER, YOUR PRODUCT MAY NOT BE IN STOCK BUT AN ETA WILL BE PROVIDED. OUR BEST EFFORTS ARE BEING MADE TO MAINTAIN STOCK LEVELS OF PRODUCTS FEATURED IN THIS CATALOGUE, BUT THE SITUATION REMAINS FLUID DUE TO
BOTTLENECKS IN GLOBAL SUPPLY CHAINS, YOUR PREFERRED DISTRIBUTOR WILL BE UPDATED AS SOON AS PRACTICAL WITH ANY INFORNATION AFFECTING THIS PUBLICATION, PRODUCTS DISTRIBUTED BY TOB BRANDS PTY LTD ARE DESIGNED.
INTENDED & MARKETED FOR TRADE AND COMMERCIAL USE ONLY ERRORS AND OMISSION EXCEPTED. "FREIGHT COST MAY APPLY ON BUYIN LINES SPECIAL ORDER PRODUCTS, KINES, LARGE OVERSIZE TIENS & IN REGIONAL AREAS.
"**UNLESS STATED OTHERWISE, ALL TOB BRANDS PRODUCTS. EXCLUDING CONSUMABLES, COME WITH A 12 MONTH OMMERCIAL USE WARRANTY AGAINST MANUFACTURING DEFECTS. THE BONUS 12 MONTH WARRANTY OFFERED EXCLUSIVELY IN
THIS PROMOTIONAL PERIOD APPLIES ONLY TO THE HYDRAULIC RAM AND HYDRAULIC PUMP FOR "BONUS" MARKED PRODUCTS. THE ADDITIONAL 12 MONTHS DOES NOT INCLUDE INSTALLATION REMOVAL LABOUR OR FREIGHT FOR THE COMPONENT.