



TA TRADEQUIP

# VORKSHOP EQUIPMENT

VALID THROUGH TO MARCH 31 2026

For full product specifications go to www.tqbbrands.com.au



## **Portable Evaporative** Cooler 750W

1035T

240V/50Hz/750W 3 speed motor Max. air flow: 23,000 m3 per hour Effective cooling area: 150-200sqm Water usage:12-18 litres per hour Water tank capacity: 130 Litres 1730H x 1120W x 680Dmm

Weight: 63kg





**Synchronous** Swing **Function** 

Remote Control Timer Panel

#### **FEATURES & BENEFITS**

Moulded polyethylene housing will not crack and is rust & leak proof. Environmentally-friendly alternative to traditional reverse cycle A/C. Cools without chemicals or refrigerants. Long-term dependability. Near maintenance free operation.

Cools where traditional cooling methods are impractical or cost-prohibitive. Remote control speed adjustment. Direct drive. LCD 24 hour timer panel. Easy to read water level sight tube gauge.

Dual pour in refill water inlet and/or 3/4" hose fitting for automatic tap refill. Adjustable water flow & drain valve. Nylon castors for easy portability.



RANGE HERE

**Excludes GST** Inc. GST \$1813.90 \*Freight Rates May Apply



**Product Demonstration online** 

## **Portable Evaporative Cooler 750W**

1029T TRADEQUIP

MADE FOR THE 240V/50Hz/750W 3 speed motor Max. air flow: 23,000 m3 per hour Water consumption: 20-35 litres per hour Effective cooling area: 200-260sqm Cooling area: 200-260m2

Water tank capacity: 200 Litres 1800H x 1600W x 780Dmm

Weight: 128kg

#### **UPGRADED 5 BLADE DESIGN INCREASING** AIR VELOCITY



**Nylon Castors for** easy portability

#### TRADEQUIP EVAPORATIVE COOLERS FEATURES & BENEFITS

Timer Panel

Moulded polyethylene housing will not crack and is rust & leak proof. Environmentally-friendly alternative to traditional reverse cycle A/C. Cools without chemicals or refrigerants.

Long-term dependability. Near maintenance free operation.

Cools where traditional cooling methods are impractical or cost-prohibitive. Remote control speed adjustment. Direct drive. LCD 24 hour timer panel. Easy to read water level sight tube gauge. Dual pour in refill water inlet and/or 3/4" hose fitting for automatic tap refill.

Adjustable water flow & drain valve. Nylon castors for easy portability.



## **Portable Evaporative Cooler 550W**

Watts

MADE FOR THE

## 1027T TRADEQUIP

240V/50Hz/550W 3 speed motor Max. air flow: 18,000 m3 per hour Effective cooling area: 100-150sqm Water consumption: 12-18 litres per hour

Water tank capacity: 100 Litres 1510H x 1120W x 680Dmm

Weight: 58kg





Remote Control Timer Panel



Excludes GST Inc. GST \$1417.90



## **Cooler Cover**

1035T-CO TO TRADEQUIP

Water-resistant fabric Lightweight and breathable UV treated and Easy to use To protect 1027T, 1028T and 1035T TradeQuip Portable Evaporative Coolers when not in use.





## **Portable Evaporative Cooler 750W**

1035T TRADEQUIP

240V/50Hz/750W 3 speed motor Max. air flow: 23,000 m3 per hour Effective cooling area: 150-200sqm Water consumption: 12-18 litres per hour

Water tank capacity: 130 Litres 1730H x 1120W x 680Dmm Weight: 63kg

Synchronou



Remote Control







MADE FOR THE

\*Freight Rates May Apply

## **SPOT COOLING AIR CONDITIONERS**

## **Portable Industrial Spot Cooling** Air Conditioners TATRADEQUIP

Code	1031T	1032T	1033T
Power Unit	240V 50Hz	240V 50Hz	240V 50Hz
Rated Power	950W	2000W	3000W
Mains Plug	10 Amp	15 Amp	15 Amp
Cooling Capacity	2.7KW/9200Btu	4.5KW/15300Btu	6.5KW/22200Btu
Max. Air Flow	400m3 p/hr	800m3 p/hr	1200m3 p/hr
Noise Level	55dB(A)	60dB(A)	65dB(A)
Operating Temp.	18º - 45º C	18º - 45º C	18º - 45º C
Suction Pressure	2.5Mpa (Max.)	2.5Mpa (Max.)	2.5Mpa (Max.)
Discharge Pressure	4.5Mpa (Max.)	4.5Mpa (Max.)	4.5Mpa (Max.)
Dimensions	855Hx430Wx405D	1035Hx520Wx480D	1245Hx640Wx560D
Excl. GST	\$1399	\$2555	\$3999
Incl. GST	\$1538.90	\$2810.50	\$4398.90



## **TRADEQUIP INDUSTRIAL AIR CONDITIONERS FEATURES & BENEFITS** Compact yet powerful. Wide operating range of 18°- 45°C.

Single duct system for easy installation. Capillary tube construction for simplicity.

5 Litre self-contained condensation tank for easy removal and emptying.

Heavy duty compressor with automatic restart and short cycle protection.

Motors and compressors have overload protection.

Durable and long lasting steel construction.

Heavy duty locking castors and handles for easy manoeuvrability.

Easy to use plug in and place the hot air duct out of window/door or into false ceiling.

TradeQuip "Made for the Trade" Portable Air Conditioners offer a quick spot cooling solution with strong air flow and easy installation.





Industrial Pedestal Misting Fan 650mm

1182T TRADEQUIP

240V/50Hz/230W 3 speed motor 90° Oscillation

Water shortage protection. Drop the temperature: 2-8°C

Adjustable mist-Exit Vol: 0-16KG/Hr Effective spray distance: 8-10mtr

Suitable for cooling people, stockbreeding or greenhouse applications.







Great for workshops and factory floor areas Adjustable height to 1.8m and 3 speed operation.

Large water storage tank & integrated water

reservoir.

No mess drip water collector.

Heavy duty base for safety and stability. Low pressure water pump for reliability and

Automatic shut-off when water tank is empty.



**Industrial Wall Mounted** 

Fan 750mm 1026 TRADEQUIP

240V/50Hz/280W 3 speed motor 750mm cast alloy 3 blade fan 0° to 90° oscillating angle Air flow: Up to 300m3/min Noise level: 86dB(A)



Cast aluminium 3 spoke fan blade.

**FEATURES** 



Includes sturdy wall mount bracket

Chrome steel cade



**FEATURES** 

The enclosed direct drive motor is protected from dust and debris to provide ye reliable service.

The 3-speed switch gives you control over the airflow, and vertical tilt helps you control angle. Solid metal construction with durable

Industrial Pedestal Fan 750mm 1015 TRADEQUIP 240V/50Hz/280W 3 speed motor 750mm aluminium 3 blade fan Adjustable height: 1235-1760mm (Blade centre) 0° to 90° oscillating angle or fixed Air flow: Up to 300m3/min aluminium Chrome steel cage **FEATURES** Rugged and dependable Direct drive motor

requires less power and less maintenance compared to other motors.

Durable all-metal construction with black finish, chromium (finger safe) steel grille.

Aerodynamically balanced 3 spoke aluminum blades for maximum airflow and motor efficiency.

Adjustable tilt to direct air where you need it. Cast Iron heavy duty base for stability.

Metal oscillating gears.

Cast Iron heavy duty base for stability

Industrial Portable Floor Fan 450mm

1045 TATRADEQUIP 240V/50Hz/220W 3 speed motor

450mm steel 3 blade fan Adjustable flow angle Air flow: 142sqm per min Noise level: 69dB(A)



Chrome steel cage

Adjustable tilt and High air flow. Metal oscillating gears.
Heavy duty wall mounting bracket.

**Industrial Ventilation Fans** TRADEQUIP

Code	1025	1056	1141T
Fan Diameter	300mm	400mm	450mm
Voltage 240V 50Hz		240V 50Hz	240V 50Hz
Power	520W	1100W	1700W
Speed	2800rpm	2800rpm	2800rpm
Noise Level	92db2 (A)	92db2 (A)	92db2 (A)
Air Delivery	60m3per minute	96m3per minute	162m3per minute
Static Pressure	343Pa	700Pa	972Pa
Excl. GST	\$295	\$735	\$869
Incl. GST	\$324.50	\$808.50	\$955.90

#### **FEATURES**

These TradeQuip "Made for the Trade" Industrial Ventilator Fans air out rooms, circulate air or dry wet areas with a powerful air output of 60m³ per minute. Features include an ergonomic handle for effortless transport and an aluminium blade with steel housing construction for long lasting durable performance. Complete with 5 metre flexible ducting

**WARNING: NOT INTENDED FOR DUST EXTRACTION** 



# PRODUCT SUPPORT

Go to our TQB Brands Website for extensive product support & regular information updates.

For a comprehensive guide to your TQB Brands product Maintenance, Setup and Demonstration



to TQB Brands Youtube Channel



Air/Hydraulic Bottle Jack Bleeding Video

12K views • 1 year ago



Hydraulic Bottle Jack Bleeding Video

17K views • 1 year ago



TradeQuip Diesel/Kerosene Workshop Heaters

5K views • 3 years ago



TradeQuip 2020 Evaporative Cooler Range

2.7K views • 1 year ago

## TROUBLESHOOTING DOCUMENTS



PORTA POWERS & PANEL REPAIR (1)

TRANSMISSION JACKS (17)

PRES

TROLLEYS & CREEPERS (O)

PRESSES & PIPE BENDERS (17)

WHEEL & SUSPENSION TOOLS (O)

STANDS, RAMPS & DOLLIES (1)

Scan code to go to TQB Brands Troubleshooting Documents

TOP TIPS

Product information

Scan code to go to our Top Tips guides and learn how to extend the life of your TQB Brands equipment

Visit our webpage www.tqbbrands.com.au for instructional & pre-start videos.





## **SCISSOR LIFTERS**



## Scissor Lift Workshop Trolley 450KG

6003T TRADEQUIP Safe working capacity: 450kg

Working height: 280-875mm Table size: 500 x 810mm Wheel Diameter: 125mm

Hands free foot-operated hydraulic pedal. Quick release hand lever. Heavy duty oil-resistant nonslip mat. Powder coated all steel construction

Perfect for moving heavy parts to vehicles.



Inc. GST \$1021.90

MADE FOR THE

FOLDABLE HANDLE



MADE FOR THE TRADE

#### **FEATURES**

Hands free foot-operated pedal. Quick release hand lever for easy, controlled release Heavy duty oil-resistant nonslip mat. Powder coated all steel construction Perfect for moving parts to vehicles.



MADE FOR THE

RADE

## Scissor Lift Workshop Trolley 500KG

6007T TRADEQUIP

Safe working capacity: 500kg Working height: 440-1575mm Table size: 1010L x 520Wmm Wheel diameter: 150mm Dimensions: 1130L x 520W x 1260Hmm

MADE FOR THE

#### FEATURES

Double Scissor High Lift Foot-operated hydraulic pedal keeps vour hands free. Quick release hand lever for easy, controlled hydraulic release. 2 locking heavy duty swivel castors.
All steel construction. Powder coated for extra protection. Perfect for moving heavy parts to

and from the vehicle.

CAPACITY 500KG

## Scissor Lift Workshop Trolley 300KG

6008T TRADEQUIP

Safe working capacity: 300kg Working height: 350mm-1285mm Table size: 820L x 520Wmm

GST \$1153.90

DOUBLE SCISSOR HIGH

CAPACITY 300KG



Perfect for moving parts to vehicles.



## **AUXILIARY SUPPORT/LIFTING**

#### Transmission Saddle Upgrade **PROTSUNI**

Fits following TQB Brands models: PROTL1000: PROTL500: 2063T: 2022T Transmission Lifter Shown in images sold separately Rated maximum capacity: 1,000kg (See your transmission lifter's capacity) Lifting platform size: 160x145mm (475x465mm Max.)

Forward tilt: 11° Rearward tilt: 11° Left tilt: 9° Right tilt: 11 Weight: 19kg



#### **FEATURES**

The saddle frame is constructed of superior grade steel and built to premium standards for professional quality and durability The enlarged threaded rods paired with cantilevered handles allow for faster adjustments over standard saddle design resulting in higher efficiencies.

The four ratcheting securing pins are easily Ine four ratcheting securing pins are easily and quickly adjustable making transmission lifting safer & more secure.

Two tie-down straps included to safely secure the transmission to the saddle.

Four rounded tie-down points and holes in securing pins allow for added level of customisation to secure the load. One removable saddle pin allows for accommodation of longer gearboxes Compatible with and for use on selected TQB Brands Transmission Lifters Only





# Auxiliary Lifter 500KG 2058T Tradequip the Country of the Country Rated capacity: 500kg

Working height: 1175-1985 mm Lifting platform size: A: 362 x 362mm B: Φ 107.5mm

#### **FEATURES**

perfect underhoist aid during removal and installation of small components. It features a mounting cradle and lift pad and a manually operated hydraulic system with smooth hydraulic lift and descent. The hydraulic system also includes

a bypass system to prevent over extension and accidental overloading.



MADE FOR THE

height 2045mm

NOT INTENDED FOR SUPPORTING LOADS
AND NOT INTENDED
AS STAND ALONE
TRANSMISSION LIFTER



**Underhoist Auxiliary** 

Stand 680KG 1198T TRADEQUIP

Safe working capacity: 680kg Height: 1370-2045mm Base diameter: 300mm Weight: 16.5kg





#### **FEATURES**

foot pedal operation

Fast and safe technology for professional mechanics.

Heavy gauge steel frame prevents distortion or twisting. Provides partial support for components -

NOT designed to support the vehicle.
Foot pedal allows easy load movement

and hand free operation.

Quick action adjustable height mechanism. Sold individually recommended only to be used individually.





**Auxiliary Lifter** Kit 500KG

Includes

Cradle,

Lift Pad &

Fuel Tank Adaptor

A

2068T TRADEQUIP

Rated capacity: 500kg Working height: 1175-1985 mm Lifting platform size: A: 362 x 362mm В: Ф 107.5mm

C: 812 X 352mm

Inc. GST \$746.90

NOT INTENDED FOR SUPPORTING LOADS AND NOT INTENDED AS STAND ALONE

## **TRANSMISSION LIFTERS**



## **TRANSMISSION LIFTERS**



## **BOTTLE JACKS**



## Air/Hydraulic Bottle Jack 20,000KG



## Air/Hydraulic Bottle Jack 20,000KG



#### Air/Hydraulic Bottle Jack 30,000KG BWBBJ30T /= BORUM

Safe working capacity: 30,000kg Working height: 275 - 532mm Hydraulic lift: 162mm Adjustable height: 95mm Base area: 229x180mm Op. air pressure: 90-120psi



WELDED BASE





## Air/Hydraulic Bottle Jack 35,000KG



FEATURES OF TQ Pro BOTTLE JACKS
Using CNC technology, TQ Pro products
are constructed using superior-grade steel
and built to premium TQ Pro standards
for professional useful. for professional quality and durability.

Trusted by serious prof
Premium quality large diameter hydraulic steel cylinders are machi
then treated and polished to minimise wear and extend service life.

Excludes GST

Incorporating the latest technology in aggressive wiper seals and OD exclusion, the high capability premium quality seal systems efficiently protect internal hydraulics keeping it free from dirt, mud,

water, and other contaminants.

A lead-free paint finish is applied after a thorough chemical wash to ensure a long-lasting premium finish with a final coat that is oil, grease and dirt-resistant for easy cleanup.

## Air/Hydraulic Bottle Jack 20,000KG

PROBJ20TA Safe working capacity: 20,000kg Working height: 261.5-525mm Hydraulic lift: 156mm Adjustable lift: 95mm Operating air pressure: 110-125psi Air inlet fitting: 1/4" Base: 230 x 150 x 30mm Weight: 19kg



**Professional** Reputable Outstanding

Excludes GST Inc. GST \$493.90



Air Actuated Bottle Jack Squat 20,000KG

PROBJ20TAS

Safe working capacity: 20,000kg Working height: 185-330mm Hydraulic lift: 80mm Operating air pressure: 110-125psi

Adjustable height: 61mm Air inlet fitting: 1/4" Base: 230 x 150 x 30mm Weight: 16kg



Reputable Outstanding



## Air/Hydraulic Bottle Jack 30,000KG

PROBJ30TA Safe working capacity: 30,000kg Working height: 279.5-533mm Hydraulic lift: 155mm Op. air pressure: 110-125psi Air inlet fitting: 1/4" Base: 250 x 180 x 40mm Weight: 29kg LATEST APPLIED TECHNOLOGIES

**Professional** Reputable Outstanding

Excludes GST **GST \$647.90** 



## **BOTTLE JACKS**





Machined and polished cylinders with die-cut threads provide non-abrasive leak-free, durable performance. Fabricated from hard-cast steel with heat-treated critical

Unique cross-type forged release valve ensures positive load control.

Overload protection Hydraulic system is protected from internal damage by a by-pass mechanism. High quality glide-action pressure pump. Supplied with 500mm pump handle

Code	2012	2013	2014	2015	2016
Capacity	10,000kg	15,000kg	20,000kg	12,000kg	20,000kg
Hydraulic Lift	125mm	125mm	145mm	85mm	115mm
Adjustable Height	70mm	70mm	60mm	50mm	75mm
Min. Height	205mm	227mm	245mm	180mm	200mm
Max. Height	400mm	447mm	450mm	315mm	390mm
Base Area	124x124mm	148x136mm	167x156mm	157x134mm	167x156mm
Excl. GST	\$109	\$132	\$169	\$129	\$169
Incl. GST	\$119.90	\$145.20	\$185.90	\$141.90	\$185.90

## Air/Hydraulic Bottle Jack 12,000KG

Safe working capacity: 12,000kg Working height: 260-510mm Adjustable screw: 80mm Work pressure: 110-125psi Hydraulic stroke: 170mm Air inlet fitting: 1/4"

#### **FEATURES**

Compact powerful Air Turbo motor.
Versatile "quick connector provides 'quick & easy air connection. Two piece pump handle. Convenient welded carry handle.

Excludes GST Inc. GST \$240.90



Air/Hydraulic Squat Jack 20,000KG TQBJ20TAS TRADEQUIP

Safe working capacity: 20,000kg Working height: 178-328mm Adjustable screw: 63mm Work pressure: 110-125psi Hydraulic stroke: 87mm

> Excludes GST Inc. GST \$339.90

Air inlet fitting: 1/4"



000kg apacity

## Air/Hydraulic Bottle Jack 20,000KG

2026T TRADEQUIP Safe working capacity: 20,000kg Working height: 265-510mm Hvdraulic lift: 170mm (265mm to 435mm) Adjustable height: 75mm (max. height 510mm) Base area: 224x134mm Work pressure: 90-120psi

Weight: 16kg

#### **FEATURES**

Compact powerful Air Turbo motor. Versatile "quick connector provides quick & easy air connection. Two piece pump handle. Convenient welded carry handle

Inc. GST \$317.90



Air Actuated Super Low Profile Jack 20,000KG

2051T TRADEQUIP

Safe working capacity: 20,000kg Working height: 148-259mm Screw extension height: 45mm Operating air pressure: 100-145psi Hydraulic stroke: 66mm Air inlet fitting: 1/4"

DEQUIP

#### **FEATURES**

Compact powerful Air Turbo motor. Versatile "quick connector provides 'quick & easy air connection. Chrome plated

rams. Convenient welded carry handle



Inc. GST \$416.90

## **TYRE LIFTER/DOLLY**



Wheel Dolly Single 250KG

B250WH F= B O R U M

Safe working capacity: 250kg Maximum depth: 305mm Overall height: 1000mm Weight: 14kg



# **Capacit**

#### FFATURES

Adjustable arms

Adjustable arms.
Equipped with rollers for easy positioning.
Stop rollers on the rear side.
Ergonomic handle with rounded & soft safety grip.

This BORUM WHEEL DOLLY is a sturdy & handy transport aid for various types of wheels (trucks, vans, utes and cars). This versatile and easy to operate piece of equipment features adjustable arms. Equipped with two wheels and an ergonomic handle, the units manoeuvrability is not hampered by the size of the wheel.







**Capacit** 





For the lifting, lowering, supporting & transporting of tyre & rim assemblies up to 50kgs & 300mm wide.



castors

Safe working capacity: 130kg Height: Min. 288mm, Max. 980mm Chassis: 1041 x 609mm 1 x 2" Alignment Spline Included (10 Tooth)
1 x 1-3/4" Alignment Spline





#### **FEATURES**

Designed for lifting, lowering & installing/removing heavy vehicle clutch/flywheel assemblies. Industrial-grade steel frame. High quality hydraulic steel cylinder. Industrial hydraulic system. Rugged heavy industrial wheels and full swivel ball castors. User-friendly rotating handle. Paint is oil, grease and dirtresistant for easy cleanup. Two 10-tooth alignment splines included store on chassis.



Truck Wheel Lifter BTWD750 F= B O R U M Safe working capacity: 750kg Lift arm spread: 533-635mm Lifting range: 60-275mm Tilt range: -2.5 to 10 degrees 787L x 1092W x 895H mm INDUSTRIAL

Inc. GST \$1098.90





## **JACKS & STANDS**

#### Car and 4WD Jack Stands

#### TRADEQUIP the trusted brand in equipment

#### **FEATURES**

Constructed of high-grade steel & built to exacting standards for quality & durability. Lead-free paint finish is oil, grease and dirtresistant for easy cleanup.

Quick action adjustable height mechanism.

Quick action adjustable height mechanism Double-lock safety pin design for extra safety and security. (1128T & 1148T). Welded steel frame & cast iron support. Adjustable height.

Adjustable height. Reinforced shaft for added strength stability. Sold in pairs and only recommended to be used in pairs.



Code	1128T	1148T	1162T
Load limit	2,000kg	4,000kg	8,000kg
Min. Height	285-428mm	395-605mm	468-715mm
Base Area	206x186mm	287x252mm	324x294mm
Excl. GST	\$105	\$181	\$309
Incl. GST	\$115.50	\$199.10	\$339.90



Garage Jack 3,000KG Low Profile

## 2906T TRADEQUIP

Working load limit: 3,000kg Height: 118 - 488mm Handle length: 1400mm

Front wheels: 90mm dia 40mm width Rear castors: 60mm dia 25mm width

Saddle diameter: 115mm Dimensions: 670L x 380W x170Hmm Weight: 43kg

#### FEATURES

Low profile and deep reach.
Heavy gauge steel construction.
1400mm long handle for deeper reach.
Quick Lift Dual Pump technology .
Internal bypass valve overload protection.
Lead-free paint finish to ensure a longlasting finish and prevent rust.
Paint is oil, grease and dirt-resistant.
Protective foam handle cover prevents

Protective foam handle cover preve vehicle damage.



**\$519** 

488mm

max. lift

height

HEAVY GAUGE

Inc. GST \$570.90





## **Mechanics Creeper 130KG**

1023T TRADEQUIP

Safe working capacity: 130kg 1010L x 475W x 115Hmm





Inc. GST \$101.20

#### FEATURES

The creeper body is manufactured to "Made for the Trade" quality using a high-impact polymer material that resists impacts, won'r rust and is easy to clean. Comfortable padded headrest this low-profile creeper is one of the lightest and most durable available.



## Ratcheting Positioning Jacks

1054T TRADEQUIP

Safe working capacity: 680kg each Max. distance between rollers: 710mm Min. distance between rollers: 340mm Suits tyres up to: 280mm (W)

Swivel castors: 100mm

MADE FOR THE

#### FEATURES

Steel construction with metal rollers. Heavy duty nylon swivel castors. Easy foot-pedal lifting design. 2 jacks permit full 180° vehicle pivot. 4 jacks place vehicle on a 360° rolling platform. Lead-free paint finish helps prevent rust and is oil, grease and dirt-resistant for easy cleanup. Quick action adjustable height mechanism. Sold &recommended only to be used in pairs.

Easy foot pedal lift

Heavy duty nylon swivel castors



Excludes GST **\$4.69**Inc. GST \$515.90
pair

# Vehicle Positioning Rack

1054T-R TRADEQUIP 1054T Storage capacity: 1 on ground,

up to 3 vertically Distance between spigots: 170mm Overall footprint: 605 x 130 x 145mm

Weight: 2.4kg

MADE FOR THE

#### **FEATURES**

Steel Construction with metal chocks to lock rollers into place.
Rack is designed to connect to 1 x 1054T &

can have up to 3 x 1054T stored vertically. Heavy duty locking pin secures rack to 1054T Vehicle Positioning Jack. Lead-free paint prevents rust & is oil, grease and dirt-resistant for easy cleanup. Sold separately and only to be used on TradeQuip 1054T Vehicle Positioning Jacks.





## **TRUCK JACKS**

## Air Actuated Truck Jack 35,000KG

BTJ35TA /= BORUM

Safe working capacity: 35,000kg Lift range: 255-633mm

Hydraulic lift: 155mm Adjustable height: 123mm Adaptors: 21, 61, 100mm Handle length: 1110mm

Operating air pressure: 110-125psi Chassis: 555L x 255H x 295Wmm

#### FEATURES

Pro quality rugged steel construction. Wear-resistant quality sealing O-rings. Strong hydraulic pump & 3-position

Temperature-resistant hydraulic oil.
Treated and polished piston and ram. Built-in bypass hydraulic safety

Overload.
Compact design and Quick Lift ram.
Convenient & efficient height adaptors.
High quality lead-free paint.



Inc. GST \$1846.90

50.000KG

**Excludes GST** 

35.000KG

**Includes** 

Height

Adaptors

Air Actuated Jack 2 Stage 15,000/30,000KG

BTJ1530TA /= BORUM

1st stage: 30,000kg safe working capacity 2nd stage: 15,000kg safe working capacity First stage hydraulic lift: 73mm Second stage hydraulic lift: 66mm Operating air pressure: 145-175psi Height: 150-409mm Adaptors: 45 and 75mm

Handle length: 1300mm Chassis: 480 x 290 x 150mm

#### **FFATURES**

Double sealing function using XTP industry sealing.
Telescopic air actuation lift (air-

hydraulic pump).
Long T-handle lets you easily position your jack under vehicle.
Self-returning lower & lift switch .
Internal and external cylinders hard

chromed. High manoeuvrability & deep reach

under vehicles. 2 extension adaptors/saddle plates Large rubber wheels.



Air Actuated Truck Jack 50,000KG

BTJ50TA PAR D R U M

Safe working capacity: 50,000kg Lift range: 287-650mm Hydraulic lift: 153mm Adjustable screw: 110mm Adaptors: 20, 60, 100mm Handle length: 1230mm Operating air pressure: 110-125psi Chassis: 525L x 288H x 325Wmm

INDUSTRIAL

#### **FEATURES**

Pro quality rugged steel construction. Wear-resistant quality sealing O-rings. Strong hydraulic pump & 3-position handle. Temperature-resistant hydraulic oil. Treated and polished piston and ram.
Built-in bypass hydraulic safety overload.
Compact design and Quick Lift ram. Convenient & efficient height adaptors High quality lead-free paint.

Air Actuated Jack 2 Stage *20,000/40,000KG* 

BTJL2040TA Z BORUM

1st stage: 40,000kg safe working capacity 2nd stage: 20,000kg safe working capacity Lift range: 150-295mm (no adaptors) 1st stage hydraulic lift: 77mm 2nd stage hydraulic lift: 68mm Adaptors: 10, 35, 65mm

Operating air pressure: 100-145psi Handle length: 1290mm Chassis: 543L x 291Wmm



**FEATURES** 

Wear-resistant quality sealing O-rings Strong hydraulic pump.
Temperature-resistant hydraulic oil. Treated and polished piston and ram. Built-in bypass hydraulic safety overload system. Quick Lift lifting ram comes in contact with the load faster.

Convenient & efficient height

3-position pumping handle. High quality lead-free paint

Air Actuated Truck

BTJ60TA /= BORUM

Jack 60,000KG

Safe working capacity: 60,000kg

Lift range: 420-1031mm

Adaptors: 100 & 200mm

Handle length: 1290mm

Hydraulic lift: 311mm

INDUSTRIAL QUALITY

Includes Height Adaptors

LIFTS 40.000KG

## Air Actuated Truck Jack 30,000KG

BTJ30TA /= BORUM

Safe working capacity: 30,000kg Lift range: 360-772mm Hydraulic lift: 267mm Adaptors: 45 & 100mm Handle length: 1370mm Operating air pressure: 145-175psi Chassis: 840L x 360H x 282Wmm



Inc. GST \$4761.90

30,000KG

**DUSTRIAL** 

Includes Height Adaptors



#### **FEATURES** Double sealing function using XTP industry

sealing. Telescopic air actuation lift. Self-returning lowering and lifting switch.
Internal & external cylinders hard chromed

Long T-handle for high manoeuvrability & deep reach under vehicles.

Designed for extremely high axles

# Height Adaptors

Includes

Inc. GST \$5498.90

60.000KG

#### **FEATURES**

XTP industry double sealing function using Telescopic air actuation lift.
Self-returning lowering and lifting switch. Internal & external cylinders hard chromed Long T-handle for high manoeuvrability & deep reach under vehicles.

Designed for extremely high axles



## **TRUCK JACKS**

#### Air Actuated 2 Stage Truck Jack 10,000/25,000KG

BTJ1025TA = BORUM

Stage 1: 25,000kg safe working capacity Stage 2: 10,000kg safe working capacity Lift range: 185-497mm

Hydraulic lift: Stage1: 97mm, Stage2: 95mm

Adaptors: 45, 75mm

Handle length: 1380mm

Operating air pressure: 145-175psi Chassis: 770L x 282H x 185Wmm



Includes Height Adaptors

#### **FEATURES**

Double sealing function - XTP industry sealing Telescopic air actuation lift. Self-returning lowering and lifting switch.
Internal & external cylinders hard chromed



BTJ2550TA /= B O R U M

Stage 1: 50,000kg safe working capacity Stage 2: 25,000kg safe working capacity Lift range: 215-564mm

Hydraulic lift: Stage1: 115mm, Stage2: 114mm

Adaptors: 45, 75mm Handle length: 1380mm

Operating air pressure: 145-175psi Chassis: 805L x 282H x 215Wmm



Double sealing function - XTP industry sealing. Telescopic air actuation lift. Self-returning lowering and lifting switch.
Internal & external cylinders hard chromed Long T-handle for high manoeuvrability & deep

LIFTS

25.000KG

Includes Height Adaptors



### Air Actuated 3 Stage Truck Jack 10,000/25,000/50,000KG

BTJ102550TA = BORUM

Safe working capacity: Stage 1: 50,000kg Stage2: 25,000kg, Stage3: 10,000kg Lift range: 160-472mm Hydraulic lift: Stage1: 62mm Stage2: 61mm, Stage3: 69mm Adaptors: 45, 75mm Handle length: 1380mm

Includes

Height

Adaptors

Operating air pressure: 145-175psi Chassis: 825L x 282H x 160Wmm



50.000KG

#### FEATURES

Double sealing function using XTF industry sealing.
Telescopic air actuation lift

Self-returning lowering and lifting switch.
Internal & external cylinders hard chromed
Long T-handle for high manoeuvrability & deep reach under vehicles





## Air Actuated 3 Stage Truck Jack 20,000/40,000/60,000KG

BTJ204060TA = BORUM



First stage: 60,000kg safe working capacity Second stage: 40,000kg safe working capacity Third stage: 20,000kg safe working capacity First stage hydraulic lift: 57mm

Second stage hydraulic lift: 59mm Third stage hydraulic lift: 61mm Height: 150-447mm

Adaptors: 45 and 75mm

Operating air pressure: 145-175psi

Handle length: 1380mm Chassis: 875 x 295 x 150mm



Includes Height Adaptors



80,000KG



Double sealing function using XTP industry sealing Telescopic air actuation lift (air-hydraulic pump). Long T-handle lets you easily position your jack

Self-returning lowering and lifting switch Internal and external cylinders hard chromed .
High manoeuvrability & deep reach under vehicles 2 extension adaptors / saddle plates.
Large rubber wheels.



## Air Actuated 2 Stage Truck Jack 50,000/80,000KG

BTJ5080TA /= BORUM

First stage: 80,000kg safe working capacity Second stage: 50,000kg safe working capacity

First stage hydraulic lift: 111mm Second stage hydraulic lift: 102mm Height: 230-563mm

Adaptors: 45 and 75mm Operating air pressure: 145-175psi Handle length: 1300mm Chassis: 930 x 340 x 230mm



Inc. GST \$5058.90



Includes Height Adaptors

#### FEATURES

Double sealing function using XTP industry sealing. Telescopic air actuation lift (air-hydraulic pump). Long T-handle lets you easily position your jack under vehicle. Self-returning lowering and lifting switch.

Internal and external cylinders hard chromed .
High manoeuvrability & deep reach under vehicles. 2 extension adaptors / saddle plates Large rubber wheels.

## **RAMS & JACKS**

## Air Actuated Truck Jack 22,000KG

B2003T Z= BORUM

Safe working capacity: 22,000kg Lift range: 210-525mm Hydraulic lift: 120mm Adjustable height: 105mm Handle length: 1075mm Air supply: 100-120psi Wheel diameter: 175mm Adaptors: 20, 50, 100mm Chassis: 500L x 215H x 320Wmm











Air Jack Support Stand 10,000KG

**FEATURES** 

BSJ10T F BORUM

Safe working capacity: 10,000kg Height: Min. 536mm - Max. 1298mm Hydraulic lift: 292mm

Rated air pressure capacity: 200psi Weight: 91kg

Base diameter: 339mm

#### FFATURES

Solid heavy duty construction.
Advanced technology sealing rings.
Fast motion super duty air pump.
Temperature-resistant hydraulic oil. Treated and polished piston and ram. Built-in bypass hydraulic safety overload system. Compact design easily fits dual tandem

axles.
Convenient & efficient height adaptors

3-position pumping handle. High quality lead-free paint is oil, grease and dirt-resistant finish for easy cleanup.

## Air Actuated Truck Jack 22,000KG

2004T TRADEQUIP

Safe working capacity: 22,000kg Lift range: 225-552mm Hydraulic lift: 124mm Adjustable height: 103mm Chassis: 560L x 230H x 320Wmm Adaptors: 21, 60, 100mm Handle length: 1160mm Wheel diameter: 200mm



**Excludes GST** Inc. GST \$801.90

#### **FEATURES**

Trade quality rugged steel construction. Wear-resistant quality sealing O-rings. Strong hydraulic pump. Temperature-resistant hydraulic oil Treated and polished piston and Quick lift ram.

Built-in bypass hydraulic safety overload system. Compact design easily fits dual tandem axles. Convenient & efficient height adaptors.
3-position pumping handle.
High quality lead-free paint is oil, grease and dirtresistant finish for easy cleanup

#### Air Actuated Truck Jack 20,000KG PROTRJA20T

Safe working capacity: 20,000kg Working height: 215-541mm Hydraulic Lift: 141mm Adjustable screw: 85mm Adaptors: 20, 50, 100mm Handle length: 1335mm Operating air pressure: 145-175psi Chassis: 520L x 215H x 258Wmm







**Professional** 

Reputable

**Outstanding** 

#### FEATURES

Double sealing using XTP industry sealing Telescopic air actuation lift (air-hydraulic pump). Long T-handle lets you easily position your jack under vehicle

Self-returning lowering and lifting switch.
Internal and external cylinders hard chromed.
High manoeuvrability & deep reach. nsion adaptors/saddle plates



Includes Height Adaptors

10.000KG

The BORUM Industrial AIR JACK/SUPPORT STAND 10,000KG is a reinforced pin style jack and stand with industrial quality design and support bracing system to sustain heavy loads up

Inc. GST \$1483.90

to 10,000kg. Adjusts to match the job with a 536mm minimum height, 292mm of hydraulic lift and up to 1298mm maximum height using the extension tube!! Featuring Heavy-Duty Industrial design, this tough air jack/support

stand is ideal for truck, bus, farm, earthmoving equipment and fleet vehicle maintenance workshop use.





#### **FEATURES** Long retractable T-handle for easy positioning.

"NON-SKID BASE" - 4 ply pads of rubber grips are bolted and glued to the 6mm steel floor plates and they will not skid ahead of

Replaces need for a pit or hoist, and at a fraction of the cost and floor space



SELF.

## Truck Jack Stands /= BORUM

#### **SOLD INDIVIDUALLY**

Code	15TJSSHORT	15TJS
Load limit	15,000kg	15,000kg
Height	446 - 631mm	645-1077mm
Base Area	300x300mm	460x460mm
Excl. GST	\$439	\$529
Incl. GST	\$482.90	\$581.90
Code	25TJSSHORT	25TJS
Load limit	25,000kg	25,000kg
		25,000kg
Height	415 - 539mm	680-968mm
	, ,	, ,
Height	415 - 539mm	680-968mm



#### **FEATURES**

Manufactured from high-grade steel and built to exacting standards for quality and durability. Lead-free paint finish is oil, grease and dirt-resistant for easy cleanup. High strength locking pin. Controlled pin holes for easy height adjustments. Turned post slide for easy quick adjustments.

adjustments.

Heavy-gauge steel gusseted uprights prevent distortion or twisting.

Rugged base provides plenty of stability.

Conveniently located carry handle. Sold individually. (not in pairs)



from

#### **Auxiliary Stand 7,000KG**

Safe working capacity: 7,000kg
Working height: 1295-1905mm
Adjustable pin heights:
8 (75mm increments)
Base: 300x300x300mm
Weight: 65kg

#### FEATURES

Heavy duty design and support bracing system to sustain heavy vehicle loads.

wehicle loads.

Manufactured from high-grade steel and built to exacting standards for quality and durability.

durability.
Fitted with spring loaded castor wheels to ensure easy movement around the workshop.
Fitted with spring loaded support

beam. Lead-free paint finish is applied after a thorough chemical wash to ensure a long-lasting finish and to help prevent rust. Paint is oil, grease and dirtresistant for easy cleanup. High strength locking pin.

Controlled pin holes for easy height adjustments.

Turned post slide for easy quick adjustments.



Spring loaded castor wheels



## Support Stand 10,000KG

Safe working capacity: 10,000kg Working height: 720-1190mm Adjustable pin heights: 10 Saddle dimensions: 150x80mm Base: 406 x 556mm Weight: 23.5kg

#### **FEATURES**

Stable 4 legged stability. Lead-free paint is oil, grease and dirtresistant for easy cleanup. High strength locking pin & controlled pin holes for easy height adjustments. Turned post slide for easy adjustment.

\*10TSS/10TSSHORT SOLD INDIVIDUALLY

Support Stand SHORT 10,000KG /= B D R U M

#### 10TSSHORT

Safe working capacity: 10,000kg Working height: 480-780mm Adjustable pin heights: 6 Saddle dimensions: 150x80mm Base: 310 x 310mm Weight: 18kg Excludes GST **\$369** Inc. GST \$405.90

10 Metric Sizes:

Weight: 14kg

Inc. GST \$456.50

INDUSTRIAL

QUALITY

0000

<u>Capacity</u>

#### Jumbo Spanner Set 10 Piece Imperial

#### B10PJSI - BORUM

10 Imperial Sizes: 1 5/16", 1 3/8", 1 7/16", 1 1/2", 1 5/8", 1 11/16", 1 3/4", 1 13/16", 1 7/8" 2" Wallet rolled out: 830 x 690 x 30mm Wallet rolled up: 150 x 690 x 130mm Weight: 14kg

\$259 Inc. GST \$284.90



# Excludes GST **\$259** Inc. GST \$284,90





**Jumbo Spanner Set** 

B10PJSM = BORUM

34mm, 36mm, 38mm, 41mm, 42mm, 44mm, 45mm, 46mm, 48mm & 50mm Wallet rolled out: 830 x 690 x 30mm

Wallet rolled up: 150 x 690 x 130mm

10 Piece Metric



Code	7000T	7001T	7002T	7003T	7004T	7005T
Vice type	Fixed	Fixed	Fixed	Swivel	Swivel	Swivel
Jaw Width	125mm	150mm	200mm	125mm	150mm	200mm
Jaw Opening	130mm	150mm	170mm	140mm	170mm	220mm
Throat Depth	69mm	76mm	88mm	76mm	86mm	110mm
Anvil Size	85x90mm	100x105mm	105x105mm	106x106mm	127x127mm	147x147mm
Excl. GST	\$149	\$199	\$269	\$218	\$319	\$439
Incl. GST	\$163.90	\$218.90	\$295.90	\$239.80	\$350.90	\$482.90





#### **Bench Offset Vice 150MM** 7007T TRADEQUIP

Jaw width: 150mm Jaw opening: 140mm Throat depth: 103mm

Weight: 21kg





#### **Commercial Bench Vice** Swivel with Anvil 150MM

BRV150 /= BORUM



## **Commercial Bench Vice** Swivel with Anvil 200MM

Swivel

Base

BRV200 /= BORUM



INDUSTRIAL QUALITY

Reinforced

mounting

lugs

## **DRILL PRESSES**

#### **ALL BORUM DRILL PRESSES FEATURE**

Flexible worklight. Engineering style work table. Oversize micro-switch activated safety guard.

Low-noise belt drive with cast iron balanced pulleys.

Safety ON-OFF switch fitted with a dust cover and positive action push buttons plus a large (Red) self locking "Emergency Stop" hinge cover. Precision spindle bearing for long life & high accuracy

Table control via hand crank and gear rack with high load capacity. Long quill stroke, easy to adjust depth stop at the capstan handle.

Thick-walled, precision-ground column for extra rigidity. Powerful long-life commercial drive motor provides high reliability.

Ground set-up areas on table and base plate.

Solid rotating work table with diagonal clamping slots.

# The same reliable 'Heavy Duty Industrial Quality Drill Presses'

since we started manufacturing them in 1984... but with the benefit of some 21st Century features

#### 3/4HP Pedestal Drill **Press 16 Speed**

CH16NFT /= BORUM

Motor: 240Volt 3/4HP Number of speeds: 16 Spindle taper: MT2

Spindle speeds: 162-3000rpm Max. drilling capacity: 16mm Max. spindle stroke: 78mm

Max. distance spindle to table: 7810mm Max. distance spindle to base: 1219mm

Chuck: 16mm Swing: 535

Size of table: 473x410mm Diameter of column: 73mm Size of base: 450x265mm Overall height: 1588mm



INDUSTRIAL











## 1HP Pedestal Drill **Press 16 Speed**

CH18FT /= BORUM

Motor: 240Volt 1HP Number of speeds: 16 Spindle taper: MT2

Spindle speeds: 200-3160rpm Max. drilling capacity: 20mm Max. spindle stroke: 82mm

Max. distance spindle to table: 775mm Max. distance spindle to base: 1270mm

Chuck: 16mm Swing: 430mm

Table diameter: 350mm Diameter of column: 80mm Size of base: 460x270mm

Overall height: 1625mm









## **2HP Pedestal Drill** Press 12 Speed

CH30T /= BORUM

Motor: 240Volt 2HP Number of speeds: 12 Spindle taper: MT4

Spindle speeds: 210-2160rpm Max. drilling capacity: 32mm Max. spindle stroke: 122mm

Max. distance spindle to table: 720mm Max. distance spindle to base: 1230mm

Chuck: 16mm Swing: 535

Size of table: 473x410mm Diameter of column: 92mm Size of base: 572x495mm Overall height: 1780mm





Scan code to go to our Top Tips guides and learn how to extend the life of your TQB Brands equipment

Visit our webpage www.tqbbrands.com.au for instructional & pre-start videos.



# MORE THAN JUST A PRESS!

## **Workshop Mate Workstation featuring a** 30,000KG Shop Press & Spring Compressor

MADE FOR THE



Safe working capacity: 30,000kg Working range: 224mm-819mm Piston ram stroke main ram:

140mm (Standard load cap fitted)

Bed height settings: 85mm increments-8 settings

Bed width: 466mm Bed gap: 200mm

Spring compressor: Piston ram stroke: 295mm

Operating air pressure: 90-125psi

Overall dimensions: 1820H x 1170W x 820Dmm

Weight: 400kg



#### **FEATURES**

AIR/HYDRAULIC OPERATED 30.000KG PRESS SPRING COMPRESSOR. FILTER CRUSHING ACCESSORY DOZENS OF UNIQUE TOOLING OPTIONS ON-BOARD TOOLING STORAGE STAND WINCH OPERATION TO LOWER AND RAISE BENCH

#### **BENEFITS**

Press almost any bearing or bush with PRECISION and ACCURACY in minutes, saving valuable workshop time.

Smooth AIR/HYDRAULIC foot pedal operation for handsfree accuracy & control.

Hands free Spring Compression.

Even the most difficult pressing tasks become SAFE & EASY.

Complete with COMPREHENSIVE HIGH QUALITY Interlocking Tool, Die and Spacer Kit to ensure SAFE WORK PRACTICES.

Complete on machine storage - minimises time spent searching for the required tools & spacers for each job!

Tasks like SUSPENSION BUSHES once seen as too hard become a breeze.

A comprehensive variety of spring adaptors, suitable to almost any type or model of spring SAFE & EASY to compress in minutes.

Decrease labour time & increase productivity and efficiencies.

#### INCREASE WORKPLACE SAFETY.

Undertake jobs that are currently too difficult.

## **Workshop Mate 18 Piece Sleeve Kit**

18 Piece Sleeve Set includes: 28x20x80mm; 33x25x80mm; 38x30x80mm; 43x35x80mm; 48x40x80mm; 53x45x80mm; 58x50x80mm; 63x55x80mm; 68x60x80mm; 73x65x80mm: 78x70x80mm; 83x75x80mm; 88x80x80mm; 93x85x80mm; 98x90x80mm; 103x95x80mm; 108x100x80mm; 1 13x105x80mm

18 sleeves constructed from heat-treated forged carbon steel. Sturdy metal carry case.

Designed and engineered to work as an added accessory to all current Workshop Mate Workstations.

WSMP50

ACCESSORY



## **WORKSHOP MATE**



# Workshop Press 20,000KG

1061T TRADEQUIP

Safe working capacity: 20,000kg Working range: 60-773mm Overall height: 1503mm Overall width: 705mm Overall depth: 660mm

Bed width: 504mm

BARRIER AWAILABLE SEPARATELY

Bed gap: 103mm Bed inside: 285 x 103mm Press head diameter: 40mm Press head length: 68mm Jacking handle: 694mm Piston ram stroke: 160mm



#### **FEATURES**

High-grade Channel Steel Hydraulics are powered with a high

quality oil.
Integrated overload protection valve keeps from overloading the system Lead-free paint finish is oil, grease and dirt-resistant for easy cleanup and to help prevent rust.



Inc. GST \$625.90

## **Workshop Press** 30,000KG

1062T TRADEQUIP

Safe working capacity: 30,000kg Working range: 45-705mm Overall height: 1605mm Overall width: 745mm BARRIER Overall depth: 660mm AVAILABLE Bed width: 480mm SEPARATELY Bed gap: 124mm Bed inside: 254 x 124mm Press head diameter: 50mm Press head length: 68mm Jacking handle: 694mm



Piston ram stroke: 163mm

Weiaht: 113ka

#### FFATURES

High-grade Channel Steel Hydraulics are powered with a high Integrated overload protection valve keeps from overloading the system.

Lead-free paint finish is oil, grease and dirt-resistant for easy cleanup and to help prevent rust.



## **Hydraulic Workshop** Press 20,000KG

1063T TRADEQUIP

Safe working capacity: 20,000kg Working range: 43-882mm Overall height: 1795mm Overall width: 780mm Overall depth: 690mm Bed width: 505mm Bed gap: 105mm Bed Inside: 358 x 105mm Press head cap diam: 45mm Press head cap length: 17mm Ram lateral adjustment: 180mm Piston ram stroke: 185mm Weight: 90kg

#### **FEATURES**

High-grade Channel Steel. 100mm pressure gauge. High quality large diameter hydraulic steel cylinder unit.

Hydraulics are powered with a high

quality oil.

Integrated overload protection valve keeps from overloading the system. Lead-free paint finish is oil, grease and dirt-resistant for easy cleanup and to help prevent rust.

#### **Lateral Ram Adjustment**





**Hydraulic Workshop** Press 30,000KG

1064T TRADEQUIP

Working range: 50-1030mm Overall height: 1950mm Overall width: 830mm Overall depth: 660mm Bed width: 455mm Bed gap: 154mm Bed inside: 230 x 154mm Press head diameter: 56mm Load cap length: 17mm Jacking Handle: 639mm Ram lateral adjustment: 70mm Piston ram stroke: 170mm

## Weight: 138kg

FEATURES
High-grade Channel Steel.
100mm pressure gauge.
High quality large diameter hydraulic steel cylinder unit. Hydraulics are powered with a high quality oil.
Integrated overload protection valve

keeps from overloading the system. Lead-free paint finish is oil, grease and dirt-resistant for easy cleanup and to help prevent rust.


#### **Lateral Ram Adjustment**





## **Hydraulic Workshop** Press 45,000KG WIDE

2036T TRADEQUIP



Piston ram stroke: 190mm Ram diameter: 90mm 1707H x 1420W x 826Dmm Bed height settings: 6 Weight: 296kg



#### **FEATURES**

High-grade steel frame. 100mm pressure gauge. Bed winch for easy raise and lower adjustment. Lead-free paint finish is oil, grease and dirt-resistant Hand winch for fast adjustment.



SAFETY

BARRIER

HEIGH











Bed internal: 390 x 200mm

Safe working capacity: 50,000kg

Working range: 137-837mm

Bed outside: 356mm

Bed inside: 210mm

Bed width: 713mm

HEIGHT

#### Hydraulic Workshop Press 50,000KG 2048T TRADEQUIP

TO TRADEQUIP

Ram diameter: 95mm Op. air pressure: 110-125 psi 1700H x 1290W x 745Dmm Bed height settings: 6 Weight: 271kg





SVIIIN BARRIER SEPARATELY



TO TRADEQUIP

#### **FEATURES**

Heavy-duty high-grade steel frame. Hand operated air trigger ram travel control. 100mm pressure gauge. Polished pneumatic aluminium air motor. Bed winch for easy raise and lower adjustment.
Lead-free paint finish helps prevent rust& is oil grease and dirt-resistant. High quality large diameter hydraulic unit. Hand winch for fast height adjustments.



## Air/Hydraulic Workshop Press 45,000KG WIDE

2038T TRADEQUIP

Safe working capacity: 45,000kg Working range: 159-859mm Bed outside: 359mm Bed inside: 195mm Bed width: 826mm Piston ram stroke: 190mm Ram diameter: 90mm Op. air pressure: 110-125 psi 1707H x 1420W x 800Dmm Bed height settings: 6 Weight: 301kg

#### AIR OPERATED

#### **FEATURES**

High-grade steel frame 2 speed pump. 100mm pressure gauge.
Bed winch for easy raise and lower adjustment.
Paint is oil, grease and dirtresistant for easy cleanup. High quality large diameter hydraulic steel cylinder unit. Piston-ram is treated, polished. Includes hand winch. Integrated overload protection valve prevents overloading.

Extra-long handle included for easy pumping force.

Double spring ram return for



fast ram retraction



TO TRADEQUIP

## **Workshop Press Adaptor Kit**

BPAK /= BORUM

Includes 8 different sized pins (mandrels) ranging from 2,000kg to 20,000kg capacity, a pin holder, a storage shelf along with a mounting kit, and a pin plate with the weight capacity shown for each pin. This very handy set of eight steel mandrels,

adaptor and press plate expands the uses of your workshop press for a wider range of applications involving different sized work pieces.





Mandrel Length x Diameter 50mm x 10mm

60mm x 12mm 60mm x 16mm 85mm x 18mm

85mm x 20mm 85mm x 22mm 15mm x 25mm

110mm x 30mm



\*\*\*UNLESS STATED OTHERWISE, ALL TQB BRANDS PRODUCTS, EXCLUDING CONSUMABLES, COME WITH A 12 MONTH COMMERCIAL USE WARRANTY AGAINST MANUFACTURING DEFECTS. THE BONUS 12 MONTH WARRANTY OFFERED EXCLUSIVELY IN



30,000kg <u>capacit</u>

LATEST APPLIED

- ✓ Mandrel Kit Included
- ✓ Long Pump Handle
- ✓ Premium Bed Blocks
- ✓ Winch Adjustable Bed
- ✓ Premium Hydraulic System
- ✓ Premium Paint Finish
- ✓ Precision Lateral Ram Adjustment
- **Premium Grade Steel Construction**
- ✓ Designed for maximum strength, reliability and durability

✓ Foot Pedal Air/Hydraulic Operation



EPROP30TE

LATEST APPLIED TECHNOLOGIES Profession Reputable Outstanding

30,000kg Capacity

#### **FEATURES**

Excludes GS1

GST \$3298.90

TEL RUNC

Heavy-duty high-grade steel H-frame Integrated overload protection valve. Foot & Hand operated pump. 100mm pressure gauge.
STEEL SAFETY MESH BARRIER Lead free paint finish is oil, grease and dirt-resistant for easy cleanup. Piston-ram is fitted with backup ring, preventing bypass oil drift. High quality hydraulic oil offers better corrosion resistance and flexibility. Pair of bed plates included.

Inc. GST \$3738.90







#### Air/Hydraulic **Workshop Press** 50,000KG

#### PROSHPR50TA

Safe working capacity: 50,000kg Working range: 80-780mm Screw adjustment: 75mm Bed inside: 200mm Bed outside: 220mm BARRIER AVAILABLE Bed width: 750mm Ram diameter: 68mm

Bed height settings: 6 1900H x 930W x 535Dmm Weight: 243kg









## Electric Workshop Press 50,000KG

#### **EPROP50TE**

Safe working capacity: 50,000kg Working range: 80-780mm Screw adjustment: 75mm Bed inside: 200mm Bed outside: 220mm Bed width: 750mm Ram diameter: 68mm Bed height settings: 6 1900H x 1240W x 535Dmm Weight: 243kg

LATEST APPLIED TECHNOLOGIES

#### **FEATURES**

Heavy-duty high-grade steel H-frame. Integrated overload protection valve. Foot & Hand operated pump.

100mm pressure gauge STEEL SAFETY MESH BARRIER

Lead free paint finish is oil, grease and dirt-resistant for easy cleanup.
Piston-ram is fitted with backup

ring, preventing bypass oil drift. High quality hydraulic oil offers better corrosion resistance and flexibility.
Pair of bed plates included.

Inc. GST \$5058.90



#### Air/Hydraulic Workshop Press 75,000KG Air/Hydraulic Workshop Press 100,000KG BSP75TA /= BORUM

Safe working capacity: 75,000kg Working range: 170-884mm Overall height: 1925mm Overall width: 1340mm Overall depth: 800mm Bed width: 800mm

Bed surface depth: 279mm

Piston ram stroke: 250mm Ram diameter: 125mm Width between side posts: 217mm Bed height settings: 8 Operating air pressure: 110-125psi

Air inlet: 1/4"NPT Weight: 451kg 8 HEIGHT

Power to safely remove & install bearings, gears, U-joints, bushings, ball joints and pulleys with precision and versatility!



## BSP100TA /= BORUM

Safe working capacity: 100,000kg Working range: 113-813mm Overall height: 1848mm Overall width: 1250mm Overall depth: 990mm Bed width: 787mm Bed surface depth: 342mm

Piston ram stroke: 300mm Ram diameter: 140mm Width between side posts: 268mm Bed height settings: 6 Operating air pressure: 110-125psi

Air inlet: 1/4"NPT Weight: 652kg

Ideal for straightening, stamping, bending and pressing any component that is difficult to handle.



6 HEIGHT

SETTINGS



- Heavy-duty H-frame constructed of high-grade steel and built to exacting standards for quality and durability.

  Foot operated air trigger ram travel control. 100mm pressure gauge. Extra tall working range for versatility. Pair of bed plates included
- Table winch system lowers or raises the bed. Integrated overload protection valve keeps from overloading the system.
- High quality large diameter hydraulic steel cylinder unit results in lower oil pressure needed to raise the load, helping to reduce wear and extend service life.
- Piston-ram is treated and polished and fitted with backup ring, preventing load from falling slowly or bypassing oil drift.

  Hydraulics are powered with a high quality oil, which offers better corrosion resistance & high/low temperature flexibility, allowing the unit to operate at temperatures.
- Léad-free paint finish is applied after a thórough chemical wash to ensure a long-lasting finish to help prevent rust & is oil, grease, & dirt-resistant for easy clean up.

UNILESS STATED OTHERWISE, ALL TOB BRANDS PRODUCTS, EXCLUDING CONSUMABLES, COME WITH A 12 MONTH COMMERCIAL USE WARRANTY AGAINST MANUFACTURING DEFECTS. THE BONUS 12 MONTH WARRANTY OFFERED EXCLUSIVELY IN

## PRESS/PULL ACCESSORIES

# Polycarbonate TQB Shop Press Safety Barrier

TRADEQUIP

SUIT TQB BRANDS PRESSES ONLY



Multiple Height Settings

**SGUARD-1** 

SGUARD-2

**SUIT 1064T** 

PRESS GUARD
POLY CARBONATE

PRESS GUARD POLY CARBONATE SUIT 1061/1062/1063T



PRESS GUARD POLY CARBONATE SUIT BSP75TA Excludes GST **\$259** Inc. GST \$273.90

SGUARD-4

PRESS GUARD POLY CARBONATE SUIT 2038T/ 2036T/BSP100TA

Excludes GST \$315
Inc. GST \$346.50

\* \* \* \* AVAILABLE IN FOUR DIFFERENT SIZES \* \* \* \*



#### Master Press & Pull Set 28 Piece

9028T TRADEQUIP

4 x Step plates: 74, 76, 78, 80mm 4 x Pulling spindles with thrust bearings 20 x Press sleeves: 44 x 43; 46 x 36; 48 x 38; 50 x 40; 52 x 42; 54 x 44; 56 x 46; 58 x 48; 60 x 50; 62 x 52; 64 x 54; 66 x 56; 68 x 58; 70 x 60; 72 x 62; 74 x 64; 76 x 66; 78 x 68; 80 x 70; 82 x 72mm Heat-treated forged carbon steel Sturdy Blow Mould Case



MADE FOR THE



#### FWD Wheel Bearing Kit 23 Piece

9029T TRADEQUIP

Hub screw length: 207mm Hub screw drive: 32; 38mm Sleeve external: 76.5 x 65; 86 x 77; 91 x 81.5; 102 x 92mm Drift sizes: 50; 55; 59; 63; 66.5; 70; 71.5; 73; 73.5; 75, 77.5; 81.4; 83.3; 86; 88.4; 102mm Heat-treated forged carbon steel Sturdy Blow Mould Case



Excludes GST **\$229** Inc. GST \$251.90



Universal Press & Pull Sleeve Kit 26 Piece

9024T TRADEQUIP

4 Beams 3 ½" Sleeves 20 Sleeves 11pieces (GOLD) 9 pieces (SILVER)



For removal and installation of bushes, bearings and seals, races, sprockets and pulleys on cars, trucks, off-road construction equipment and machinery



## Hydraulic Gear Puller 23 Piece

9023T TRADEQUIP

Capacity: 10,000kg Bearing Separator: 20-105mm Twin/triple head, beam and legs to build: 100, 150 and 200mm Two and three leg hydraulic pullers with separator capacity: 75-105mm Size: 355L x 195W x 150Hmm

Pulls bearings, timing gears, steering wheels and pulleys on most cars and light trucks





## Universal Press Support Block 30,000KG

9025T TRADEQUIP

Base block: 250 x 200 x 40mm Height adaptor block: 200x70x40mm

Made from Billet aluminium



Excludes GST **\$355**Inc. GST \$390.50

For use with a hydraulic shop press for workpieces with a complicated shape to allow bearings to be pressed in or out accurately.





## **MOTORCYCLE LIFTERS**



2102T TRADEQUIP

Safe working capacity: 360kg Height: 205 - 780mm Platform: 490W x 1345Lmm





#### **Motorcycle Scissor** Lift 500KG

2104T TRADEQUIP

Safe working capacity: 500kg Height: 95 - 420mm

Platform dimensions: 450x150mm Weight: 13.8kg

Designed to deliver the ideal lift for use with motorcycles, ATV's, tractors, personal watercraft, and snowmobiles

Lifts back wheel off lift table for tyre/wheel Powder coated structural heavy duty steel

construction. Rotate lead screw to adjust & raise the lift.







## **Motorcycle Lifter 450KG** 2101T TRADEQUIP

Safe working capacity: 450kg Height: 175 - 750mm

Platform: 680W x 2200Lmm Weight: 120kg



Ideal lift for use with motorcycles, ATV's

Powder coated structural heavy duty steel Extra Long Full width loading ramp.

Lockdown bolts to prevent unwanted

movement during use. Does not include tie down straps







tractors, personal watercraft & snowmobiles Locking bar for safety.

Step-less rate of lowering irrespective of load.
Oil trap plate for easy drainage.
2 foot pedals for raising & lowering - for easy

hands free operation.
Fitted with 2 position platform locking device

to prevent accidental lowering.
Quality wheels and swivel castors making it easier to position and move around.





## Motorcycle Lifter Air Actuated 680KG

2103T TRADEQUIP

Safe working capacity: 680kg Height: 185 - 825mm

Platform dimensions: 710 x 2000mm Required air pressure: 0.75-0.85Mpa

Weight: 169kg







#### **FEATURES**

Designed to deliver the ideal lift for use with motorcycles, ATV's, tractors, personal watercraft, and snowmobiles. Locking bar for safety. Extra long full width loading ramp.

Powdercoated structural heavy duty steel Stepless rate of lowering irrespective of the load

Oil trap plate for easy drainage.

Lockdown bolts.

2 foot pedals for raising & lowering - for easy hands free operation. Fitted with 2 position platform locking device





## **PARTS WASHERS**

#### Parts Washer 90 Litre

1003T TRADEQUIP

Pump power: 240V/50Hz/0.5A Pump output: 2.7-3.3 Litres per min. Tank: 758L x 527W x 275Hmm Minimum fluid capacity: 18 Litres Maximum fluid capacity: 45 Litres Size: 780L x 540W x 908Hmm



#### **FEATURES**

Sturdy metal construction and quality enamelled gloss finish.

Enclosed "High Volume" electric pump & fully screened pump housing.

Built-in replaceable pump inlet filter.
Chromed flexible metal fluid delivery

Chromed flexible metal fluid delivery pipe Large removable parts cleaning shelf for inspection and drying.

Immersion soaking when parts cleaning shelf removed.

Non welded one-piece tank with Quick Close fire safe lid mechanism.

Suitable for use with aqueous water based cleaning fluids.

Replacement parts available.



## TRADEQUIP PARTS CLEANERS Code 5083T 5082T

FORMULATED FOR USE IN ALL

NON-TOXIC

**Parts Cleaning Concentrate** 

ENVIRO FRIENDLY

ODEGRADABLE

10 & 20 Litre MADE FOR THE

7@ TRADEQUIP



from Excludes GST \$ 8 9 Inc. GST \$97.90





#### **Parts Washer 180 Litre**

1004T TRADEQUIP

Pump power: 240V/50Hz/0.5A
Pump output: 2.7-3.3 Litres per min.
Tank:1135L x 545W x 320Hmm
Min. fluid capacity: 33 Litres
Max. fluid capacity: 90 Litres
Size: 1150L x 560W x 1430Hmm



#### **FEATURES**

Sturdy metal construction and quality enamelled gloss finish.
Enclosed "High Volume" electric pump & fully screened pump housing.
Built-in replaceable pump inlet filter

Chromed flexible metal fluid delivery pipe.

Large removable parts cleaning shelf for inspection and drying. Immersion soaking when parts cleaning shelf removed.

Non welded one-piece tank with Quick Close fire safe lid mechanism. Suitable for use with aqueous water based cleaning fluids.

Replacement parts available.



# Replacement Parts Washer Pump

1005 TRADEQUIP

Power: 230V 50Hz 26W 0.6Amp Cable length: 305mm Head max: 1.8m

Flowrate: 3.15 litres per minute
Outlet thread: 1/2" NPT Female
100L x 85H x 65W mm

WARNING: ONLY SUITABLE FOR USE WITH WATER BASED SOLUTIONS

Parts Washer Brush & Hose

1806 TRADEQUIP

Long life 70mm synthetic bristles
Polypropylene handle
Stepped hose fitting suitable for connecting
to 13mm and 16mm spouts
Suits TradeQuip parts washers
1003T, 1004T & 1050

Stiff bristles are ideal for cleaning automotive and machined parts

Excludes GST \$28
Inc. GST 30.80
WARNING: ONLY

WARNING: ONLY SUITABLE FOR USE WITH WATER BASED SOLUTIONS



\$85 Inc. GST \$93.50

MADE FOR THE

#### **FEATURES**

Sturdy poly/plastic body. Stainless steel shaft.
Suits parts washers with chromed flexible metal fluid delivery pipes.
Snap off inlet grill for easy cleaning.

Snap off inlet grill for easy cleaning.
Suitable for use with aqueous water based cleaning fluids.
Works with TradeQuip parts washers (Code/s 1003T, 1004T and 1050, sold separately)

## **ULTRASONIC CLEANERS**

# DESIGNED FOR AUTOMOTIVE EINDUSTRIAL APPLICATION

DON'T BE FOOLED BY CHEAPER IMITATIONS THAT ARE DESIGNED FOR DENTISTRY, MODEL BUILDING, OPTOMETRY & LIGHTER DUTIES

#### 6 Litres TRADEQUIP

Capacity: 6 Litres Ultrasonic power: 150W Ultrasonic frequency: 40KHz Heating power: 300W Heating temperature: 20-80 C

1036T

Timer range: 0-30 Minutes Tank material: 304 Grade 2mm thick Tank size: 300L x 155W x 150Hmm Size: 330L x 180W x 310Hmm

MADE FOR THE

#### 13 Litres Tradequip

Capacity: 13 Litres Ultrasonic power: 300W Ultrasonic frequency: 40KHz Heating power: 400W Heating temperature: 20-80 C

1037T

Timer range: 0-30 Minutes Tank material: 304 Grade 2mm thick Tank size: 330L x 300W x 150Hmm Size: 360L x 330W x 310Hmm



\* 30 Minute Timer \* Adjustable Temp. Control \* 304 Grade Stainless Steel Tank



CLEANING FLUID OPTION

AVAILABLE

SEE PAGE 26



#### 27 Litres TRADEQUIP

Capacity: 27 Litres Ultrasonic power: 500W Ultrasonic frequency: 40KHz Heating power: 500W Heating temperature: 20-80 C Timer range: 0-30 Minutes
Tank material: 304 Grade 2mm thick
Tank size: 500L x 300W x 200Hmm
Size: 550L x 330W x 360Hmm

1038T

## 36 Litres TRADEQUIP

Capacity: 36 Litres Ultrasonic power: 600W (adjustable) Ultrasonic frequency: 28/40KHz Heating power: 800W Heating temperature: 20-80 C

Timer range: 0-30 Minutes Tank material: 304 Grade 2mm thick Tank size: 500L x 290W x 250Hmm Size: 570L x 360W x 450Hmm

1039T



LARGER SIZES AVAILABLE FOR SPECIAL ORDER.
PLEASE ENQUIRE WITH YOUR PREFERRED DISTRIBUTOR.

## **PORTER POWER**

#### Hydraulic Ram Kit 2011T TO TRADEQUIP

Blow mould carry case: 530 x 500 x 110mm Weight: 24kg





INDUSTRIA

GUALITY

Inc. GST \$1582.90

Set Includes: 4 x Hooks - 2 Large and 2 Small 2,000kg Mini Ram - Compressed 139mm > Stroke 76mm 4,000kg Mini Ram - Compressed 42mm > Stroke 16mm 10,000kg Mini Ram - Compressed 118mm > Stroke 60mm 4,000kg Porta Power Ram - Compressed 276mm > Stroke 132mm 10,000kg Porta Power Ram - Compressed 350mm > Stroke 150mm 2,000kg Pull Back Ram - Extended 537mm > Stroke 128mm 5,000kg Pull Back Ram - Extended 613mm > Stroke 128mm

## **Porta Power Kit** BPP20T = BORUM

Safe working capacity: 20,000kg Extension tubes: 125, 255, 510, 700mm 3 each. 70mm connective tube & 60mm joint connector tube Base, Ram toe, Plunger toe Wedge toe, V-base, Wrench Retracted ram length: 285mm Ram stroke: 125mm Hydraulic hose length: 1470mm Weight: 62kg

#### **FEATURES**

Constructed of high-grade steel and built to exacting standards for quality and durability. Lead-free paint finish is oil, grease and dirtresistant for easy cleanup.
High quality hydraulic steel cylinder unit helps right quanty hydraulis steet dynitider thin riesps to reduce wear and extend service life. Piston-ram is treated and polished. Hydraulics are powered with a high quality oil, which offers better corrosion resistance and high/low temperature flexibility. Heavy walled extension tubes.





# Air/Hydraulic Pump MADE FOR THE

2054T TRADEQUIP Maximum output pressure: 10,000psi

Usable hydraulic fluid capacity: 2.25 Litres Operating air pressure: 90-145 psi Air consumption: 7.5CFM @ 100 psi Oil delivery with No Load: 49.5 cu.in/min Oil delivery with Load: 7.6 cu.in/min Input (Air) port thread: 1/4" -18 NPT Output (Óil) port thread: 3/8" -18 NPT

#### FEATURES

Durable light-weight corrosion-free aluminium. Built-in overload system prevents pump from being used beyond its safety capacity. Ergonomic hand/foot activation lever. Air/oil filters minimise contaminants in hydraulic system.
Perfect for porta power rams & bead breakers.
Compact design fits in truck storage boxes. Air exhaust muffler for quiet operation

EH-8206F Hose to suit - \$189 ex gst \$207.90 inc gst Inc. GST \$801.90

# Excludes

#### Porta Power Kit 2010T TATRADEQUIP

Safe working capacity: 10,000kg 14 Piece Kit containing pump and hose fittings

Ram length retracted: 322mm Ram length extended: 452mm Extensions: 110,265,365,520mm Case: 905L x 385W x 175H mm Hydraulic hose length: 1500mm Hydraulic oil capacity: 650ml Adaptor diameter: 33mm Weight: 31ka



#### FEATURES

Spring loaded ram return system, allowing controlled retraction of the ram.

Pump may be used in horizontal & vertical position.

Constructed of high-grade steel and built to exacting standards for quality and durability.

Lead-free paint finish is oil, grease and dirt-resistant.

Pump has an automatic overload system.

Easily adapts to hoses, rams, pumps, spreaders, and other accessories using common 1/4" fittings

Inc. GST \$530.20

## Combi Portable Bead Breaker 5,000KG

BTBB05 /= B O R U M

Working load limit: 5,000kg Pressure connection: 3/8"-18NPTF Rated pressure: 10,000psi

Maximum rim size: 26 Suits 1,2 & 3 pce rims (up to 26")

with pry bar / bead loosening pockets Ram stroke: 90mm

INDUSTRIAL QUALITY

#### Durable steel construction Clamps to wheel rim & breaks bead simply with up to 5,000kg of force. Requires 10,000psi air/hydraulic

FEATURES

pump (sold seperately).

## Giant Portable Bead Breaker 13,000KG

BTBB13 F= BORUM

Working load limit: 13,000kg Pressure connection: 3/8"-18NPTF Rated pressure: 10,000psi Suits 5 pce rims 635-1,295mm (25"-51")

with pry bar / bead loosening pockets Maximum rim size: 26"

Ram stroke: 105mm

#### FFATURES

Economical solution for earthmover wheels 25" – 51" multi-piece rims with pry bar pockets.

Hydraulically clamps on wheel.

Durable steel construction.

Hydraulic power breaks beads in seconds. Requires 10,000psi air/hydraulic pump (sold seperately)

Inc. GST \$878.90







## **SANDBLASTING**

#### **Blasting Cabinet 220 Litre Capacity**

MADE FOR THE

3051 TATRADEQUIP

Cabinet capacity: 220 Litre Working pressure: 60-110psi

Maximum media capacity: 20kg 4 Ceramic nozzle tips: 4, 5, 6 & 7mm With gun & low voltage internal fluorescent light

Tempered glass view window: 250 x 525mm External size: 1400H x 890L x 550Wmm







Freestanding floor model. Complete with gun and low voltage internal fluorescent light. Tempered glass viewing window with

Protective shields.
Cabinet fitted and ready to be used with a workshop vac as dust collection system. Spare parts available in Australia



Tempered

Side

opening

door

## **Blasting Cabinet 420 Litre Capacity**

3036T TRADEQUIP

Cabinet capacity: 420 Litre Air regulator & gauge panel 4 Ceramic nozzles: 2x5mm, 2x6mm Maximum media capacity: 70kg Maximum air pressure: 125psi Required air supply: 15-25CFM 14 gauge steel legs & 16 gauge panels Sand blasting efficiency: 100cm²/min Optimum operating pressure 60-110psi External size: 1680H x 1180W x 940Dmm



Oversized hinged top door opening Includes 240V dust extraction system



Includes blasting gun and vinyl blaster gloves

#### **FFATURES**

Perfect for surface preparation on any type where other forms of preparation are difficult.

are difficult.
Ideal for removing paint, rust, scale and oxidation.
Large viewing window gives the operator a wide viewing area.
Oversized hinged top door opening & large inside work area allows easy maneuverability.
Hinged door on hopper allows for easy abrasive changes

abrasive changes.
Fluorescent light kit and 90CFM dust collector help the operator to maintain a

collector neight re operator to maintain good visual.

Rear-mounted dust collector.

Replaceable protective window.Footpedal-controlled siphon blast gun.





## **Soda/Sand Blasting Hood**

3053 TRADEQUIP

Durable fabric & synthetic-leather construction Large 110mm x 55mm acrylic viewing plate Adjustable internal helmet for added comfort Reinforced side ventilation panels for increased airflow

#### **FEATURES**

Protect eyes and face from "rebounding" abrasive particles by wearing Abrasive Blasting Hood. Ideal for many abrasive blasting applications





## **BLASTING MEDIA ABRASIVE**

TradeQuip "Made for the Trade" Blasting Media Abrasives are designed for use in conjunction with our TradeQuip Mobile Blasting Kits and Blasting Cabinets. Abrasive blasting has been used for many years to clean and remove rust, paint and corrosion. There are many types of abrasive media available, the most common being Garnet, Steel Grit and Glass Bead. These media have an aggressive cut and can rapidly remove paint and rust. However, they can also generate significant heat, potentially resulting in warped metal and etched surfaces, and they cannot be used on fibreglass. Also, chrome, plastic, rubber, trim, and other parts must be removed from a work surface or masked-off before blasting.

Alternatively, less-aggressive media, such as Walnut Shell, will do a great job at removing paint. Walnut Shell does not generate as much heat as other media, and can be used on sheet metal and fibreglass without damaging the base material. However, Walnut Shell as with any abrasive media, will require more clean-up as it leaves particles in the car body's seams and crevices that can be difficult to completely remove. Soda blasting media has non abrasive properties which makes it a very universal blasting media which can

be applied to lighter materials such as aluminium, plastic, fibreglass, wood etc. Soda Blasting does not damage glass, rubber, chrome items if they are left on a vehicle for blasting.

#### GARNET 25KG MEDIUM 30/60 3020T TRADEQUIP

Garnet is a gemstone with excellent naturally abrasive properties.

This hard abrasive is fast-cutting, low-dust producing and low-consuming, excellent for removing tough coatings, paint, rust and mill scale from steel. Garnet also permits precise feathering control. A good general outdoor surface preparation abrasive.



#### WALNUT SHELLS 20KG 6-100 MICRON 3022T TRADEQUIP

Walnut Nut shells and other organic materials, don't cause anchor patterns, making them useful for removing dirt, grease, oil, carbon, scale, burrs and paint without changing the underlying substrate. Walnut shells can be an excellent choice for softer surfaces such as wood — they won't cause etching. Walnut shells are one of less abrasive blasting media you can use and are completely biodegrad able, making them among the most environmentally-friendly



#### **GARNET 25KG COARSE 20/40** 3023T TRADEQUIP

Garnet is a gemstone with excellent naturally abrasive properties. This hard abrasive is fast-cutting, low-dust producing and low-consuming, excellent for removing tough coatings, paint, rust and mill scale from steel. Garnet also permits precise feathering control. A good general outdoor surface preparation abrasive.



#### GLASS BEAD 25KG 106-300MICRON 3025T TARADEQUIP

Glass beads are used for general cleaning, peening and cosmetic finishing of sensitive metal surfaces; removing automotive paint; brightening grout and removing fungus and calcium deposits from tile; polishing cast iron, stainless steel, aluminium, propellers and turbine blades. Glass Beads are environmentally friendly and can be used in many blast applications to provide a finish with no profile Use while working with metal, plastic or rubber materials to clean



## Mobile Blasting Kit 37 Litre Capacity

3008 TRADEQUIP

Tank capacity: 37 Litre Working pressure: 60-125psi Air delivery: 400-600 Ltr p/min. @ 125psi (dependent on nozzle size) 4 ceramic nozzle tips: 2.0 2.5 3.0 3.5mm Hose length: 2.4M

508H x 305Ø MADE FOR TH



Inc. GST \$346.50

#### **FEATURES**

Heavy duty welded steel design. High volume extra large valve.

Designed for high flow with minimal air input.

Blast gun fitted with safety trigger. Heavy-wall blast hose. Durable wheels Safety pressure-relief valve. Safety mask, thread tape and refill funnel. Onboard pressure regulator. Easy to fill screw tank cap.



## **CRANS & SUPPORTS**



Foldable Engine Crane 1,200KG

1001T TRADEQUIP

Safe working max. capacity: 1200kg (AS1418.5 approved)

(AS 1416.5 approved)
Adjustable boom: 250kg, 500kg, 750kg & 1200kg
Max. lifting height @ 1200kg: 620mm
Max. lifting height @ 250kg: 1160mm
Jib length fully retracted @ 1200kg: 1040mm
Jib length fully extended @ 250kg: 1580mm

Leg height: 190mm

Ideal for automotive & light engineering. Adjustable boom in four positions. Outrigger legs easily fold up for storage. Six swivel castor wheels.

High-grade steel and built to exacting standards for quality and durability.

Short lifting chain & hook with safety latch. Lead-free paint is oil, grease and dirt-resistant for easy cleanup.



## **Engine Crane** Load Leveller

1030 TRADEQUIP

Safe working capacity: 680kg Chain length: 300mm Chain anchor positions: 3 Engine mount positions: 4 Weight: 6kg





## **Engine Support Bar** 1019T TRADEQUIP

Safe working capacity: 500kg Extension: 1020 - 1600mm Weight: 15kg

Adjusts to fit across most car bonnets Supports engines or transmissions. Powder coat finish.

Adjustment screw for load leveling.

Supplied with short length of chain



Excludes GS1 Inc. GST \$195.80

## Ram to Suit TradeQuip 1001T Engine Crane

0861

2008 TRADEQUIP

Safe working capacity: 8,000kg Length: 630-1135mm

Ram pin hole: 16mm dia. 35mm Outside ram Ram diameter: 80mm

Clevis base pin hole: 16mm dia Clevis base: 25mm inside - 45mm outside

Base width: 129mm Weight: 10.5kg



Inc. GST \$189.20

**Capacit** 

## **Engine Support Bar**

1021T TO TRADEQUIP

Safe working capacity: 500kg Extension: 1020 - 1630mm Weight: 23kg



#### **FEATURES**

Cross bar feature for improved stability and more flexibility.

Dual hook assemblies for balanced support of engines & transmission High gloss enamel finish. Adjustment screw for leveling.

Inc. GST \$280.50



## **Engine Support Bar**

1020T TRADEQUIP

Safe working capacity: 500kg Extension: 1020- 1430mm Weight: 19kg diustable

#### **FEATURES**

Dual hook assemblies for balanced support. Adjustable to fit across most car bonnets. Supports engines or transmissions Rubber cushioned support legs. High gloss enamel finish. Adjustment screw for load leveling.
Supplied with a short length of chain.



## **CRANS & SUPPORTS**



# Engine Crane 3,000KG 1193 TRADEQUIP The State of the state of the specific and the specific

Safe working capacity: 3000kg
Adjustable boom: 1000kg, 1500kg, 2000kg & 3000kg
Maximum lifting height @ 3000kg: 1745mm
Maximum lifting height @ 1000kg: 2088mm
Jib length fully retracted @ 3000kg: 1100mm
Jib length fully extended @ 1000kg: 1730mm Leg height 190mm

#### FEATURES

This heavy duty TradeQuip "Made for the Trade<sup>n</sup> engine crane has a long stroke lifting ram, a single action pump with a maximum load capacity of 3,000kg.

Very simple to use manual hydraulic operation. The jib extends to the desired lifting capacity of 1000kg, 2000kg or 3000kg secured by a single locking pin.

Mounted on heavy duty castor wheels for excellent manoeuvrability around the workshop.





1894T TRADEQUIP

Safe Working Capacity: 4/5/6/V6 cylinder less than 4ltr Rated capacity: 500kg 360° rotating head 1190L x 850W x 1230H mm Weight: 54kg

Inc. GST \$907.50

**WORM GEAR HEAD DRIVE** STURDY REINFORCED **NECK** 

#### **IMPORTANT:** ENGINE DIMENSIONS

MUST BE WITHIN LEGS OF ENGINE STAND



Removable legs

#### **Engine Stand** 1891T TRADEQUIP

Safe working capacity: 4 cylinder & V6/V8 less than 5ltr Rated capacity: 680kg 360° rotating head Centre height: 895mm 870L x 800W x 900H mm Weight: 39kg



Inc. GST \$303.60



Inc. GST \$152.90

MODEL RUNOUT

360°

rotating

## **Engine Stand**

TQES450 TRADEQUIP

Safe working capacity: 4cylinder engine only Rated capacity: 450kg 360° rotating head Centre height: 780mm 700L x 750W x 860H mm Weight: 21kg

**SPACE SAVING** COMPACT DESIGN **EASY SETUP &** DISASSEMBLY



## **Engine Stand**

1192T TRADEQUIP

Safe working capacity: 4/5/6/V6/V8 Cylinder less than 6.2ltr Rated capacity: 900kg 360° rotating head Centre height: 800mm 1110L x 530W x 900H mm Weight: 45kg



**FOLDING LEGS** STURDY REINFORCED **NECK AND** STABLE WIDE BASE

## **IMPORTANT:**

**ENGINE DIMENSIONS** MUST BE WITHIN LEGS OF ENGINE STAND

ADE FOR THE

**Excludes GST** Inc. GST \$379.50

ALL TRADEQUIP ENGINE STANDS ARE INTENDED FOR PASSENGER AND LIGHT COMMERICAL VEHICLES ONLY



#### Steel Workbench

1014T TATRADEQUIP

Safe working capacity: 90kg Work surface: 1510x700mm Raised edge height: 50mm 1520L x 710W x 830Hmm Weight: 48kg

#### FEATURES

Sturdy steel construction. High gloss enamel paint finish Raised protective edge to work surface Adjustable feet for levelling on uneven floors. Quick and easy to assemble.

Easily wipe dirt and grime from surface with a soft cloth.

50mm 1520mm

#### 3 Drawer Steel Workbench

1012T TRADEQUIP

Safe working capacity: 300kg Heavy duty steel construction High gloss enamel paint finish Includes bottom shelf & 3 locking drawers Each drawer holds up to 50kg 2000L x 860H x 640Wmm

Manufactured from high quality, heavy-duty steel and features a large surface for more work space and an extended lip around the surface of the table.

The tough high gloss enamel paint finish is designed to provide years of protection against normal wear and tear.

2000mm





#### Mobile Workbench

6047 TRADEQUIP
the trusted brand in equipment Safe working capacity: 250kg Bench top capacity: 150kg

Bench top: 1200L x 640Wmm 1200L x 640W x 875H mm Shelf: 1110L x 460Wmm Shelf capacity: 100kg Weight: 56.5kg

## MADE FOR THE Inc. GST \$812.90 1200mm

**Mobile Bench** 1073T TRADEQUIP

Safe working capacity: 300kg Work surface: 1100 x 700mm 1100L x 700W x 830H mm Weight: 60kg

#### **FEATURES**

Sturdy steel construction. High gloss enamel finish. Heavy-duty handle Quality castors - two fixed & two locking swivel.

1100mm

## **FEATURES**

Heavy duty rolled edge steel construction. Convenient removable drain bowl. 13mm benchtop rim to contain leaking fluids when working on engines and transmissions. Quality castors (2 swivel with brake). Lockable steel drawer

with ball bearing slides. High gloss enamel finish



TRADE



## 22 Bin Parts Storage Rack

6053 TRADEQUIP

MADE FOR THE Working load capacity: 100kg 15 parts bins: 345x105x75mm (3kg load capacity) 4 parts bins: 345x140x150mm (5kg load capacity) parts bins: 345 x 205 x 150mm (8kg load capacity)

Swivel castor diameter: 100mm



## 36 Bin Parts Storage Rack

6054 TRADEQUIP Working load capacity: 200kg

15 parts bins: 345x105x75mm (3kg load lapacity) 12 parts bins: 345x140x150mm (5kg load lapacity) 9 parts bins: 345 x 205 x 150mm (9kg load lapacity)

Swivel castor diameter: 100mm 880L x 410W x 1705Hmm

> MADE FOR THE Excludes GS

Inc. GST \$757.90

#### FEATURES

Sturdy nine-tier steel powder coated rack Zinc plated wire shelving with bin locating guides Quick & easy clip together adjustable shelves. Stackable bins made of moulded polypropylene Ideal for garage, workshop, office, shed Powder coat frame resists corrosion. Quality swivel castors (2x lockable) nient access to removable hins



## **WORKBENCHES & STORAGE**





6056T TRADEQUIP 340x300x45mm drawer Adjustable from 860-1200mm high Includes drawer and top tray liner 80kg Distributed load capacity 730x500x25mm top tray

#### FEATURES

Height adjustable for most vehicles. Ball Bearing wheels for easy moving.
Multi-functional top table with 3 compartments and 6 screwdriver holes. Top EVA mat for skid resistance. Extra drawer for more



## **Truck Mobile Workshop Table**

BMWST Z BORUM Safe working capacity: 34kg

Adjustable working height: 960-1500mm Distance between front casters: 955mm Caster wheel diameter: 75mm Table top: 797L x 695W Main tray: 556L x 695W Depth at full width: 485mm





Height adjustable to most commercial vehicles Smooth rolling casters Extra wide legs to suit commercial vehicles.
Multi-functional top table with 2 compartments and 8 screwdriver

Top EVA mat for skid resistance. Protective bumper for top tray.
Strong tubular steel construction. Sturdy main support post.



#### **Workshop Trolley 2 Drawers** & Lockable Sliding Top

6019T TRADEQUIP

Safe working capacity: 100kg Two lockable drawers & top 100mm composite rubber castors Two 75mm deep shelves 700L x 370W x 760Hmm



Heavy gauge steel construction with lockable sliding top. Quality 35mm ball bearing sliding drawers, which are locked when top is closed. Side handle for comfort/control when moving. Tough enamel finish.

Non slip rubber tool tray liners



Inc. GST \$423.50

Workshop Trolley Single Drawer 6020T TRADEQUIP

Safe working capacity: 155kg Lockable drawer: 635L x 320W x 80Hmm Top storage tray: 695L x 405W x 65Hmm Lower storage tray: 750L x 395W x 68Hmm Rubber castors: 100Dmm

775L x 415D x 890Hmm



Heavy gauge steel construction with lockable drawer on smooth runners. Two top mounted handles for added control when manoeuvring. Tough enamel finish. Non slip EVA foam tool tray liner Two heavy-duty locking swivel casters for control and maneuverability. Large top & bottom shelf giving

TRADEQUIP



with Lockable Top Excludes GST

6052 TRADEQUIP

Safe working capacity: 260kg 4 lockable drawers on 35mm ball bearing slides Two 75mm deep shelves for plenty of storage (one lockable)

Top 2 drawers (each): 310W x 370D x 50Hmm Middle drawer: 680W x 370D x 70Hmm Large drawer: 660W x 370D x 100Hmm

Two swivel and two fixed 100mm smooth rolling composite rubber castors. 850L x 445D x 972Hmm



Heavy gauge steel construction with lockable sliding top on smooth ball bearing runners. Quality ball bearing slide drawers, that lock when top is closed. Side handle for comfort and control when manoeuvring. Tough high gloss enamel finish Non slip rubber tool tray liners Heavy-duty ergonomic grip handle. Two heavy-duty locking castors for control and stability.





## WORKSHOP TROLLEYS



Weight: 22kg 22(5) 30 MADE FOR THE **FEATURES** 

## Workshop Trolley (Polymer)

**Workshop Trolley (Polymer)** 

6042T TRADEQUIP

Smooth rolling rubber castors: 125D x 25Wmm

Safe working capacity: 226kg Tray: 900L x 600W x 65Hmm Tray capacity: 113kg (each)

Ground clearance: 140mm

6043T TRADEQUIP Safe working capacity: 226kg Trav capacity: 76kg (each) Tray: 900L x 600W x 65Hmm

Weiaht: 33.5ka

MADE FOR THE

FFATURES

Two deep and wide shelves for plenty of storage. Convenient push handle. Virtually maintenance free.

Two swivel and two fixed smooth rolling rubber castors

Will not dent, rust or chip. No painting required. Cleans easily.

Smooth rolling rubber castors: 125D x 25Wmm Ground clearance: 140mm

Excludes GST

**Excludes GST** 

Inc. GST \$372.90

Inc. GST \$427.90

## **Workshop Trolley 3 Tool Trays**

6004 TRADEQUIP

Safe working capacity: 150kg Powder coated .6mm steel 100mm composite castors 845L x 410W x 780Hmm

> Excludes GST Inc. GST \$196.90

#### **FEATURES**

This three shelf workshop tool trolley is durable enough for moving tools and car parts. Deep shelves give you plenty of storage for your tools and parts.

Capacity

## **Workshop Trolley 2 Tool** Trays & 1 Drawer

6012T TRADEQUIP

Safe working capacity: 100kg One lockable drawer 100mm composite rubber castors Two 100mm deep shelves 770L x 370W x 830Hmm

> Excludes GST Inc. GST \$295.90

#### **FEATURES**

Heavy gauge steel construction 35mm ball bearing slide drawer. Side handle for comfort and control Tough enamel finish.



## **Workshop Trolley (Polymer)**

Three deep and wide shelves for plenty of storage

Convenient push handle. Virtually maintenance free.
Two swivel and two fixed smooth rolling rubber castors.
Will not dent, rust or chip. No painting required. Cleans easily.



Inc. GST \$416.90

## **FLUID HANDLING**



Excludes GS1

Inc. GST \$449.90

# EDGLE PAO

## **ABOUT EAGLE PRO HYDRAULICS**

With nearly 3 decades experience of manufacturing hydraulic tools for industrial applications, Eagle Pro Hydraulics has become the trusted partners for applications spanning from offshore plant maintenance to mining, infrastructure, commercial and industrial. Eagle Pro Hydraulics are manufactured to ISO 9001:2018 through international quality assurance programs which involve consistent observation of administration, management, manufacturing and production control. Eagle Pro hydraulic cylinders meet or exceed ANSI B30.1. This results in reliable and dependable high-quality products you can count on every time.

## **ES SERIES**

#### Single Acting General Purpose

Eagle Pro ES series redefines durability for the harshest of industrial environments with its high strength alloy steel construction. Hardened and chromed piston ensures superior product life by reducing wear and corrosion.

Eagle Pro ES series is not only durable, it gets the job done! Heavy-duty, straight pull return springs provide fast retraction. For greater flexibility and easy mounting, the ES series comes with collar, multiple piston threads, and base mounting holes. Hardened and E-coated snap-in type saddle prevents piston jamming and mushrooming, practically eliminating downtime. The female coupler comes with a dust cover – preventing dirt and debris from entering the hydraulic system.

The Eagle Pro ES series also complies with ASME B30.1 standard.



## **EDH SERIES**

#### Double Acting Hydraulic

The Eagle Pro EDH series incorporates a hollow piston design that allows both pushing and pulling forces. The construction of high strength alloy steel maximizes durability. The EDH series' double acting operation ensures fast and controlled piston reaction time.

Accidental over-pressurization is prevented with a built-in safety valve. The collar, piston threads, and base mounting holes enable easy fixturing.



## **ED SERIES**

#### Double Acting General Purpose

The Eagle Pro ED series produces fast and controlled piston contraction thanks to the double acting operation.

A built-in safety valve prevents accidental-over pressurization. Most models include collar, piston threads, and base mounting holes to make fixturing a simple task.

Piston jamming and mushrooming is prevented by the cylinder's hardened, and E-coated snap-in saddle. The ED series enhances durability with a hardened and chromed piston that reduces wear and corrosion. ED series cylinders are easy to move around the job site with the addition of carrying handles (and eyebolts on larger models) that ease positioning and carrying. A durable, anti-corrosive finish is added using an environmentally friendly coating process.



## **EAGLE PRO HYDRAULICS**

## **EDX SERIES**

#### Double Acting High Tonnage

Eagle Pro EDX series maximizes durability with the use of a high strength alloy steel. The built-in safety valve prevents accidental over-pressurization. The EDX is easy to carry and position with the included eyebolts. Optional tilt saddles are also available. The hardened and chromed piston minimizes wear and corrosion damage. The incorporation of base mounting holes enables easy fixturing. An environmentally friendly coating process provides a highly durable finish.



## **EL SERIES**

#### Single Acting With Locking Collars

The Eagle Pro EL series includes an alloy steel lock nut for mechanical load holding. The EL series is constructed of a high strength alloy steel to maximize durability. The hardened chrome piston reduces damage caused from wear and corrosion. The over flow port functions as a stroke limiter.

The over flow port functions as a stroke limiter.

The EL series includes hardened grooved replaceable saddles.

Composite bearings prevent metal-to-metal contact. Quick reaction times are obtained through with heavy-duty straight pull return springs. An environmentally friendly coating process produces a finish that further increases durability.



## **ESL SERIES**

#### Low Profile And Pancake Style

Featuring a low-profile, or flat design, the Eagle Pro ESL series cylinder is an optimal choice for confined spaces. The hardened and chromed piston is constructed of high strength alloy steel that increases durability by reducing wear and corrosion.

The grooved piston end does not require a saddle and the inclusion of mounting holes permits easy fixturing.

Retraction time is quick thanks to the heavy duty, straight pull return springs. An environmentally friendly coating process is used to provide the durable anti-corrosion finish.



## **ESH SERIES**

#### Single Acting Hollow Piston

The Eagle Pro ESH Series allows for both pushing and pulling by incorporating a hollow piston design. The heavy-duty return spring provides notoriously quick reaction times. Easy fixturing with the inclusion of collar threads.



## **EPA SERIES**

#### **Dual Speed Hand Pumps**

The Eagle Pro EPA series hydraulic hand pumps are some of the most durable, powerful and reliable hand pumps in the industry today. The EPA series feature valve blocks that are machined from a single piece of high strength aircraft grade aluminum and high capacity reservoirs made from alloy steel\* that maximizes durability. The EPA series hand pumps are compact and easy to carry around the job site. To get the job done faster, these powerful dual speed pumps offer some of the best flow rates in the industry. All of the EPA series hydraulic hand pumps feature an internal safety valve to prevent system damage.



## **EAGLE PRO HYDRAULICS**

# TEAGLE PROPERTIES





			ПΥ	UKA	ULIC	COMPA	HOSE & PUMP ATIBILITY CHART			
	Model	Description	Cylinder Capacity @ 10,000PSI (700 BAR)	Stroke	Cylinder Effective Area	Oil Capacity	Collapsed Height	Extended Height	Price ex GST	Price inc GST
١			Metric Kg	MM	CM <sup>2</sup>	CM <sup>3</sup>	MM	MM		
	ES-50	SINGLE ACTING RAM	5,000	16	7.1	11.4	42	58	\$399.00	\$438.90
	ES-51	SINGLE ACTING RAM	5,000	25	7.1	17.8	110	135	\$489.00	\$537.90
	ES-55	SINGLE ACTING RAM	5,000	127	7.1	90.2	215	342	\$619.00	\$680.90
N	ESL-50	SINGLE ACTING RAM PANCAKE STYLE	5,000	6	7.1	4	33	39	\$389.00	\$427.90
	ES-1010	SINGLE ACTING RAM	10,000	257	14.5	372.65	349	606	\$799.00	\$878.90
	ES-102	SINGLE ACTING RAM	10,000	54	14.5	78.3	121	175	\$489.00	\$537.90
	ES-104	SINGLE ACTING RAM	10,000	105	14.5	152.25	171	276	\$699.00	\$768.90
	ES-106	SINGLE ACTING RAM	10,000	156	14.5	226.2	247	403	\$799.00	\$878.90
	ESL-100	SINGLE ACTING RAM PANCAKE STYLE	10,000	10	14.5	15	42	53	\$569.00	\$625.90
	ESL-101	SINGLE ACTING RAM PANCAKE STYLE	10,000	38	14.4	55	88	126	\$599.00	\$658.90
	ESH-121	SINGLE ACTING RAM HOLLOW PISTON	13,000	42	18.4	77.3	120	162	\$969.00	\$1065.90
	ES-1510	SINGLE ACTING RAM	15,000	254	21.2	538.48	373	627	\$1099.00	\$1208.90
	ES-1514	SINGLE ACTING RAM	15,000	356	21.2	754.72	474	830	\$1199.00	\$1318.90
	ES-152	SINGLE ACTING RAM	15,000	51	21.2	108.12	149	200	\$759.00	\$834.90
١	ES-154	SINGLE ACTING RAM	15,000	101	21.2	214.12	200	301	\$929.00	\$1021.90
	ESH-206	SINGLE ACTING RAM HOLLOW PISTON	20,000	49	32.8	161	162	211	\$1749.00	\$1923.90
	ESL-200	SINGLE ACTING RAM PANCAKE STYLE	20,000	11	28.3	31	51	62	\$699.00	\$768.90
	ESL-201	SINGLE ACTING RAM PANCAKE STYLE	20,000	45	28.3	127	98	143	\$769.00	\$845.90
	ES-251	SINGLE ACTING RAM	25,000	26	33.2	86.32	139	165	\$999.00	\$1098.90
	ES-252	SINGLE ACTING RAM	25,000	50	33.2	166	165	215	\$1079.00	\$1186.90
	ES-254	SINGLE ACTING RAM	25,000	102	33.2	338.64	215	317	\$1179.00	\$1296.90
	ES-256	SINGLE ACTING RAM	25,000	158	33.2	524.56	273	431	\$1349.00	\$1483.90
	ESH-302	SINGLE ACTING RAM HOLLOW PISTON	30,000	64	48	307	179	242	\$1888.00	\$2076.80
	ESH-306	SINGLE ACTING RAM HOLLOW PISTON	30,000	156	48	744	330	485	\$2599.00	\$2858.90
	ESL-300	SINGLE ACTING RAM PANCAKE STYLE	30,000	13	41.8	54	58.5	71	\$1055.00	\$1160.50
	ESL-302	SINGLE ACTING RAM PANCAKE STYLE	30,000	62	41.8	259	117	179	\$979.00	\$1076.90
	EL-506	SINGLE ACTING RAM LOCKING COLLAR	50,000	150	70.8	1062	264	414	\$1929.00	\$2121.90
	ES-502	SINGLE ACTING RAM	50,000	51	70.9	361.59	176	227	\$1229.00	\$1351.90
	ES-506	SINGLE ACTING RAM	50,000	159	70.9	1127.31	282	441	\$1699.00	\$1868.90
١	ESL-500	SINGLE ACTING RAM PANCAKE STYLE	50,000	16	63.6	102	67	83	\$979.00	\$1076.90
	ESL-502	SINGLE ACTING RAM PANCAKE STYLE	50,000	60	63.6	382	122	182	\$1199.00	\$1318.90
	ESH-603	SINGLE ACTING RAM HOLLOW PISTON	60,000	76	87.4	664	247	322	\$3199.00	\$3518.90
	EL-1002	SINGLE ACTING RAM LOCKING COLLAR	100,000	50	132.7	663.5	187	237	\$2399.00	\$2638.90

## **EAGLE PRO HYDRAULICS**

		Cylinder Capacity		Max. Cylin	der Capacity	Cylinder Effective Area		Oil Capacity			
Model	Description	@ 10,000PSI	Stroke	Advance	Retract	Advance	Retract	Advance	Retract	Price	Price
		(700 BAR)								ex GST	inc GST
		Metric Kg	MM	METRIC TON	METRIC TON	CM <sup>2</sup>	CM <sup>2</sup>	CM <sup>3</sup>	CM <sup>3</sup>		
EDX-506	DOUBLE ACTING RAM	50,000	150	53	26	75.4	36.9	1,131	1,131	\$1799.00	\$1978.90
EDX-1006T	DOUBLE ACTING RAM	100,000	150	93	43	132.7	61.9	1,991	928	\$2549.00	\$2803.90
EDH-307	DOUBLE ACTING RAM HOLLOW PISTON	30,000	178	33	22	47.7	32.4	849	577	\$2249.00	\$2473.90
EDH-603	DOUBLE ACTING RAM HOLLOW PISTON	60,000	89	60	39	87.4	56.2	778	481	\$2549.00	\$2803.90
EDH-606	DOUBLE ACTING RAM HOLLOW PISTON	60,000	166	60	39	87.4	56.2	1451	891	\$3199.00	\$3518.90
ED-1012	DOUBLE ACTING RAM	10,000	305	10	3	14.5	4.9	443	149.5	\$1799.00	\$1978.90

					Usable Oil	Pressure	Pressure Rating		ent Per Stroke	Handle		
	Model	Description	Cylinder Type	Speed	Volume	1st Stage	2nd stage	1st Stage	2nd Stage	Force	Price ex GST	Price inc GST
					CM <sup>3</sup>	BAR	BAR	CM <sup>3</sup>	CM <sup>3</sup>	KG	ex 031	IIIC GST
E	EPA-10921A	HAND PUMP, S/A, TWO SPEED, 55 IN3	SINGLE ACTING	TWO	750	25	700	33	3.3	49	\$699.00	\$768.90
E	EPA-12321A	HAND PUMP, S/A, TWO SPEED, 140 IN3	SINGLE ACTING	TWO	2300	25	700	33	3.3	49	\$1019.00	\$1120.90
E	EPA-12322A	HAND PUMP, D/A, TWO SPEED, 140 IN3	DOUBLE ACTING	TWO	2300	25	700	33	3.3	49	\$1349.00	\$1483.90

Model	Description	Internal Diameter	Length	Hose	Working Pressure	Burst Pressure	Hose End (	Configuration	Price	Price	
Model	Description	MM	MM	Material	PSI	PSI	Pump End	Cylinder End	ex GST	inc GST	
EH-8206F	1/4" IDX6' RBR HYDHOSE 3/8" NPT EAB-201B	6	1800	-	10,000	20,000	3/8" NPT	3/8" NPT	\$199.00	\$218.90	

١	Model	Description	Max. Pressure	Typo	Thread	Female Coupler	Male Coupler	Price	Price
Model	Description	PSI	Type		remale coupler	Male Couplet	ex GST	inc GST	
	EAB-201	3/8" MALE/FEMALE HIGH FLOW QUICK	10,000	HIGH FLOW	3/8" - 18NPT	EAB-201A	EAB-201B	\$85.00	\$93.50

Model	Model	Description	Pressure Range		Thread	Gauge Diameter	Price	Price
	Model	Description	PSI	MPa	IN	IN	ex GST	inc GST
	EG-2510	2.5 IN. 15,000 PSI PRESSURE GAUGE	0 - 15,000	0 - 100	1/4" - NPT	2.5	\$239.00	\$262.90

	Model	Description	Male Coupler Thread	Female Coupler Thread	Gauge Port Thread	Price	Price inc GST
			IN/D	IN/E	IN/C	ex GST	
	EGA-005	GAUGE ADAPTOR	3/8" - NPT	3/8" - NPT	1/4" - NPT	\$89.00	\$97.90

	Model	Description	Cylinder Capacity @ 10,000 PSI (700 BAR)	Oil Capacity	Tip Clearance	Maximum Spread Distance	Cylinder Effective Area	Weight	Price ex GST	Price inc GST
			US TON	CM <sup>3</sup>	MM/A	MM/B	CM <sup>2</sup>	KGS		
	EFS-14	14 TON HYDRAULIC SPREADER	14	78.33	6.09	81.02	14.51	7.17	\$2389.00	\$2627.90



## **EVAPORATIVE COOLING**

# PORTABLE EVAPORATIVE COOLING

FIND OUT MORE ABOUT TOB BRANDS LATEST OFFERING HERE....



These **eQuipt Portable Evaporative Cooling** units are specifically designed for smaller workspaces, offering an impressive air flow capacity.

These user-friendly units feature a robust, weather resistant molded polyethylene housing that is both crack- and leak-resistant.

Equipped with a three-speed fan, these coolers efficiently circulate warm air over rigid, water saturated evaporative cooling media, resulting in a notable reduction in ambient temperatures of up to 10°C.

The adjustable swing louvre feature allows for customizable directional air flow, enabling users to tailor the cooled air output to their preferences.







# Portable Evaporative Cooler 150W

E11-0010

240V/50Hz/150W 3 speed motor Max. air flow: 6,000 m³ per hour Water consumption: 4-5 litres per hour Effective cooling area: 45-55sqm Water tank capacity: 45 Litres Dimensions: 1185H x 650W x 430Dmm Weight: 17kg

# **eQuipt**

# Portable Evaporative Cooler 200W

E11-0020

240V/50Hz/200W 3 speed motor Max. air flow: 9,000 m³ per hour Water consumption: 5-6 litres per hour Effective cooling area: 60-70sqm Water tank capacity: 70 Litres Dimensions: 1360H x 820W x 545Dmm Weight: 35kg

# **eQuipt**

# Portable Evaporative Cooler 450W

E11-0030

240V/50Hz/450W 3 speed motor Max. air flow: 12,000 m3 per hour Water consumption: 8-10 litres per hour Effective cooling area: 70-90sqm Water tank capacity: 60 Litres Dimensions 1430H x 900W x 560Dmm Weight: 45kq

#### TOB BRANDS TERMS & CONDITIONS

This is a priced product guide with RTP valid to 31 March 2026. At time of going to print, excluding some new products, stock is plentiful with replenishment stock in production and shipping. At the time that you place your order, your product may not be in stock but an ETA will be provided. Our best efforts are being made to maintain stock levels of products featured in this catalogue, but the situation remains fluid due to bottlenecks in global supply chains. Your preferred distributor will be updated as soon as practical with any information affecting this publication. Products distributed by TQB BRANDS PTY LTD are designed, intended & marketed for trade and commercial use only. Errors and omission excepted.

\*Freight cost may apply on buy-in lines, special order products, none stock lines, large oversize items & in regional areas

\*\*\*Unless stated otherwise, all TQB Brands products, excluding consumables, come with a 12 month commercial use warranty against manufacturing defects. The bonus 12 month warranty offered exclusively in this promotional period applies only to the hydraulic ram and hydraulic pump for "bonus" marked products.

The additional 12 months does not include installation/removal labour or freight for the component.







